



Model: 1204057

## CYNCH-LOK™ Fall Restricting Pole Strap

### Description:

The DBI-Sala® Cynch-Lok™ Fall Restriction Device was developed by linemen for linemen. It is the most user friendly pole climbing device on the market that meets the stringent CSA Z259-14 standard. When used correctly, the Cynch-Lok™ will reduce fall distances in accordance with CSA standards. It is available in distribution and transmission models with interchangeable components for versatility in the field.

### Features & Benefits:

- Lightweight design – at 4.5lbs it's not a burden to carry and use
- Pinch free ergonomic grips
- Cynch-Lok adjustment that easily adapts to the diameter of the pole
- Versatility – distribution and transmission straps are interchangeable
- Abrasion resistance – neoprene impregnated outer strap and protective sleeve on inner rope prolong product life
- Protected labels with I-safe

### Models:

- Cynch-Lok™ Distribution
  - Full Assembly = 1204057
  - Additional/Replacement strap = 1200110
- Cynch-Lok™ Transmission
  - Full Assembly = 1204058
  - Additional/Replacement strap = 1200111

### Specifications:

- Capacity: One user – 350 lbs (140kg)
- Weight
  - 1204057 = 4.5lbs
  - 1200110 = 1.6lbs
  - 1204058 = 5.0lbs
  - 1200111 = 2.1lbs
- Pole Dimension Compatibility (Diameter/Circumference)
  - Distribution – Min = 5.5"/17.5"
  - Distribution – Max = 16.0"/50.0"
  - Transmission – Min = 5.5"/17.5"
  - Transmission – Max = 37"/116"
- Webbing – Neoprene Impregnated Nylon
- Connectors – Alloy steel 5000lbs tensile strength, 3600lb gate strength
- Cynch-Lok Adjustor (turned o-ring) – High strength alloy steel construction with zinc plating for corrosion resistance
- Rope Adjustor – Lightweight Machined aluminum with gold anodized finish
- Stopping Cleat – Heat treated steel with zinc plating for corrosion resistance
- Rope – 10,000 lb tensile strength, Nylon core static kernmantle rope
- Rivets – High alloy stainless steel semi tubular rivets
- Thread – Size 346 Polyester threads
- Standards: Meets CSA Z259.14 Type A; Connectors meet ANSI Z359.1-09

### **Capital Safety**

USA: 800.328.6146 • Canada: 800.387.7484 • Latin America: +1 651.385.4301 • Asia: +65 6558 7758 • Australia: 1800 245 002  
 New Zealand: 0800 212 505 • Europe, Middle East, Africa: +33 (0)4 97 10 00 10 • Northern Europe: +44 (0) 1928 571324  
[www.capitalsafety.com](http://www.capitalsafety.com) • [info@capitalsafety.com](mailto:info@capitalsafety.com)