Innovation in Fall Protection
WestFallPro.com
(573) 355-5470

LOAD PRO™ Double Braid Polyester

Family Code: 1AP • **Manufactured by Pelican Rope Works®**

Designed for use in cable pulling, the highly versatile LOAD PRO combines low-stretch with high-strength. This double braid load line also offers dependability and unsurpassed wet resistance to abrasion. Our optional urethane coating penetrates the fibers of the outer cover, providing additional protection to the inner core, whlle increasing abrasion resistance.

Features & Benefits

- Balanced Core & Cover Design
- Abrasion Resistant
- High Strength
- Torque-Free
- Chafe Guard
- Low Stretch
- Cover: Polyester | Core: Polyester
- Eye Option: Spliced Eye (SE)

Ideal For

Cable Pulling | Distribution & Transmission | Stringing | Winching | Lifting

SKU	Ø (in)	MBS (lbs)	ABS
WF-LL12XXXX	3/8	5,000	5,556
WF-LL16XXXX	1/2	11,000	12,222
WF-LL20XXXX	5/8	17,000	18,333
WF-LL24XXXX	3/4	21,000	23,333

Spools include a 6" eye splice each end with chafe guard.
Optional **Pelican Tuff Coating** avaiable in standard colors:
Yellow, Red, Blue, Green, and Orange

Rope weight per foot:

3/8" = .045 lbs per foot
1/2" = .092lbs per foot
5/8" = .137lbs per foot
3/4" = .183lbs per foot

MIL-SPEC MIL-DTL-24677B Available