



PRODUCT SPECIFICATIONS

LOAD LINE



This highly versatile rope combines low stretch with high strength offering dependability and unsurpassed resistance to abrasion, sunlight and common chemicals. It has a melting point between 489°-500° F and a loss of strength between 244-250° F.

Our optional urethane coating penetrates the fibers of the outer cover providing additional protection to the inner core while increasing abrasion resistance.

Spools include a 6" eye splice each end with chafe guard.

PART	LENGTH	DIAMETER	TENSILE STRENGTH	WEIGHT PER 100'
LL120300	300'	3/8" (10 mm)	5,900 lbs	4.6 lbs
LL160300	300'	1/2" (13 mm)	10,000 lbs	9.2 lbs
LL200300	300'	5/8" (16 mm)	16,000 lbs	13.5 lbs
LL120600	600'	3/8" (10 mm)	5,900 lbs	4.6 lbs
LL160600	600'	1/2" (13 mm)	10,000 lbs	9.2 lbs
LL200600	600'	5/8" (16 mm)	16,000 lbs	13.5 lbs
LL121200	1,200'	3/8" (10 mm)	5,900 lbs	4.6 lbs
LL161200	1,200'	1/2" (13 mm)	10,000 lbs	9.2 lbs
LL201200	1,200'	5/8" (16 mm)	16,000 lbs	13.5 lbs

BENEFITS & FEATURES

- High strength
- Low stretch
- Abrasion resistant
- Balanced core and cover design
- Torque free
- Factory spliced eyes and chafe guard
- Ideal for: cable pulling, stringing lines, winch lines, lifting lines, transmission lines
- Urethane coating available upon request

MATERIAL SPECIFICATIONS

- **Construction:** Double braid
- **Cover:** Polyester
- **Core:** Polyester

For more information visit www.westfallpro.com