

FWLSP

LINE SPECIALTIES

By **GME** Supply Co



THE LINEMAN'S STORE
SUMMER 2023 • FWLSP.COM • 800.466.7153



M-F - 8:00am - 5pm Pacific Standard Time
Closed Saturday and Sunday

TO PLACE YOUR ORDER CALL
1-800-466-7153
You can also order online! WWW.FWLSP.COM

FOR INQUIRIES OR TECHNICAL INFORMATION
Call or e-mail us at support@fwlsp.com

FARWEST LINE SPECIALTIES

830 E. Parkridge Ave. Corona, CA 92879

Toll free phone orders 800-466-7153




In stock items ordered before 2 p.m. will ship same day.

New Products.....	4-10
Boots: Lineman, Work Boots, Lineman Pacs.....	11-16
Belts.....	17-20
Wood Fall Protection and Secondary Straps.....	21-24
Belt Accessories.....	25-28
Positioning Straps.....	28
Harnesses/Lanyards/Rescue Products/Tower Products.....	29-32
Pole Climbers and Climber Accessories.....	33-37
Hand Tools, Tethers and Tool Attachments.....	38-50
Electrical Underground Equipment.....	51-54
Battery Tools, Hydraulic Tools, Impact Drills, Bits.....	55-68
Electrical Test Equipment.....	69-70
Canvas Goods & Bucket Accessories.....	71-76
Hoists/Grips/Hardware/Blocks/Ox Block/Slings.....	77-85
Rope.....	86
Hot Tools, Etc.....	87-72
Work Gloves/Leather Protectors/Rubber Goods.....	93-96
Digging Tools.....	97
Arborist Equipment.....	98-99
Safety Products.....	100-102
Lighting Equipment.....	103-104
FR Raingear and FR Hi-Vis Clothing.....	105-106
FR Clothing.....	107-112
Gifts and Awards.....	113-116
Books/Training Aids.....	117-118

PHONE: Call (800) 466-7153 from 8AM - 4PM (CST) Mon-Fri; 8AM - 1PM (CST) Saturday. Closed Sunday.

WEB: Place your orders online at www.fwslp.com and check out our full line of products with the latest pricing. You can also email us at support@fwslp.com.

SHIPPING: Quick Ship Items  typically ship out the same day for orders placed by 5PM (CST) Monday - Friday.

RETURN AND EXCHANGE POLICY: Click the  button on www.fwslp.com to initiate a return if you're not satisfied with your purchase for any reason within the first 30 days. A 20% restocking fee may apply depending on the manufacturer's terms or if the items are returned without original packaging. Check out our full policy along with our process for freight claims and damaged shipments on www.fwslp.com/shipping.

DISCLAIMER: All photographs, specifications and costs contained in this catalog are based on the latest product information available at the time of the publication. Farwest Line Specialties reserves the right to make changes at any time, without notice or obligation, to all of its products and prices.



**MORE INFORMATION
ON GME.COM/PRO**

- Save money with company pricing online and prompt payment discounts
- Track shipments and expenses at a glance by location, buyer, and more
- Make product selection and approval simple and consistent
- Simplify reordering and budgeting with Gear Lists
- Streamline order requests from the field - one system replaces dozens of calls and emails



AVAILABLE EXCLUSIVELY AT GME SUPPLY www.gme.com | (800) 940-6762

Empower Employee Ordering | Streamline Distribution | Maximize Purchasing Control

- One-Stop-Shop - including FR uniforms, fall protection equipment, PPE, electrical safety, footwear and consumables
- Seamless Spend Control - leveraging approval workflows, vouchers and kitting
- Allow your field staff and management to efficiently order the safety equipment they need while seamlessly implementing spend controls, manager approvals, vouchers and predefined kits



Milwaukee M18 FORCE LOGIC 12T Linear Crimper

Designed to allow one-handed use in multiple orientations. Uses "U" style dies. Includes crimper, 2.0 and 5.0 batteries, charger and bag.

495-2878-22



Milwaukee M18 FUEL Utility Fencing Stapler Kit

Delivers power to seat staples into the toughest utility poles. Designed to be used with Milwaukee 9 gauge staples (sold separately).

495-2843-22

Milwaukee M18 Cordless FORCE LOGIC 6T Latched Linear Utility Crimper Kit

340° rotating head delivers unmatched access into confined spaces. Uses "W" style dies. Includes crimper, qty 2 2.0 batteries, charger and bag.

495-2979-22



Milwaukee Linemans Pliers

MT550T - Linemans Pliers w/ thread cleaner & comfort grip

MT550 - Linemans Pliers w/ comfort grip

MT500T - Linemans Pliers w/ thread cleaner & dipped handles

MT500 - Linemans Pliers w/ dipped handles

MT555 - 8" Long Nose Comfort Grip Pliers



Milwaukee M18 REDLITHIUM HIGH OUTPUT CP3.0 Battery

The M18 REDLITHIUM HIGH OUTPUT CP3.0 Battery Pack provides 50% more power and runs 50% cooler vs M18 REDLITHIUM CP battery packs.

48-11-1835

Milwaukee Hammers

495-48-22-9320 - 21oz

Milled Face Poly/Fiberglass Handle Hammer, 14" Handle

495-48-22-9023 - 22oz

Smooth Face Framing Hammer, Steel I-Beam Handle with SHOCKSHIELD grip

495-48-22-9022 - 22oz

Milled Face Framing Hammer, Steel I-Beam Handle with SHOCKSHIELD grip



495-48-22-9023

495-48-22-9022

495-48-22-9320



Milwaukee M18 FUEL 14 Top Handle Chainsaw

Cuts faster than 35cc gas, delivers the power to cut hardwoods, and eliminates the headaches associated with gas engines. Tool only.

495-2826-20T



Milwaukee M18 FUEL 10 Inch Pole Saw Kit with QUIK-LOK Attachment Capability

Meets the needs of professionals, giving them the power to cut hardwood branches, reach full throttle in under 1 second, and delivers up to 150 cuts per charge. Tool Only.

495-2825-20PS



Klein Tools Step Bit Spiral Double Fluted Kit - 4 Pc

All-Purpose Step Bit Kit with 4 common step bits sizes (1/2, 3/4, 7/8 & 1-3/8") cuts holes in wide variety of applications and materials (up to 16 gauge steel, plastic, aluminum, wood); 1/4" Hex Shank

KT-25950



Klein Tools Step Bit Spiral Double Fluted Kit - 3 Pc

3 step bits sized 7/8, 1-1/8, and 1-3/8-Inch; 1/4" Hex Shank; Ranges: 3/16" to 7/8"; 7/8"-1-1/8"; 7/8"-1-3/8"

KT-25951



Milwaukee Electric Tool Shockwave Lineman's Penta Socket

Designed for use with 13/16" Penta Bolts; deep well; 1/2" square drive.

495-49-66-5133



Milwaukee Lineman's 3-in-1 Transmission Utility Socket

For use with 3/4", 7/8" and 1" Square Headed Machine Bolts; Includes 7/16" Hex to 1/2" Square Adapter for use with 7/16" quick connect chucks

495-49-66-5102



Klein Tools 7-in-1 Impact Flip Socket Set, No Handle

Includes 1/4", 5/16", 11/32", 3/8", 7/16" and 1/2" nut driver sizes.

32907



Klein Tools 2-in-1 Penta/Hex Flip Socket with Adapter

Easy-to-use flip feature allows for quick changes between Penta and Hex socket sizes; 13/16" Penta, 3/4" Hex; 1/2" drive.

66080



PART	DESCRIPTION	LENGTH	WIDTH	WEIGHT	GATE	MBS	CERTIFICATION
7440	WestFall Pro Steel Carabiner	8-5/8"	5-1/8"	1.75 lbs	2"	35 kN	ANSI Z359-12-2009
7430	WestFall Pro Steel Carabiner	7-1/2"	4-1/2"	1.80 lbs	2-1/4"	45 kN	ANSI Z359-12-2009
7425	WestFall Pro Steel Carabiner	7-1/8"	4-1/2"	1.25 lbs	1-1/8"	50 kN	ANSI Z359-12-2009
7420	WestFall Pro Steel Carabiner	7"	3-3/4"	1.00 lbs	1-3/4"	35 kN	ANSI Z359-12-2009
7435	WestFall Pro Aluminum Carabiner	4-3/4"	3"	0.22 lbs	1"	25 kN	ANSI Z359-12-2009
7436	WestFall Pro Aluminum Carabiner	4-7/8"	3-1/8"	0.32 lbs	7/8"	30 kN	ANSI Z359-12-2009
7400	WestFall Pro Steel Carabiner	4-7/8"	3-1/8"	0.28 lbs	1-1/16"	45 kN	ANSI Z359-12-2009
7460	WestFall Pro Aluminum Carabiner	8-5/8"	5-1/8"	1.00 lbs	1-1/5"	25 kN	ANSI Z359-12-2009
7452	WestFall Pro Steel Rebar Hook	9-3/5"	5-3/10"	1.50 lbs	2-1/2"	23 kN	ANSI Z359-12-2009

Buckingham Adjustable 6-D Body Belt

Revolutionary multi-hole D-ring (patent-pending) provides numerous points of connection for both your primary (WPFR) and secondary lanyard(s). The numerous points of connection allow the user to climb, work, and transition in several different configurations.

20122CM1-S - Fits D-Ring Sizes: 20, 21, 22, 23

20122CM1-M - Fits D-Ring Sizes: 23, 24, 25, 26

20122CM1-L - Fits D-Ring Sizes: 26, 27, 28, 29

20122CM1-X - Fits D-Ring Sizes: 29, 30, 31, 32, 33



Buckingham Backpack Pro Gear Bag

Padded back straps; 32" Height, 16" Width; 10" Depth; 11 Total Pockets.

BK-4377



Buckingham Magnet Pouch

Designed to wrap onto 1-3/4" harness webbing or the belt strap; for lanyard parking attachment point or storing hardware.

BK-M4





FallTech APEX Pro Adjustable Wood Pole Fall Restrict Device

Designed for exceptional user experience and performance, allowing you to work smoother and faster.

FH-8180T - For Transmission Poles: Compatible with wood poles measuring 4" to 30" in diameter

FH-8180D - For Distribution Poles: Compatible with wood poles measuring 4" to 18" in diameter



Klein Tools Wide Range Grips

16499 - Transmission Grip; Securely pulls ACSR, AAC and bare copper cables; Holds cable sizes from 0.68" to 1.42".

1647728 - Securely pulls HDPE-coated cable commonly known as tree wire or fire wire; holds cable sizes from 0.162" to 0.883".

1647724 - EHS Jaw holds a wide range of cable from 0.162" to 0.883".



FallTech APEX Pro Adjustable Wood Pole Fall Restrict Device

Designed for exceptional user experience and performance, allowing you to work smoother and faster.


FH-8180SR - FallTech APEX Pro Secondary Rope Positioning Lanyard; 8'



Estex Blue Mesh Duffle Bag

Mesh bag allows air to get to items such as rain gear and harnesses; 10" x 24"

ETX-2608-1024-M



Slingco 3K Strap Hoist

Use to splice, dead end, and sag lines; 1,500lbs single line capacity; 3,000lbs double line capacity

ZLH10504 - (Standard)

ZLH10524 - (Hot Stick Operated)



Milwaukee 75 lb Canvas Utility Bucket w/ Pockets
Rated to 75 lbs; Swiveling Metal Carabiner; 2 Internal Pockets.
495-48-22-8270



Klein Tools Utility Bar Storage Module for S Hooks
10" long bar holds hammers, straps, ropes and other long handled tools
linemen use on a daily basis; requires 2 S-Hooks
KT-BC508S



Ergodyne Arsenal Bucket Truck Tool Board w/ Tool Tethering Attachment Points
Hang from bucket hooks for convenient gear access and prevention of dropped objects;
24" L x 22" H
ED-13699



Klein Tools Hard Tool Storage Module, S-Hook
18 compartments to accommodate a variety of Lineman tools;
Requires (2) S-Hooks (sold separately)
BC501S



Klein Tools Magnetic Tool Storage Module, S-Hook
(4) Rare Earth magnetic plates strong enough to hold metal hand tools and parts; requires (1) S-Hook (sold separately)
BC504S



Klein Tools Tool Apron Storage Module, S-Hook
(12) compartments to accommodate a wide variety of Lineman tools; 15.5" L x 19.5" H
BC502S

Klein Bucket Hooks
5144LG3 - 3" Gated Bucket Hook
BC312 - 3" Utility Bucket S-Hook
BC311 - 2" Utility Bucket S-Hook



5144LG3

BC312

BC311



Meta Design & Manufacturing Shear Plate Receptacle Cutter

Provide a clean, fast cut every time. Available in two sizes, for 2" or 4" shear plates.

2SHEAR 2"

4SHEAR 4"



Journeyman Gear Corner Pocket

Hangs in the corner of the bucket with bucket hooks (sold separately) for hanging all types of tools and equipment. 55 lbs weight rating.

CP1



Journeyman Gear Key Biscuit

Simple solution to lost or dropped cotter pins.

KB1



Ripley 45 Degree Cable Insulation Chamfering Tool

Easily adjusts to suit XLPE & EPR insulation materials on 0.5" to 2.36" cable diameters.

OD-US10-7001



Hastings Transformer Last Check Meter

Utilized to test the condition of transformers and capacitors before placing them into service

HFP-6793



Buckingham Buck Lube

Specially formulated for cleaning, lubricating and maintaining hardware & rubber goods; 12 oz can; Non-flammable formula / high dielectric strength (22kv)

BUCKLUBE



Linestar Waffle Hammer Head 1/4 - 1-1/4 Inch Utility Wrench

Thread Chaser in the handle; 3/4" Box End; Waffle Hammer Head

LUS-TG0010CHL



Ariat Mens FR M4 Low Rise Boot Cut Shale Jean

13 oz ring-spun stretch denim;
CAT 2: 20 cal/cm²

10012555



Blaklader 4786 Multinorm FR Shell Jacket

Combines wind and waterproof design
with durable materials that will shelter
you from the harshest conditions;

32 cal/cm², CAT 3

BLD-478615353389



Benchmark FR Amarillo FR Hi-Viz Hoodie

12 oz with segmented striping;
19 cal/cm²

BF-7025FR



Blaklader FR Pants

10 oz, Arc Rating 11 cal/
cm²; comes complete
with a gusseted crotch for
maneuverability and com-
fort as well as the tool
pockets on both sides.

BLD-167615508900



Blaklader FR Pants w/ Utility Pockets

10 oz, Arc Rating 11
cal/cm²; back pockets
with bellow

BLD-163615508900



Blaklader FR Long Sleeve T-Shirt

Navy Blue; 7 oz; ATPV
rating: 13 cal/ cm² CAT 2;
Chest Pocket

BLD-349317708900



Blaklader FR Hoodie

Navy Blue; 12 oz; Kangaroo
Pocket; ATPV rating: 13 cal/
cm² CAT 2

BLD-349217638900



Hoffman **EH** Composite Toe Classic - 6" and 8"

The Hoffman Composite Toe Classic is a Mountaineer style hiker lineman boot. Features a one piece seamless leather vamp with no stitching to come undone around the foot area. An added rubber rand around the boot protects the upper from abrasion and other wear. A waterproof SympaTex membrane helps keep water while allowing the boot to breath. A solid Vibram sole provides long time wear and a taller heel to accommodate a good gaff fit. Dual shank system provides unsurpassed arch support while climbing. Meets the 2413-11 EH Rating
 Sizes 8-13 Medium and Wide (available in 1/2 sizes except for 12 1/2)

8Q

6"

8R

8"



Hoffman **EH** Composite Toe Armor Pro Lineman Boot - 6" and 8"

This rugged mountaineer hiker is coated in "stark" material (similar to truck bed lining) making it cut resistant, adding another level of waterproofing and extending the overall life of the boot. Padding in the ankle area and dual shank system take ease of wear to the next level. Highlights- SympaTex waterproof liner, Dual arch support system with composite mid-sole and EH rated composite toe.

Sizes 8-13 Medium and Wide (available in 1/2 sizes except for 12 1/2)

3F

6"

3G

8"

Hoffman Hiker and Power

THE LIGHTWEIGHT CLIMBING BOOT

- Double Midsole and DUAL STEEL SHANK
- Rebuildable vibram lug sole and 1" CLIMBING HEEL
- A WATERPROOF* liner
- Leather/cordura upper provides breathability to keep you cool
- Available in sizes 7-12, 13D and 8-12, 13EE

* Although waterproof failure is rare in the construction of this boot, Hoffman will not warranty the waterproofness of this boot.



2A Standard Hiker

6S Hiker EH w/ Safety Toe

6X 10" Power

6T 10" EH Power w/ Safety Toe



10" All Leather Powerline

Hoffman's All-Leather Powerline features an all-leather upper for more leg and ankle support than our standard Powerline offers. Built with the same terrific features that all of our Powerlines have, this boot features a waterproof bootie, dual steel shanks and a Vibram lug sole for great performance. Although waterproof failure is rare in the construction of this boot, Hoffman will not warranty the waterproofness of this boot.

Available in sizes 7-13, 14D and 8-12, 13EE

6J 10" Leather Power

6L 10" EH Leather Power w/ Safety Toe



8S

Hoffman **EH** XT Powerline Composite Toe

The XT Powerline adds extra arch flash protection by adding FR Fabric to the sides of the boot while help keeping the boot breathable. A leather toe cap was added to the boots for extra durability in the toe area. Dual Steel Shanks for outstanding climbing support comes standard on the XT Powerline. A water resistant membrane, contour cushion insoles and boot tongues are all features found on this boot. For safety, a composite safety toe is added and this boot meets the ASTM F2413-11 EH standard. Made in the USA

Available in sizes 8-13 (available in 1/2 sizes except for 12 1/2) D or EE width



3H

10" Meindl Logger Lineman Boot- Plain Toe

The German made Meindl boot has an extremely supportive upper that provides excellent leg/ankle support and stability. A waterproof liner helps insure dryness and a removable insole adds cushion to your every step.

Hoffman has added dual steel shanks for all day climbing comfort.

Majority of customers order 1/2 size smaller. Although waterproof failure is rare, Hoffman will not warranty waterproofness of this boot.

Available in sizes 8-13 (available in 1/2 sizes except for 12 1/2)



3R

10" **EH** Meindl Eureka Steel Toe Lineman Boot

The German made Meindl boot has an extremely supportive upper that provides excellent leg/ankle support and stability. A waterproof liner helps insure dryness and a removable insole adds cushion to your every step.

Hoffman has added dual steel shanks for all day climbing comfort.

Majority of customers order 1/2 size smaller. Although waterproof failure is rare, Hoffman will not warranty waterproofness of this boot.

Available in sizes 8-13 (available in 1/2 sizes except for 12 1/2)

8W



Hoffman 6" Summit Work Boot

The Summit mountain boot can be used for light line work. A SympaTex waterproof bootie is added to provide waterproof protection. A 5 1/2mm nylon mid-sole provides excellent lateral support. Made in Italy.

Available in sizes 8-13 (Fits Medium/Wide Width)

6R



Hoffman EH Composite Toe Rancher Lineman

The Hoffman Composite Toe Rancher is a solid choice for a pull-on style work boot with a hint of style. The 5 1/2 oz. leather upper is designed to offer comfort and longevity. Their easy on, easy off performance makes this style of a boot a favorite for those looking for a boot with no laces. A waterproof membrane is added to keep you dry no matter what the weather is doing. A durable Vibram work sole, re-enforced triple ribbed climbing shank and a heavy duty mid-sole are added to provide stability and support. The Rancher features a composite toe that meets ASTM 2413-11 safety standards and is EH rated.

Available in sizes 8-13 (available in 1/2 sizes except for 12 1/2); D or EE width

9C



Hoffman Lineman Felt Pac

The Hoffman Lineman felt pac has become the best selling lineman pac in America. Constructed with a re-buildable American made rubber bottom, the boot features qualities not found in other manufacturer's products. DUAL STEEL SHANKS

including a 5" triple ridge steel shank, and a 12 iron mid sole offers

unsurpassed support and comfort that won't be found in other lineman pacs. Made in the USA. Full sizes only.

These boots run a little big. If you wear a size 9 1/2 go down to a size 9. If you are a size 9 stay at that size. L13

9A (not shown)- 10" Pac
9C (SHOWN)- 14" Pac

9Q



14" Hoffman Lineman Thinsulate Pac

Very popular with those who work in milder weather conditions. Lined with a removable Thinsulate® liner, this boot is an excellent choice for those looking for a slimmer alternative to felt pacs.

Equipped with DUAL STEEL SHANKS providing excellent support. Claw- lug sole. Rebuildable. Whole sizes only.

Run Small. For example if you are a sz. 9 or 9 1/2 you would order size 10.

9JEH



Hoffman EH Lineman Steel Toe Felt Pac

This boot has many of the same features of the Hoffman Lineman Felt Pac including our DUAL STEEL SHANK system that adds the most arch support of any lineman boot available. The waterproof rubber

bottom includes a steel toe that meets or exceeds the safety standard requirements of the ANSI (Z41Pt91, MI-75 C-75). This boot is re-buildable for years of service. L14EH

9GEH 10" Steel toe Pac
9JEH 14" Steel toe Pac

Hoffman Felt Liners

9L-10" Liner \$28.00
9N- 14" Liner \$28.00

Hoffman Thinsulate Liners 9R- 14" Liner



CAROLINA®



7RR

Carolina 10" Waterproof EH Rated Composite Toe Lineman Boot

- Cork Harness Leather Upper
- Composite Safety Toe Cap
- Waterproof Scubaliner™
- Imported
- Sizes: 8-12, 13, 14 (D and EE width)

#CA1904



H2

HOFFMAN
BOOT OIL
- 16 oz
- Helps protect
and preserve
leather



H3

HOFFMAN
PREMIUM
BOOT
DRESSING
- 8 oz
- Helps protect
and preserve
leather

11Q



NYLON
LACES
FOR 10" AND
16" BOOTS


LEATHER LACES
FOR 10" AND 16" BOOTS

11R



PEET
BOOT
DRYER

11K



AMBIENT AIR SAFELY
REMOVES PERSPIRATION, WETNESS AND ODOR FROM
ANY FOOTWEAR OVERNIGHT.
IMPROVES FOOT COMFORT AND HEALTH WHILE PRO-
TECTING YOUR FOOTWEAR INVESTMENT. LETS LEATHER
BREATHE AND RETAIN ITS NATURAL OILS TO EXTEND
FOOTWEAR LIFE
11K-10"-12" BOOTS
11L - 14" -16" BOOTS

4 D-RING BELTS



Buckingham **Short Back** Mobility Belt

- Offers a man rated upper belt strap that is bound to the lower work positions strap by 1 3/4" web
- Four dee ring belt supports the use of wood fall restriction devices
- No lower strap

12E

Fully padded 7" high back wrapped in ultra-soft leather

12F

Fully padded 7" Drilex high back with cushioning



12D

Buckingham Leather Buck Mobility Belt

- Offers a man rated upper belt strap that is bound to the lower work positions strap by 1 3/4" web
- Four dee ring belt supports the use of wood fall restriction devices
- No lower strap

Fully padded 9" high back wrapped in ultra-soft leather



12Q

Buckingham Buck-Lite Line Pro

- Based off the 2000M belt, this belt is designed to be worn the same as a traditional line belt, but includes a lower seat section which supports the user around lower buttocks. Large dee rings at both the upper and lower positions allows the user to attach their wood fall restriction device and secondary lanyard to either set of dee rings. Made of soft leather for a broken in feeling right out of the box.



12W

Buckingham cushioned **Drilex*** Lined Belt with 8" backsaver to provide back support. With 4 D-rings.



12Y

Buckingham cushioned **Drilex*** Lined Belt with Gutstrap Backsaver and 4 D-rings

*BECAUSE OF PADDING ON DRILEX BELTS IT IS RECOMMENDED THAT YOU ORDER 1-2 D-RING SIZES LARGER THAN YOUR REGULAR D-SIZE



12X

Buckingham Heritage Short Back Mobility Belt 20192M-BH

- Offers a man rated upper belt strap that is bound to the lower work positions strap by 1 3/4" web
- Four dee ring belt supports the use of wood fall restriction devices
- No lower strap
- 7" ultra-soft, distressed leather for that already broke in feel and vintage look



90H

Buckingham Heritage Nut and Bolt Bag 4570BH



16H

Buckingham Heritage 5 Pocket Tool Holster 42266-BH



12V

Buckingham Adjustable Body Belt

- The adjustable 4 D-Ring Body Belt offers an adjustable lower work positioning D-piece that allows the user to customize the size of the body belt at any given moment.
- This belt features only 4 sizes- Small, Medium, Large and X-Large (see sizing below)
- Perfect for those who work in areas of the country with large temperature swings. Can now adjust their belt to the clothing they are wearing.
- Also, great for those entering the trade who may either lose weight during line school or lose/gain weight throughout their career.
- Fully padded 7" Short Back; Ultra soft leather
- 7.5 Pounds and meets ASTM F887 Standards

SIZES:

X-Small (D18-D20)

Small (D20-D23); Medium (D23-D26)

Large (D26-D29); X-Large (D29-D33)



The Buckingham 2000M - A popular belt among Lineman. Linemen do not like the stiff feel of new body belts. This belt is hand-crafted of the most pliable and highest quality leather available to create that broken-in feeling from the first day worn. It features a full float body belt with a 5 1/2" foam cushioned pad reinforced with rawhide lace. The belt strap is leather and nylon sewn together for strength and comfort. The sliding dees allow the lineman a 4" lateral movement on the pole. Weight 6lbs.
2000M- Black



Jelco 4 D-ring Lineman's Belt
Soft leather gives belt a broken in feeling from the start. Tongue buckle belt connection with a quick connect attachment for the top belt.



Buckingham Black 4 Dee Body Belt - 2000EM

- Crafted of high quality leather
- Full float body belt with 5 1/2" foam cushioned pad reinforced with rawhide lace
- 4 floating in-line dees provide a 4" lateral movement



Buckingham 1994FR
2 D-ring Full Float lightweight Belt with 5" wide pad



Bashlin EZ Rider - Nylon Cushion

- New ergonomic, contoured design allows the belt to be worn comfortably and correctly, without compromising safety
- Easily connect Wood Fall Protection Devices
- 6.4 lbs.



Bashlin EZ Rider - Leather Cushion

- New ergonomic, contoured design allows the belt to be worn comfortably and correctly, without compromising safety
- Easily connect Wood Fall Protection Devices
- Glove soft leather cushion that needs no break-in period; 6.7lbs



Bashlin 4 D-ring tool belt -

Hugs the hips and has extra D-rings for carrying a secondary lanyard. The upper D's are positioned in just the right place. Upper tongue has quick release buckle.

13G

Nylon Mesh Cushion

13K

Leather Cushion



The Floridian (88) - One of the most popular belts around! Superior design and performance makes this belt the industry standard.

It combines a padded, contour section with flares for the shifting "D" rings and a 5 1/2" back. This belt gives excellent support and climbing comfort. It is a practical belt with wearable quality, which makes it economical. Weight 6 1/2lbs

13A Standard 88 Belt
13M Black Maverick Leather



Bashlin Black In-Line 4 D-Ring Belt

- 88 style belt with 4 d-rings
- low profile and less bulk
- full floating, shifting d-ring design
- glove soft cushion

SECONDARY STRAPS & ACCESSORIES



90S

Buckingham 9A4+R-8 Buckadjuster with Aluminum Components


- Features an aluminum snap hook and carabiner with 3600 lb. gates. Fabric wear guard protects the rope when in use. Overall length is 8'.
- Weights 2.2 pounds



90R

Buckingham 9+R-8 Buckadjuster with Aluminum Components

- Features an aluminum snap hook and carabiner with 3600 lb. gates. Clear plastic tube protects the rope when in use. Overall length is 8'.
- Weights 2.2 pounds



90Z

Buckingham 92C+R-8 Tough Rope Buckadjuster with Aluminum Components

- Features an aluminum snap hook and carabiner with 3600 lb. gates. Wear resistant TrebleKern rope. Overall length is 8'.



BK6

Buckingham 92E+R-8 Buck Adjuster With Black Tough Rope

- Features an aluminum snap hook and carabiner with 3600 lb. gates. Wear resistant TrebleKern rope. Overall length is 8'.



90GL

Buckingham 8' LeverJust™ - 9M8-8

- Allows users to lengthen without removing weight from the lanyard with the use of the LeverGrab™. LeverGrab™ allows for easy one handed adjustment. 2.4 lbs.



90G

9-8

Buckingham Buck-A-Juster Rope Lanyard with Micro Adjuster

- Microadjuster gives the user the ability to easily adjust the length of the lanyard with one hand. Lanyard is stitched 1/2" rope with a green and white jacket and red core.



90P

Buckingham BuckEcojuster

- Contrasting core for easy rope inspections. Original BuckGrab is the easy to use adjuster with a two stage carabineer for body belt connections



90N

DBI-Sala 8 ft Adjustable Rope Positioning Lanyard With Steel Hardware

- Abrasion resistant sleeve
- Blue wear indicating core




55L

13088

Jelco Work Positioning Rope Lanyard- Steel Snap Hook

- 8 foot with 1/2" Diameter rope and adjuster



90T

Jelco 8' Adjustable Rope Safety with Aluminum Snap hook

- An 18" fabric tube is constructed of ballistic material for longevity



90Y

DBI-Sala 8 ft Adjustable Rope Positioning Lanyard With Aluminum Hardware

- Abrasion resistant sleeve
- Blue wear indicating core

BUCKINGHAM WOOD FALL PROTECTION



Buckingham SuperSqueeze with Rope Inner Strap w/ BuckGrab Adjustment and Carabiners

5G

Distribution(up to 15.9" Diameter)
36" Outer Strap/70" Inner Strap 488R

5GM

Mid-Length(up to 22.2" Diameter)
44" Outer Strap/70" Inner Strap 488MRMC

5GT

Transmission(up to 28.6" Diameter)
52" Outer Strap/78" Inner Strap 488TRTC



Buckingham SuperSqueeze with Web Inner Strap w/ WebGrab Adjustment and Carabiners

5W

Distribution(up to 15.9" Diameter)
36" Outer Strap/70" Inner Strap 488DWMC

5WM

Mid-Length(up to 22.2" Diameter)
44" Outer Strap/70" Inner Strap 488MWMC

5WT

Transmission(up to 28.6" Diameter)
52" Outer Strap/78" Inner Strap 488TW2



SuperSqueeze with Rope Inner Strap and Snaps

(up to 22.2" Diameter)

44" Outer Strap/70" Inner Strap



SuperSqueeze with Web Inner Strap and Snaps

(up to 22.2" Diameter)

44" Outer Strap/70" Inner Strap



Buckingham EZ Squeeze with Rope Inner Strap w/ BuckGrab Adjustment and Carabiners; features BuckHorn Adjustment lever and loop handle

5RDC

Distribution(up to 15.9" Diameter)
36" Outer Strap/70" Inner Strap 490R

5RMC

Mid-Length(up to 22.2" Diameter)
44" Outer Strap/70" Inner Strap 490MRMC

5RTC

Transmission(up to 28.6" Diameter)
52" Outer Strap/78" Inner Strap 490TRTC



EZ Squeeze with Rope Inner Strap w/ BuckGrab Adjustment and Snaps

(up to 22.2" Diameter)

44" Outer Strap/70" Inner Strap



Buckingham EZ Squeeze with Web Inner Strap w/ WebGrab Adjustment and Carabiners; features BuckHorn Adjustment lever and loop handle

5WDC

Distribution(up to 15.9" Diameter)
36" Outer Strap/70" Inner Strap 490DWMC

5WMC

Mid-Length(up to 22.2" Diameter)
44" Outer Strap/70" Inner Strap 490MWMC

5WTC

Transmission(up to 28.6" Diameter)
52" Outer Strap/78" Inner Strap 490TW2



EZ Squeeze with Web Inner Strap w/ WebGrab Adjustment and Snaps

(up to 22.2" Diameter)

44" Outer Strap/70" Inner Strap


Replacement Components for SuperSqueeze

#5DD: Nylon Backstrap 36" (Distribution) no Hardware
#5DM: Nylon Backstrap 44" (Mid-Length) no Hardware
#5DT: Nylon Backstrap 52" (Transmission) no Hardware
#5XD: Inner Strap Web no Hardware for Distribution
#5XT: Inner Strap Web no Hardware for Transmission
#5RD: Inner Strap Rope no Hardware for Distribution
#5RT: Inner Strap Rope no Hardware for Transmission
#5RH 70" Inner Strap Rope with Hardware/Snaps
#5WH: 70" Inner Strap Web with Hardware/Snaps

Replacement Components for EZ Squeeze

- All inner strap replacement parts are the same as used for the SuperSqueeze; see chart to left
#5BD: Nylon Backstrap 36" (Distribution) no Hardware
#5BM: Nylon Backstrap 44" (Mid-Length) no Hardware
#5BT: Nylon Backstrap 52" (Transmission) no Hardware
#5BH: EZ Squeeze webgrab with BuckHorn for outer strap
#5DH: Nylon Backstrap 36" (Distribution) with Webgrab/Buckhorn
#5MH: Nylon Backstrap 44" (Mid-Length) with Webgrab/Buckhorn
#5TH: Nylon Backstrap 52" (Transmission) with Webgrab/Buckhorn

WOOD FALL PROTECTION



Buckingham SuperSqueeze with Black Tough Rope For Distribution

- wear-resistant TrebleKern Tough Rope™ eliminates the need for a wear guard (up to 15.9" Diameter)
- 36" Outer Strap/70" Inner Strap



Buckingham EZ Squeeze with Black Tough Rope For Distribution

- wear-resistant TrebleKern Tough Rope™ eliminates the need for a wear guard
- features a Loop Handle on the outer strap
- BuckHorn™ Adjustment Lever (up to 15.9" Diameter)
- 36" Outer Strap/70" Inner Strap



Jelco Pole Choker 5

Wood pole climbing fall arrest system.

The Choker Strap is a key component of the Jelco Pole Choker. The 1 3/4" wide yellow nylon strap squeezes the pole, the roller's teeth dig in to provide the gripping force required to prevent you from falling down the pole. Comes with double-eye snap hook.

#99F 5.25' 03725 10"-16" Pole Diameter

#55H 6.2' 03726 11"-20" Pole Diameter

#55J 6.8' 03727 14"-30" Pole Diameter (For Transmission)



Bashlin Patriot

- Lightweight
- Ergonomic design reduces upper body stress
- Allows proper body position and leg placement when climbing
- Handle placement is where a pole strap would be when hiking a pole

55Z

Standard Model: Adjusts for poles ranging from 6"-20" in diameter

55K

Transmission Model: Adjusts for poles ranging from 6"-30" in diameter



Cynch-Lok™ Fall Restricting Pole Strap- Rope Model

- meets CSA Z259.14-01 standards for Type A and AB,
and ASTM F887-11

- Roller adjuster provides one-handed adjustment

55T

Distribution Model: Diameter: 5.5" Min and 18.5" Max
Circumference: 17.5" Min and 58" Max; 4.8 lbs

55MR

Mid-Length Model: Diameter: 5.5" Min and 27.5" Max
Circumference: 17.5" Min and 86" Max; 5 lbs

55TM

Transmission Model: Diameter: 5.5" Min and 30.5" Max
Circumference: 17.5" Min and 96" Max; 5.3 lbs

55DS

Cynch-Lok™ Replacement Rope Interior Strap



Cynch-Lok™ Fall Restricting Pole Strap- Web Model

- meets CSA Z259.14-01 standards for Type A and AB,
and ASTM F887-11

- Roller Adjuster provides one-handed adjustment

55WD

Distribution Model: Diameter: 5.5" Min and 18.5" Max
Circumference: 17.5" Min and 58" Max; 4.9 lbs

55MW

Mid-Length Model: Diameter: 5.5" Min and 27.5" Max
Circumference: 17.5" Min and 86" Max; 5 lbs

55WT

Transmission Model: Diameter: 5.5" Min and 30.5" Max
Circumference: 17.5" Min and 96" Max; 5.4 lbs

55WS

Cynch-Lok™ Replacement Web Interior Strap



Cynch-Lok™ Replacement Strap

55ND

Replacement Strap for Distribution

55MD

Replacement Strap for Mid-Length

55NT

Replacement Strap for Transmission

BELT ACCESSORIES / ZIPPER BAGS

5T



Buckingham 5 Pocket Tool Holder- Black
42266-BL

5S



Buckingham 4 Pocket Tool Holder- Black
49261-BL

K2



Klein 5 Pocket Tool Pouch- Black
5118P5

16F



Bashlin 4 Pocket Tool Holder
111HLS

16G



Bashlin 5 Pocket Tool Holder
111HLDS

16U



Bashlin Black 4 Pocket Tool Holder
111HLSX

16W



Bashlin Black 5 Pocket Tool Holder
111HLDSX

16K



Bashlin Black 5 Pocket Tool Holster
with Knife Pouch

16NN



Buckingham Black 3 Inside Pockets
Leather Bag 10x9, 52993

16H



Buckingham Heritage 5 Pocket
Tool Holster
42266-BH

5C



Black Buckingham 5
Pocket Tool Holder with
Knife Pouch

17S



Klein Cordura® Ballistic Nylon
Zipper Bag 5139B
Great for storing dies and bushings
12.5" x 7"

17R



Klein Canvas Zipper Bag
Great for storing dies and bushings
12.5" x 7"

17G



Klein Stand-Up Zipper Bags, 2 Pack
- Stand-up bottom allows items to be
found more easily
Grey 7.5"H x 9"L
Orange 6.5"H x 8.5"L

17A



Large Canvas Bag with one pocket on the inside, 5142-P 9"x10"

17B



Extra Large Klein Canvas Ditty Bag 10"x12"

17X



Klein Black Nut and Bolt Bag - 10" X 9" with interior pocket

17J



Buckingham Nut and Bolt Bag - With magnet, reinforced bottom, inside pocket and loops for cotter pins 9"x9.5"



90U

Buckingham Canvas Ditty Bag with Magnet 9"x10"
90U- Natural Canvas
90UB- Black



90V

Buckingham Canvas Ditty Bag with Elastic Retainer - Prevents equipment from falling out while allowing easy access into bag 9"x10"



17E

Buckingham Black Canvas Bag 9x10, 4570B2



17L

Buckingham BuckVis Safety Green Nut & Bolt Bag 9x10, 4570G4



17K

Bashlin Black Ballistic Nylon Bag with inside pocket 8 1/2"x9"x4"
25ABX



17Y

Bashlin Canvas Bag with Magnet and inside pocket 8 1/2" x 9"x 4"
25AM2



17C

Bashlin Canvas Bag 8 1/2" x 9"x 4"
25A



16M

Jelco Bolt Bag with Multi-Pockets 84501



16R

1040-HB



Estex Canvas Hard Body Ditty Bag 10"x6"x3"



16S

1061-1-HB



Estex Hard Body Vinyl Water resistant Ditty Bag 10"x6"x3"

GUT STRAPS / BELT ACCESSORIES



Buckingham Man-Rated Gut Strap with Tongue Buckle

- add this gut strap to your existing standard climbing belt to have extra 2 D-rings for use with your secondary lanyard
- Size S-2XL



Buckingham Man-Rated Gut Strap with Quick Connect Buckle

- add this gut strap to your existing standard climbing belt to have extra 2 D-rings for use with your secondary lanyard
- Size S-2XL



Buckingham 1 3/4" Leather Gutstrap (snaps included)

Also available in Black #15AB

Sizing for Buckingham Gut Straps
Typical Fit for a Person with Waist Size

Small.....	28-32
Medium.....	32-36
Large.....	36-40
X Large.....	40-44
XX Large.....	44-48



Nylon Suspenders

6259



Buckingham Bucktender

- The BuckTender is a lightweight, compact retractable designed to keep excess slack from the tail of the secondary lanyard or wood pole fall restriction device out of the way while climbing and working.

- Allows user to make length adjustments without having to remove the tail from a hand line hook or ditty bag.

- Available with a single leg or dual leg (if user has the tails of both the secondary lanyard and the wood pole fall restriction device on one side).

- The BuckTender will break away when approximately 50 pounds of force is applied.

- Lightweight and Compact

9S Single Leg

9D Dual Leg



Tape Thong

6107



Handline Thong

6109

Barrel Rivet to attach your tool holder to your belt.



15R



15L

15M

15O

Belt Snaps

15L- Small Belt Snap

15M- Large Belt Snap

15O- Gut Strap Snap For Bashlin Gut Straps

15BA



**Bashlin Handline
Belt Hook #33L**

15K



**Buckingham
Gated Handline
Carrier #2402G**

15Z



**Buckingham Heavy-Duty
Gated Handline Carrier
#2402GH**

15H



**Wrench Holder
6102**

15JB



**Lowell Lineman
Wrench Holder -
Black 111LWHX**

15J



**Lowell Lineman
Wrench Holder
111LWH**

37A



Rock Exotica TransPORTER

- Tool carrying accessory carabiner
- Can be locked closed
- Attaches to harness
- Max Webbing Height: 2"
- WLL: 50 lbs
- Weight: 3.4oz

25J



**Buckingham Leather
Knife Pouch #4089**

35L




**Petzl ST'ANNEAU
Dyneema® Sling -
24cm(9.45") #C07 24**

35Q



**Petzl ST'ANNEAU
Dyneema® Sling -
60cm(23.6") #C07 60**

37Y



**Petzl DJINN AXESS
Quickdraw - 11" Overall
Length #M060CA00**

POSITIONING STRAPS

NEOPRENE/NYLON



BUCKINGHAM SUPERSTRAP

18L 336699E 1 3/4" x 6'6"

18M 337099E 1 3/4" x 7'

Buckingham




Slide Buckle Pole Strap

Buckingham Neoprene Nylon Pole Strap

18Z 346699E 1 3/4" x 6'6"

18ZA 347099E 1 3/4" x 7'

JELCO



Built in internal red
wear indicator

Neoprene/Nylon

99J 87633 1 3/4" x 6'6"

99K 87644 1 3/4" x 7'

HARNESSES



53J



Buckingham BUCKOHM™ TRUEFIT™ Harness w/ Dielectric D-Ring – U68L7NQ2

- Universal Harness(fits S-3X); Dielectric quick connect buckles; Lightweight back pad; Frontal Rescue Loops; Dual Trauma Straps
- Meets ASTM F887 Electric Arc Performance Requirements



53K



Buckingham BUCKOHM™ TRUEFIT™ Harness w/ Web Loop – U68L7NQ3

- Universal Harness(fits S-3X); Dielectric quick connect buckles; Lightweight back pad; Frontal Rescue Loops; Dual Trauma Straps
- Meets ASTM F887 Electric Arc Performance Requirements



4C



Buckingham Mini BuckFit 'X' Style Full Body Harness

- Quick connect buckles with leather chafes on the legs and chest straps; Buck Mini Back Pad offers comfort and ease in donning the harness; shoulder pads are made from sateen fabric with fire resistant padding; 5000lb rated nylon dorsal loop.

Meets ASTM F887 Electric Arc Performance Requirements



4D



Buckingham Mini BuckFit 'H' Style Full Body Harness

- Quick connect buckles with leather chafes on the legs and chest straps; Buck Mini Back Pad offers comfort and ease in donning the harness; 5000lb rated nylon dorsal loop.

Meets ASTM F887 Electric Arc Performance Requirements



4X



Bashlin 683XD Harness

Includes a D-ring attachment on back.

Meets ASTM F887.

Small-3XL



4S



Bashlin Q683XAX Harness

X-Style Body Harness with a nylon loop back attachment point and quick release buckles. Moisture wicking body pad for comfort and easier donning.

Meets ASTM F887.

Small-2XL

10TF



Buckingham Universal TrueFit™ Black H-Style Harness w/ Web Loop - U68D7FQ1

Fits sizes Small to 3X. This harness features QuickConnect buckles throughout, including the chest strap, a web loop dorsal attachment, as well as a removable back pad. The back pad provides users with a lightweight, comfortable, breathable and most importantly, functional back pad that will result in all day relief on the back and shoulders. Weighs approximately 4lbs. Rated to 420 lbs. when used with equivalently rated accessories.
Meets ASTM F887

10XS



Buckingham Universal TrueFit™ Black X-Style Harness w/ Web Loop - U603P8Q1

Fits sizes Small to 3X. This harness features steel QuickConnect buckles throughout, a web loop dorsal attachment, as well as a back pad. The back pad provides users with a lightweight, comfortable, breathable and most importantly, functional back pad that will result in all day relief on the back and shoulders. Rated to 420 lbs. when used with equivalently rated accessories.
Meets ASTM F887



Jelco Arc Flash Harness

- Universal (fits sizes S through XL)
- Di-electric quick connect buckles
- Lightweight Nomex comfort backpad
 - Front rescue loops
- Suspension trauma straps
- Meets ASTM F887

53L

Jelco Arc Flash Harness with Di-electric D-ring 41882

53N

Jelco Arc Flash Harness with Web Loop 41884

55V



DBI Sala ExoFit XP Arc Flash Harness

- Meets ASTM F887 40 cal Arc Flash Standard
- Includes dorsal web loop, rescue loops for bucket-truck and high-angle rescue, removable Nomex/Kevlar back pads, coated hardware to reduce static buildup, and leather insulators under fasteners
- Quick Connect Buckles
 - M, L, or XL



Bashlin Lanyard

Tubular nylon web with polyester shock absorbing core and 2- 3600lb gate snaphooks. Meets ASTM F887

4Y 4ft (2804-4HL) **4Z** 6ft (2804-6HL)



Bashlin Lanyard

Tubular nylon web with polyester shock absorbing core, 1- 3600lb gate Snaphook and a loop end. Meets ASTM F887

19T 4ft (2805-4HL) **19R** 6ft (2805-6HL)



Jelco 6' Arc Flash Lanyard with Aluminum Snap Hook(s)

Arc Flash rated to 40 Cal/Cm2; Built in shock absorbing core; Impact Indicator; Aluminum Snaps have 3600lb gate

19K Snaps both Ends- 54276

19L Snap and Web Loop- 54206



Buckingham ANSI Rated Energy Absorbing Lanyard Parking Attachment

- Easily installed in the field and designed to breakaway when a load of no more than 120 pounds is applied.

53P



Buckingham BuckYard Shock Absorbing 6' Fixed Lanyard

Snaps feature 3600lb gates; Meets ASTM F887 and OSHA Electric Arc Performance Requirements

19G Snaps both Ends- 8V1E16S1

19J Snap and Web Loop- 84V1E16S1



Buckingham BuckYard Stretch 6' Lanyard

Expands/stretchers when working; Expands to 6' when worked and will retract to 44"; Snaps feature 3600lb gates; Meets ASTM F887 and OSHA Electric Arc Performance Requirements

19Q Snaps both Ends- 8V7E16S1

19W Snap and Web Loop- 84V7E16S1



Buckingham 6ft Mini BuckLimiter™

- Rated to 350 lbs
- Lightweight and compact
- Dyneema webbing
- Swivel Top
- Alloy Housing

55Q



DBI Nano-Lok Arc Flash Self Retracting Lifeline

- 8 ft of 3/4" Kevlar fiber webbing and aluminum self-locking carabiner, swiveling anchor loop with 13" web extension and aluminum snap hook.

55EB



4W

Buckingham BuckTech FR Harness

- With the seat, the BuckTech is perfect for flying/helicopter work; seat can be removed
- Full Floating Suspension D-ring
- Meets ASTM F887 Electric Arc Performance Requirements



4U

Buckingham Access Tower Harness

- User friendly design: Harness wears like a traditional line belt and features attachments similar to traditional line belts. Good for light suspension work.
- Meets ASTM F887 Electric Arc Performance Requirements



81H

Buckingham Lightweight 16' Webbing Retractable Lifeline


- Light yet rugged composite housing
- Housing swivels to minimize twisting during use
- Weighs 4.6 lbs



81Y

Buckingham Buck Stop Dual Lanyard with Snap

- Features two Big BuckSnaps that have 3 11/32" gate opening. Red rescue loops facilitate the rescue of an injured worker
- meets Arc Flash requirements in ASTM F887 as well as ANSI 3600 lb. gate strength requirements



81K

Buckingham Buck Stop Dual Lanyard with Loop

- Features two Big BuckSnaps that have 3 11/32" gate opening. Red rescue loops facilitate the rescue of an injured worker
- meets Arc Flash requirements in ASTM F887 as well as ANSI 3600 lb. gate strength requirements



17Q

Estex Extra Large Velcro Top Closure Bag

- 11.5"H x 12"W x 2"D
- Interior tool loops
- External zipper pouch
- 4 external carabiner attachment points
- External screwdriver pocket
- Orange Cordura
- Ring to snap nylon straps for attachment



81C

Buckingham Big BuckSnap

- Allows the user to easily connect over 4" angle iron. Rounded inner edge designed to prevent damage to conductors when used in hot work applications
- 3600lb. rated gate



90W

Klein Extra-Tall Top-Closing Bolt Bag

- Extra tall for more storage space
- Top extends upwards 3" when open
- Tunnel loop fits belts up to 3" wide
- Bull-pin loop on each side
- 9" Width x 12" Height

POLE CLIMBERS & KITS

All climbers shown have replaceable gaffs, come with bottom straps and are sold in pairs. Request long slides if you are 6'2" or taller.




21FN

Bashlin Aluminum
BD14B-1N
w/ bottom straps



21G

Bashlin Steel
Off-Set w/ twist, BD16BC1N
w/ bottom straps



21H

Bashlin Steel
Off-Set, BD16B1N
w/ bottom straps



21V

Contoured
Shank

Buckingham Steel
SB94089A
w/ bottom straps



21X

Contoured
Shank
w/ TWIST

Buckingham Steel
SB94089AT
w/ bottom straps



21C

Contoured
Shank

Buckingham Titanium
TB94089A
w/ bottom straps



21D

Contoured
Shank
w/ TWIST


Buckingham Titanium
TB94089AT
w/ bottom straps



20T

Contoured
Shank
w/ GriP Technology
(keeps gaff pointed
towards heart of pole)

Buckingham Titanium
TBG94089A
w/ bottom straps



20S

w/ GriP Technology
(keeps gaff pointed
towards heart of pole)


Buckingham BuckAlloy
Matte Climber with Nylon
Straps
A94089A-MS



20R

w/ GriP Technology
(keeps gaff pointed
towards heart of pole)

Buckingham Steel Climber
with Nylon Straps
SBG94089A-BL



21JB

Buckingham Steel
Climber Kit with Big
Buck Pads with Cinch
w/ GRiP technology
SBG94K2V-BL



21VW

Buckingham
BuckAlloy™ Climber
Kit with Big Buck
Pads with Cinch w/
GRiP technology
A94K2V-BL



21QR

Buckingham Titanium
Climber Kit with Big
Buck Pads with Cinch
w/ GRiP technology
TBG94K2V-BL

CLIMBER KITS & PADS



21SK



21KA



21AL



21TB



21M

Buckingham Steel Pole Grip Climber Kit with Cushion Wrap Pads with Cinch w/ GRiP technology
SBG94K1V-BL

Buckingham BuckAlloy Climber Kit with Cushion Wrap Pads with Cinch w/ GRiP technology
A94K1V-BL

Buckingham BuckAlloy Climber Kit - Rodeo Edition continuous wrap pads w/ GRiP technology
A94K3V-BL

Buckingham Titanium Climber Kit with Cushion Wrap Pads with Cinch w/ GRiP technology
TBG94K1V-BL

Klein Hydra-Cool Pole Climber System Kit
221486



Buckingham Big Buck Pad with Angled Metal Insert and Cinch
- Adjustability of velcro wrap pad, increased surface of Big Buck pad and added moisture wicking Dri-lex lining

22V For Steel or Titanium Climbers

22VA For Buckingham BuckAlloy Climbers

22VF For Bashlin Aluminum Climbers(New Version)



Buckingham Cushion Wrap Pad with Cinch Loop & Angled Metal Insert

22G For Steel or Titanium Climbers

22GA For Buckingham BuckAlloy Climbers

22GF For Bashlin Aluminum Climbers(New Version)



Buckingham Cushion Wrap Pad with Angled Metal Insert

22M For Steel or Titanium Climbers

22MA For Buckingham BuckAlloy Climbers

22MF For Bashlin Aluminum Climbers(New Version)



Buckingham 4" Velcro Pads w/ Cinch
- Does not have metal insert



Buckingham 4" Wide Velcro Pads
- Does not have cinch or metal insert

CLIMBER PADS



Bashlin Hook-N-Loop Climber Pad with Metal Insert- Wide Model (Pair)

6Z For Bashlin Steel Climbers

6ZF For Bashlin Aluminum Climbers(New Version)



Bashlin Hook-N-Loop Climber Pad with Metal Insert (Pair)

5K For Bashlin Steel Climbers

5LN For Bashlin Aluminum Climbers(New Version)



Bashlin Hook-N-Loop Climber Pad (No metal insert)

5J

150V



6V

Buckingham 3118 Pad w/ Metal Insert

- Includes 2 Pairs of top straps

- If ordering for Buckingham BuckAlloy Aluminum Climbers use part# 6VA



Bashlin 145 Series Pads
*Includes 2 pairs of top straps

5M #145AC for Bashlin Steel Climbers

5NN #145FC for Bashlin Aluminum Climbers (New Version)



Bashlin Angled C-Pads

22Y For Bashlin Steel Climbers #105AC

22WN For Bashlin Aluminum Climbers(New Version) #105FC



Buckingham Angled C-Pads

22BB For Buckingham Steel and Titanium Climbers #35032

22CA For BuckAlloy Climbers #350321



22K

140DS

Bashlin Tunnel L-Pad



22H

130D

Bashlin Leather L-Pad



22D

3125

Buckingham Tunnel L-Pad



22U

8" Wide Pad. Felt Lining prevents Chaffing of calf muscle (pair)

* Requires (2) pairs 26" Straps #22S

3127



26" Buckingham Nylon Top Straps



24" Buckingham Leather Top Straps



24" Bashlin Nylon Top Straps



28" Bashlin Nylon Top Straps



28" Bashlin Bottom Strap Kit



26" Nylon Bottom Straps for Buckingham and Klein Climbers




26" Leather Bottom Straps for Buckingham and Klein Climbers



Buckingham Hook and Loop Climber Footstraps



Buckingham Faststrap Quick Connect Climber Footstraps



BASHLIN

- 23A — Long sleeves steel (pair)
- 23AF — Long sleeves alum (pair)
- 23B — Standard sleeves steel (pair)
- 23BF — Standard sleeves alum (pair)
- 23C — Sleeve screws (pair)
- 23D — Gaff screws (pair)
- 23E — Pole gaffs (pair)
- 23F — Polished pole gaffs (pair)
- 23G — Tree gaffs (pair)
- 23H — Gaff gauge

BUCKINGHAM REPLACEMENT GAFFS FOR STEEL AND TITANIUM CLIMBERS - DOWEL STYLE



- 22E — Replacement Pole Gaffs w/ screws
- 22J — CCA Repl. Pole Gaffs w/screws
- 23V — Tree Gaffs w/ screws
- 22N — Gaff Screws



- 23L — Standard sleeves (pair)
- 23K — Long sleeves (pair)
- 23M — Barrel Sleeve screws (4)
- 23N — Gaff gauge



KLEIN


- 23S — Klein sleeves (pair)
- 23SS — Long sleeves (pair)
- 23ZS — Sleeve Screws (set)
- 23T — Pole gaffs (pair)
- 23U — Tree gaffs (pair)
- 23UU — Gaff gauge

BUCKINGHAM REPLACEMENT PARTS FOR BUCKALLOY™ ALUMINUM CLIMBERS




- 21QB — Replacement Gaffs with screws
- 21QC — Replacement CCA Gaffs with screws
- 21QF — Sleeves with screws(pair)
- 21QL — Long Sleeves with screws(pair)
- 21QG — Gaff Screw Set
- 21QH — Sleeve Screw Set


CLIMBER ACCESSORIES



Klein Gaff Guards
also fit Bashlin Climbers



Buckingham Gaff Guards



The Universal Gaff Guard
Fits Buckingham, Bashlin
and Klein Climbers



Bashlin Leather Gaff Guards



Buckingham Magnetic Gaff Guards



Buckingham BuckGuard Retractable Gaff Guard
Easily attaches to climber sleeve



Buckingham Climber Foot Plate
Eliminates foot discomfort caused by standing on poles for extended periods of time. Fits all steel climbers. Non-slip rubber sole. Made of steel. Easy on/off.

21L For Buckingham Steel and Titanium Climbers

21LA For Buckingham BuckAlloy Climbers



Climber Shield #10
Ideal for new climbers & training. Reduces the chance of heel & ankle injuries from gaffs. Climber shields come in pairs only



Klein Gaff Sharpening Kit
KG2





Buckingham Gaff Sharpening Kit
Consists of all the necessary tools to reshape your gaffs and inspect critical climber dimensions. 6025



Bashlin Gaff Sharpening Kit #27



Master Gaff Gauge Kit
Has (1) Bashlin, (1) Buckingham, and (1) Klein Gaff gauges enclosed.



HAND TOOLS



Klein Adjustable Wrench - Extra Capacity

- 24A 12" 1 1/2" Capacity
- 24B 10" 1 5/16" Capacity
- 24C 8" 1 1/8" Capacity



25N 46037

Klein Splicer Kit
Scissors, knife and case



250

Klein Cable Copping Knife and Case



90C

Speed Systems Semi-Con Edge Wedge

SC-11



Channellock Adjustable Wrench

- 810W 10" 1 3/8" Capacity
- 812W 12" 1 1/2" Capacity



Milwaukee Adjustable Wrench

- M36 10" 1 3/8" Capacity
- M37 12" 1 5/8" Capacity



24H



24J



24K



3227



3239



3238

4L



4M



Sta-pul Stik

Minimizes risk of utility glove puncture

4L-Standard Sta-pul Stik \$21.90

4M- Super Stapler Staples up to 1 1/8"



4K

Buckingham Standard Staple Stick #574

Holds 12 Staples
7/8" Max Staple Size

10K

Buckingham Large Staple Stick #574L

Holds 10 Staples
1" Max Staple Size

Pricing/Descriptions

- 24H Lineman's wrench fits 5/8" hardware
4 sizes 1 3/32, 29/32, 13/16, 5/8 #3146
- 24J Lineman's wrench fits 3/4" hardware 4 sizes
1 5/16, 1 1/16, 5/8, 7/8 #3146A
- 24K Lineman's wrench Nema hardware 4 sizes
1 1/16, 1 3/16, 11/16, 7/8 #3146B
- 25E 11" Adjustable Spud Wrench 1 5/16" cap.
- 24L 15" Steel Construction Wrench
- 24M 15" Drive Ratcheting Const. Wrench 1/2"

BUGWRENCH



Heavy Duty Forged 4-n-1 Reversing Bugwrench
1/2" & 9/16" on one end and 5/8 & 3/4 on the other

95Z Standard Yellow Handle Model

95Y All Metal Model (not pictured)



Standard Bug Wrenches

24Z 9/16" x 3/4" BW-223 \$25.90

24ZA 9/16"x 3/8" BW-221 \$22.90

3J 9/16"x 1/2" BW-2212 \$22.90

3K 5/8"x 1/2" BW-2234 \$35.90

95G 11/16" x 15/16" BW-2242 \$34.90

3Z 13/16"x 15/16" BW-2243 \$29.90

95H 3/4"x 15/16" BW-2241S \$31.90



24ZZ

Forged Bug Wrench 9/16" x 3/4"
BW-223HD



2Z

Offset Bug Wrench 9/16" x 3/4"
BW-223F



24Y

Uninsulated Standard Wrench 9/16" x 3/4"



8Z

Uninsulated Offset Bug Wrench 9/16" x 3/4"
BW-203F



26Z

Uninsulated Forged Bug Wrench 9/16" x 3/4"
BW-203HD



M30

Milwaukee 4 in 1 Ratcheting Box Wrench
1000V Insulated 4-n-1- 1/2", 9/16", 5/8", 3/4"



M29

Milwaukee 2 in 1 Ratcheting Box Wrench
1000V Insulated 2-n-1- 9/16" x 3/4"



95W

Klein Lineman's Insulating Box Wrenches
1000V Rated 4-n-1- 1/2", 9/16", 5/8", 3/4"



RBW-QUAD1

56C

Speed Systems Quad Wrench
1/2", 9/16", 5/8" and 3/4"



Flex-Head 4-n-1 BugWrench
- 1/2" & 9/16" on one end and 5/8 & 3/4 on the other

95F

Yellow Handle Model



2 Piece Set

24X

Channellock 4-n-1 Ratcheting Wrenches
1 Wrench with 9/16", 5/8", 11/16", 3/4"
1 Wrench with 5/16", 3/8", 7/16", 1/2"

841S

5 Piece offset box wrench

1/4 x 5/16

3/8 x 7/16

1/2 x 9/16

5/8 x 11/16

3/4 x 7/8

24Q



68245

HAND TOOLS



PRICE LIST AND DESCRIPTION

25A	Buckingham Cushion Handle Knife	7H	Klein Folding Knife w/ Replaceable Blade
25B	Buck. Cush. Hndl. knife w/ notch	7J	Klein Replacement Blades (3 Pack)
25C	Buckingham Long Handle Knife	7Q	Madi Fixed Blade Skinning Knife
25G	Klein Skinning Knife	7Z	Madi OneFlip Pointed Lineman Knife
25GH	Klein-Kurve® Skinning Knife	7W	Klein Folding Knife w/ Clip
25H	MADI Spring Assisted Pocket Knife	7X	Klein Coping Folding Knife w/ Clip
25K	Klein Folding Knife	95K	Jameson Cushion Knife w/ notch
25KC	Klein Folding Knife with Clip	95J	Buckingham Skinning Knife w/ notch
25L	Klein Folding Knife	95L	Buckingham ErgoBlade Knife w/ notch
25V	MADI Brush Blade Knife	M4	Milwaukee Hawkbill Fixed Blade Knife
25VB	Replacement Brush for MADI Knife	M45	Milwaukee Hawkbill Knife w/ Stickwork
M6	Milwaukee Folding Blunt Tip Skinning Knife	M72	Milwaukee Hawkbill Folding Knife



26E



3Q



26C



26D




26K



26A



26B



3U



26F



26H



3X



3Y



90B



26G



26P



26Q



2E




2F



2G



MH1



MH2

PRICES AND DESCRIPTION

26A	Klein Side Cutters
26P	Klein Journeyman Pump Pliers
26C	Klein Journeyman Side Cutters 9 1/4"
3U	Klein Journeyman Cable Cutters
2E	Channellock 9 1/2" Pliers
26E	Klein Hardened Jaws Pliers 9 1/4"
3Y	Klein Needle Nose Pliers
2G	Channellock 12" Pliers
26G	Klein Diagonal Cutters
26K	Klein Spring Loaded Pliers
MH2	Milwaukee High-Leverage Lineman's Pliers

26B	Klein Thread Chaser
3Q	Klein Thread Chaser-Hard Jaws
26Q	Klein 10" Pump Pliers
26D	Klein Heavy Dipped Hardened Jaws
3X	Klein Needle Nose Journeyman
2F	Channellock 10" Pliers
26F	Klein Cable Cutters
90B	Semi-con Roller Grip
26H	Klein High-Leverage Cable Cutter
MH1	Milwaukee 10" Tongue and Groove Pliers



89K

FS999

20oz Straight Claw Hammer with 14\"/>



89M

606S

28oz Straight Claw Hammer with 15\"/>



53Z

707M

32oz Milled Face Straight Claw Hammer with 18\"/>



89N

FS505M

24oz Milled Face Hammer with 17\"/>



89R

L36F

36oz Lineman's Hammer with 14\"/>

M1

Milwaukee 4in1 Lineman's Hammer

- 32oz Head
- Milled on one side and smooth on the other
- Fiberglass Handle
- 15"
- Built in staple puller and J-Hook Remover



Klein Lineman's Claw Milled Hammer

- 26 Ounce
- Fiberglass Handle

832-26

53S



Klein Tools Lineman's Hammer-Milled/Smooth Face

- 36 oz head and 14" overall length

89W



MADI 32oz Milled Face Claw Lineman Hammer with staple puller

53H

CMLH-1



MADI 35oz. Milled Face Lineman Hammer with staple puller and "J" Hook Remover

MLH-1

89U



MH3

Milwaukee Multi-Purpose Tool

Incorporates a staple puller, staple pincher, fencing wire cutter, fencing wire puller and general purpose hammer



48-22-6410



Staple Puller

95MM



Klein Demolition Drivers

- Plated metal strike cap protects handle from hammer blows. Unique screwdriver design transfers impact force directly to work surface.

- 3V** 4" Shank; 9" Overall
- 3W** 7" Shank; 12 3/8" Overall



M55

48-22-2859

Milwaukee Demo Driver
11 1/4" Overall Length



Klein Cushion Grip Screwdriver with Heavy Duty Round Shank and Hex Bolster

- 27H** 4" Shank (602-4)
- 27G** 6" Shank (602-6)
- 27F** 8" Shank (602-8)
- 3S** 10" Shank (602-10)
- 3T** 12" Shank (602-12)



Klein Screwdriver with Square Shank

- 27C** 8" Shank (BD308)
- 27E** 12" Shank (BD412)



Klein Cushion Grip Screwdriver with Heavy Duty Square Shank

- 4F** 4" Shank (600-4)
- 4G** 6" Shank (600-6)
- 4H** 8" Shank (600-8)
- 4J** 12" Shank (600-12)



Klein 11-in-1 Screwdriver/ Nut Driver 32500
Contains 3/8", 5/16" and 1/4" nut drivers, #1 and #2 Phillips, 1/4" and 3/16" Slotted, #10 and #15 TORX, and #1 and #2 Square-recess



Klein Wire Bending Screwdriver-Phillips
4" Round Shank

26R



61Q



59H



Descriptions/Pricing

- 26R- Klein Crimper/Cutter
- 61Q- Klein Coaxial Cable Cutter
3/4" Maximum Capacity
- 59H- Klein Coaxial Cable Cutter
1" Maximum Capacity

25T



910-6

Klein Tools Fiberglass Ruler
- Inside Read

25S



900-6

Klein Tools Wood Ruler
- Inside Read



M99

Milwaukee Composite Folding Ruler
- Inside Read

48-22-3801

HAND TOOLS



Klein Journeyman™ T-Handle Hex Keys

6" Overall Length

3R7 5/16"

3R8 3/8"

9" Overall Length

4R1 5/16"

4R2 3/8"



27K

27L

27M

27K- 6 inch Sizes 5/64, 3/32, 7/64, 1/8, 9/64, 5/32

and 6 Metric Sizes 1.5, 2, 2.5, 3, 4, 5

27L-9 inch sizes 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4

27M- 9 inch sizes .05, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16



270

Five Key Set

Sizes: 3/16", 7/32",
1/4", 5/16", 3/8"



90F

Burndy Wire Mike

- For measuring wire sizes on stranded, solid, and ACSR



61A

Klein Can Wrench

3/8 x 7/16
For Phone & CATV Boxes

68005



25W

Klein Double Edged Knife w/ Sheath

- 5 1/2" Blade

DK06



Klein Broad-Head Bull Pin
- forged, heat-treated bull pin increases efficiency by providing a larger striking surface

53X

10" Long; 1 1/16" Top Diameter; 1/4" Point 3256

53Y

13 3/4" Long; 1 1/4" Top Diameter; 5/16" Point 3255



99Y

Speedi-Spreader Cable Spreader

- "The Solution to Midspan Nightmares"

- For use on twisted wire secondaries up to 600VAC
- Used when installing Midspan Tap in Triplex cable
- Only 10 Oz. and fits into a ditty bag, bucket or tool board
- Not to be used in place of a permanent Mid-Span Spreader

M25

48-62-6031

Milwaukee SDS-Plus Ground Rod Driver

- for use with SDS-Plus rotary hammers in hammer only mode
- Drives 1/2" and 5/8" ground rods
- 10" overall length



M23

48-62-4091

Milwaukee SDS MAX Ground Rod Driver

- for use with SDS Max rotary hammers in hammer only mode
- Drives 5/8" and 3/4" ground rods
- 10" overall length

25Z



Speedy Sharp Knife Sharpener



48036

25Q

Klein Knife and Scissor Sharpener



24R

631

Klein Cushion Grip Set

1/2, 7/16, 3/8, 11/32, 5/16, 1/4, 3/16



26X

Klein 7-in-1 Nut Driver 32807MAG

- Seven sizes in one tool allow for easy, on-handed driving
- Sizes: 1/4", 5/16", 11/32", 3/8", 1/2", 7/16" and 9/16"



25P

7095

The Buckskinner

Easily removes insulation and semi-con from all types of cable.

RE4

Reliable Manual Ground Rod Driver with Handles (No Thread)

- provides a safe effective method of installing a 5/8" standard ground rod
- Drive Shaft: 29 1/2"L x 7"W x 2 3/4" R
- Weight: 28.5 lbs



4P

702-12

Klein High-Tension Hacksaw 12" Blade



K3 Klein 8-in-1 1,000-Volt Insulated Interchangeable Screwdriver Set

- Includes tip sizes: two #2 Phillips, two 1/4-Inch Slotted, one #1 Phillips, one #1 Square, one #2 Square, and one 3/16-Inch Slotted
- Securely and easily release the blade with a quick twist of the lock collar



27S Klein 1000V Insulated #2 Phillips -4" Shank



27T Klein 1000V Insulated Standard -7" Shank



27U Klein 1000V Insulated Standard -4" Shank



Klein 1000V Insulated Nut Driver

- 27V- 1/2" Insulated Nut Driver- 6" Shank
- 27W- 3/8" Insulated Nut Driver- 6" Shank
- 27X- 7/16" Insulated Nut Driver- 6" Shank
- 27Y- 5/8" Insulated Nut Driver- 6" Shank
- 27Z- 5/16" Insulated Nut Driver- 6" Shank
- 27AA- 11/32" Insulated Nut Driver- 6" Shank
- 27AB- 9/16" Insulated Nut Driver- 6" Shank



Duct Cutter

- The duct cutter is designed to cut smooth wall polyethylene duct
- Fits duct diameters from 1/2" - 2 1/2"



K4 Klein Flip-Blade 1,000-Volt Insulated Screwdriver

- Flip-Blade has a #2 Phillips end and a 1/4-Inch Slotted end
- Securely and easily release the blade with a quick twist of the lock collar



OEL 1000V Insulated T-Handle Wrench with 6" Long Arm

- #91C- 3/16"
- #91F- 5/16"



OEL 1000V Insulated Adjustable Wrench

- 91H 10"
- 91J 12"



Spanner Wrench- 7 1/4"

- Used to install and remove tap and connector plugs on underground electrical systems

TOOLS & TOOL ATTACHMENTS



M2

908

8 oz. Steel Plumb Bob

- Steel plumb bob with plated finish to resist corrosion
- Ties easily to any string or line



52Y

FP-1

MADI 10" Lineman Fuse Plier

- All-in-One Fuse Changing Solution
- Wrenches specifically designed for tightening and removing 9/16", 5/8" and 3/4" fuse nuts
- Cuts #2 AAAC and soft wire



52Z

BSSR-1

MADI Transmission Bell Separator with Staple Remover

- Wedge end easily to push cotter pin back to separate bells
- Integrated staple remover



M7

48-22-0335

Milwaukee 35ft Compact Wide Blade Magnetic Tape Measure

- Up to 15' of Reach
- 2-Sided Printing for Easy Reading



MT6

Milwaukee D-ring (5 Pack) Weight Rating - 5 lbs

- Designed for use with Milwaukee® Self-Adhering Tape to create a secure attachment point on most tools without a lanyard hole
- Metal D-Ring serves as attachment point for tethering



MT7

Milwaukee 12ft Self-Adhering Tape


- Designed to create a secure attachment point on most tools without a lanyard hole
- Self adhering, uses no adhesives
- For use with Milwaukee D-Ring web attachments



BK1

Buckingham Buckeye Bucket Hook with Tether Hole

- Fits up to a 2 1/2" bucket lip
- 40 lb. WLL (3:1 safety factor), two inside accessory hooks with a 15 lb. WLL (3:1 safety factor)



BK3

Buckingham Buck Tool Tether

- Length: 38 in – 51 in.
- Maximum safe working capacity: 15 lbs.
- Twist locking aluminum carabiner
- Adjustable tool loop



BK2

Buckingham Buckeye Bucket Hook with Tether Hole and Tool Tether

- Combination of Bucket Hook and Tool Tether shown on left

TETHERS & TOOL ATTACHMENTS



Squids® 3100 Single Carabiner Tool Lanyard - 10lbs

- Energy absorbing cord with tubular nylon webbing
- Maximum safe working capacity: 10lbs

SQ1 Standard: 35in - 42in

SQ2 Extended: 42in - 54in



SQ3

Squids® 3100F(x) Tool Lanyard Single Carabiner - 10lbs

- Shock absorbing properties reduce the dynamic force on the body or other anchor point if drop occurs
- Extends from 38-48in
- 10lbs maximum capacity



SQ4

Squids® 3108F(x) Tool Lanyard Single Locking Carabiner - 15lbs

- Shock absorbing properties reduce the dynamic force on the body or other anchor point if drop occurs
- Extends from 38-48in
- 15lbs maximum capacity



Milwaukee Locking Tool Lanyard Weight Rating - 10 lbs

- Lanyard body is engineered to provide the best shock absorption, slowing the tool gradually if a drop occurs
- Double-Locking Carabiner

MT1 36" Length



Milwaukee Locking Tool Lanyard Weight Rating - 15 lbs

- Lanyard body is engineered to provide the best shock absorption, slowing the tool gradually if a drop occurs
- Double-Locking Carabiner

MT3 36" Length

MT4 54" Length



SQ6

Squids® 3118F(x) Tool Lanyard Double Action Dual Carabiner - 15lbs

- Shock absorbing properties reduce the dynamic force on the body or other anchor point if drop occurs
- Extends from 38-48in
- 15lbs maximum capacity



SQ8

Squids® 3175 Accessory Anchor

- Static anchor maximum safe working capacity: 400lbs
- Not for climbing or fall arrest
- 23.5in length



53T

Kong Wire Bent Paddle Carabiner - 22kN Strength
1.25" Opening; 4.5" Length




35L

Petzl ST'ANNEAU Dyneema® Sling - 24cm(9.45")
#C07 24



35Q

Petzl ST'ANNEAU Dyneema® Sling - 60cm(23.6")
#C07 60



37Y

Petzl DJINN AXESS Quickdraw - 11" Overall Length
#M060CA00

CUTTERS



Klein Tools®
Fiberglass Handle
Bolt/Guy Cutters

3L 18" Length

3M 24" Length

3N 30" Length



Greenlee®
Fiberglass Handle
Heavy Duty
Bolt/Guy Cutters

33H 18" Length

33J 24" Length

33K 30" Length



HIT®
Fiberglass Handle
Bolt Cutters
- Tested per OSHA
Specifications

33V 18" Length

33W 24" Length

33X 30" Length



Milwaukee Fiberglass
Bolt Cutter with
PIVOTMOVE™
Rotating Handles
- Adaptable rotating
handles allow you to make
more cuts around obsta-
cles common in utility
environments
- UL Classified 1000V
Insulated

MH4 18" Length

MH5 24" Length



HIT®
Fiberglass
Handle
Guy Wire Cutters
- Tested per OSHA
Specifications

24" Length

34M

30" Length

34P



Klein Tools®
Steel Handle
Bolt/Guy Cutters

33Z 14" Length

33ZZ 18" Length

33ZA 24" Length



59A

Klein Tools®
25" Fiberglass Handle Cable Cutters

- Pivot backed off to allow handles open with gravity
- Brush guards help protect against arc-flash

Max Cutting Capacity: 500 MCM Cop-
per/750 MCM Aluminum



Klein Tools®
Fiberglass
Handle
Cable
Cutters

59B 25" Length

59BB 32" Length



59C

Klein Tools®
17"
Utility
Cable
Cutters

63035



1G

Burndy®
Fiberglass Handle
Manual 21" Cable
Cutters

Capacity:
600 kcmil



34X

HIT®
Fiberglass Handles
24" ACSR and Cable
Cutters

- Tested per OSHA
specifications
- Capacity
1" Cu. & Al.
5/8" ACSR

22-ACSRF



59E

Klein Ratcheting Cable Cutters
600MCM
Maximum Cutting

63060



36N

Klein ACSR Ratcheting Cable Cutter
- Cuts up to 336 MCM ACSR
- 400 MCM Copper and 600 MCM Aluminum
- 10.25"

63607



56Z

Klein ACSR Ratcheting Cable Cutter
- Cuts up to 477 MCM ACSR multi-strand
- 600 MCM Aluminum and 400 MCM Copper
- Replaceable Cutting inserts
- Not for EHS guy strand or reinforcement rod
- Compact (Only 13 3/4")

63800ACSR



SL3

Slingco ACSR Ratchet Cutters
- Designed to cut hard cables cleanly and smoothly
- Cuts up to 954 ACSR and other hard cable
- Do not use on energized lines
- 29 1/2"

TCU09280



36T

Jenny Tools 23" C-Jaws Ratchet Cable Cutter
Fiberglass Handles
- Not designed for cutting electrically live cable
- Thumb slide release allows rapid cutting and closing
Capacity
Al. & Cu. 1000MCM ACSR 954

7122



34Y

Jenny Tools 20" C-Jaws Ratchet Cable Cutter
Fiberglass Handles
- Not designed for cutting electrically live cable
Capacity
Al. & Cu. 600MCM ACSR 556

7118



59F

Klein Ratcheting Open Jaw Cable Cutter
- Front opening jaws for tight applications
- Spring release lever for fast jaw reset between cuts
- 11 1/2" Overall Length
Maximum Cutting Capacity:
600 MCM Copper
750 MCM Aluminum

63711



36Q

HIT® Ratcheting Cable Cutters
400MCM Maximum Cutting

22-RCC10



36R

HIT® Ratcheting Cable Cutters
750MCM Maximum Cutting

22-RCC20



36L

Jenny Tools Ratcheting ACSR Cable Cutters- 10.5"
Capacity: 336 MCM ACSR and 350 MCM Cu

9009

UNDERGROUND TOOLS



2Y

Ratcheting penta socket combined with hex (Allen) wrenches are made for working on pad-mount transformers and secondary pedestals
#BW-251



3/8" hex
socket for
"twist-off"
equipment
locks



5/16" Hex
(Allen) for
transformer
secondary bars



58K

MADI Tri-Penta™ Wrench

- 3/8" screwdriver for opening the primary door on 3 phase transformers
- Hand Hole Lid Lifter
- Sleeve spins freely to open transformers and switch gears faster
- Penta Wrench designed for opening transformers and switch gears



59M

Pentahead Socket
1/2" Square Drive



Inwesco Pentahead Socket
1/2" Square Drive
59MS- Small Penta
59ML- Standard Penta



590

"T" Wrench with 3/4"
Pentahead socket



58N

Ratcheting Box Wrench

Has 5/16" hex shaft on one side, 3/8 hex shaft on other side. Penta on handle. Excellent tool for tightening bus bar set screws.

RBW-3P



580

Ratcheting Box Wrench

Has 5/16" hex shaft on one side, 3/8" hex shaft and Ratcheting penta on other end. Ergonomic handle.

RBW-51638RP

58L



PW2
Standard penta head
socket with handle grip

58M




PHW1 Has a standard penta socket on one end and a 3/4" hex on the other end with captive leverage handle



63G

Rigid Manhole
Hook 30"



63H

Flexible Manhole
Hook



Ergo Kneeling Pad Reduces Knee Trauma and Lower Back Stress

#92B- 8" x 16" #5040
#92C- 14" x 21" #5050

Ripley Cable End Strippers for 600 Volt Secondary Cable



**Square Cut Bushings (AWG)
Carried in Stock**

#6	10-32540	60 MIL Ins.
#4	10-37540	60 MIL Ins.
#2	10-47560	80 MIL Ins.
#1	10-52560	80 MIL Ins.
1/0	10-55060	80 MIL Ins.
2/0	10-60060	80 MIL Ins.
3/0	10-65060	80 MIL Ins.
4/0	10-70060	80 MIL Ins.
250MCM	10-75060	80 MIL Ins.
350MCM	11-85060	80 MIL Ins.
500MCM	11-97560	80 MIL Ins.

* If you need a bushing that isn't on this chart, please let us know the Ripley Part# or Type of Conductor, AWG or Copper, Square or Chamfer Cut, Ins. Thickness



4x4 Cable End Stripper
- Comes with 4 Bushings



2x2 Cable End Stripper
- Comes with 2 Bushings



Power Driven End Stripper w/ Snap on Bushing
Strips 3/4" to 2 1/2" lengths. To select Bushing sizes use 4x4 bushing table.
This tool comes with one bushing. WS68snap
Designed for use with a low or variable speed power drill
Bushings snap in. Hex wrench not needed.

57A- Bushings 57AA- Repl. Bushing Blades



Bugwrench Ratcheting Wire Stripper with Eyeloop
Accepts Ripley 4X4 Bushings
(Bushing not included)



Speed Systems 2750 Secondary Cable End Stripper
No Bushings Required

-Designed to End Strip 600V Cable (#4 thru 1000MCM). No Bushings required to adjust the tool to varying cable diameters.
Unlimited stripback length
- 45 mil to 110 mil insulation thickness

57R- End Stripper
57RR 2781Repl. Blade



Ripley WS 22 Double-Ended End Stripper
- For 600 volt cables 1/0 AWG to 1000 MCM
- Comes with 2 Bushings from chart below



Ripley WS 22A Power Driven End Stripper 3/8" Drill Drive
- For 600 volt cables 1/0 AWG to 1000 MCM
- Comes with 1 Bushing from chart below



57X-Extra Bushings

57Y- Repl. Blade

Ripley WS22 and WS22A In Stock Bushings to Square Cut Insulation

1/0 15-60075 95MIL	700 15-120075 95MIL
2/0 15-65075 95MIL	700 15-122590 110MIL
3/0 15-70075 95MIL	750 15-122575 95MIL
4/0 15-75075 95MIL	750 15-125090 110MIL
250 15-80075 95MIL	800 15-127575 95MIL
350 15-90075 95MIL	800 15-130090 110MIL
500 15-105075 95MIL	900 15-132575 95MIL
500 15-107590 110MIL	900 15-137590 110MIL
600 15-112575 95MIL	1000 15-137575 95MIL
600 15-115090 110MIL	1000 15-140090 110MIL

PRIMARY CABLE TOOLS



1542-2CL

Speed Systems Primary Cable Insulation Stripper

57L-Cable Range :
1/2" to 1 3/4"

Comes with wedge blade
installed and spare
straight blade; Includes
scale gauge

57L

57LL-1562 Wedge Blade
(xlp)
57LA-1581 Straight Blade
(epr)
57LS- 1646X Scale Gauge



58Q
1542-2AS

Speed Systems Combination Stripper

Strips cable insulation and scores
semi-con. All the features of the
1542-2CL and the 1700 scorer are
combined in this tool

Cable Range :
1/2" to 1 3/4"

Comes with wedge blade installed and
spare straight blade; includes scale
gauge
58Q

57LL-1562 Wedge Blade (xlp)
57LA-1581 Straight Blade (epr)
57MA- 1678 Scoring Blade



57N

Chamfering Tool

57N- CT-1 For Cable O.D. 1/2" to 1 3/8"

57NN- CT-2 For Cable O.D 1 1/4" to 2 3/4"

57NA-2672 Replacement Blade



Semi-Con Scorers

Adjustable blade scorer with square cut / spiral
cut-saddle relief for close end cut.

57M-1700-SS For cable diameter 1/2" to 2"
57MM-1800-SS For cable diameters 1 3/4" to 3"
57MA-1678 Replacement Blade



58R

Mark I Speed Stripper with Wedge Blade

(tool stop not included)

CABLE RANGE 3/4"-2"

58RA- Wedge Blade
(15-35kV XLP)
58RB- Straight Blade
(15-35kV EPR)
58RC- Shaving Blade
(bonded semi-con)
58RE- Tool Stop



58U

Mark II Speed Stripper with Wedge Blade

(tool stop not included)

- CABLE RANGE 1 3/4"-3"

58RA- Wedge Blade
(15-35kV XLP)
58RB- Straight Blade
(15-35kV EPR)
58RC- Shaving Blade
(bonded semi-con)
58UT- Tool Stop



58E

Bushing Insert Tool with Torque Key (fits all loadbreak bushing inserts)

BIT/TK120XQ 58E

58EE- For deadbreak
bushing inserts order
BIT/TK120XN



58T

2900



60Z


2900LS

Aerial Tree Wire/Spacer Cable End Stripper and Mid-Span Stripper

- Cable Outside Diameter .4" - 1.66"

- Performs both end strip and mid-span strips on 5kV, 15kV, and 25kV;
Insulation up to 300MIL

58T(Standard Model)
60Z (Stick Operable Model)
58TA Repl. Blade (2872)



58W

Bushing Insert Tool with Torque Limiter (5/16" hex Shaft)

- Preset torque limiter takes
guesswork out of bushing
installation (180 in.-lb.)
- Can be used for bushing
removal

BIT/E180AT



58C

LPW1525/TK120X

Probe Installation Tool with Tor-Key

- Combination Tool with preset
torque limiter.
- For all 15kv & 25kv elbows and
Elastimold
35KV elbows.



58S

LPW1525/TK120XN

Probe Installation Tool with Tor-Key and Neutral Winder

- Combination Tool with preset
torque limiter.
- For all 15kv & 25kv elbows and
Elastimold 35KV elbows.



58A

**PIT 1T Load Break
Probe Insertion Tool**
- For 15 to 35 KV cables
- 125 inch-pound torque
delivery system



58B

**LBIT-1T
Load Break
Bushing
Insertion Tool**

- For 200 amp Bushing
inserts with internal
hexagon socket drive
- Prevents stud breakage
with 180 in-lb. Preset torque
setting



69W

WS 5A



WS 5A-DA

58X



58Z

**SW2 Ratchet
Wrench**

- For extra leverage on
WS 5A Tool

WS 5A and WS5A-DA Adjustable End Stripper

- For 600 volt to 35 KV Cables
- Adjustable Strip Stop with rotary mechanism eliminates need for hex wrench
- Adjustment window allows easy setting of stop for precise strip lengths
- .260 to 1.285 in. cable O.D.
- Strips XLPE, polyethylene, and EPR insulation up to 400 mils thick
- Bushings sold separately
- WS5A-DA model comes with 3/8" Drill Adapter

69W- WS 5A
58X- WS 5A-DA
69XR- Bushings
69XB- Repl. Blade
69XC- Drill Adapter

WS 5 Series Bushing Selection Table

Cable O.D. (inch)	Bushing #	Cable O.D. (inch)	Bushing #
.260 - .285	WS 5-300	.761 - .785	WS 5-800
.286 - .310	WS 5-325	.786 - .810	WS 5-825
.311 - .335	WS 5-350	.811 - .835	WS 5-850
.336 - .360	WS 5-375	.836 - .860	WS 5-875
.361 - .385	WS 5-400	.861 - .885	WS 5-900
.386 - .410	WS 5-425	.886 - .910	WS 5-925
.411 - .435	WS 5-450	.911 - .935	WS 5-950
.436 - .460	WS 5-475	.936 - .960	WS 5-975
.461 - .485	WS 5-500	.961 - .985	WS 5-1.000
.486 - .510	WS 5-525	.986 - 1.010	WS 5-1.025
.511 - .535	WS 5-550	1.011 - 1.035	WS 5-1.050
.536 - .560	WS 5-575	1.036 - 1.060	WS 5-1.075
.561 - .585	WS 5-600	1.061 - 1.085	WS 5-1.100
.586 - .610	WS 5-625	1.086 - 1.110	WS 5-1.125
.611 - .635	WS 5-650	1.111 - 1.135	WS 5-1.150
.636 - .660	WS 5-675	1.136 - 1.160	WS 5-1.175
.661 - .685	WS 5-700	1.161 - 1.185	WS 5-1.200
.686 - .710	WS 5-725	1.186 - 1.210	WS 5-1.225
.711 - .735	WS 5-750	1.211 - 1.235	WS 5-1.250
.736 - .760	WS 5-775	1.236 - 1.260	WS 5-1.275
		1.261 - 1.285	WS 5-1.300

Banana Peeler

Precise removal of
primary cable jackets and
semi conductor covering.

Cable diameter Range
57F-BPA .38" - .750"
57G -BP 1A .75" - 1.10"
57H -BP 2A 1.25" - 1.75"

57HH- Repl. Blade



57F



58G

Ripley Semi-con Scoring Tool

- Accommodates cable ranges
of .31" - 1.77"
- Easy and precise blade
adjustment from
0" - .16"
- Allows for longitudinal,
spiral and square cuts

58H - Repl. Blade



Ripley 1/2" Square Drive Torque Wrench and Hex Shaft

- For 600 amp connector system with rubber
molded components
- Dual hex shaft 5/16" and 3/8"
- Torque wrench supplies the proper torque
(50-60 ft-lb) as recommended by the
manufacturer



57Z

**Speed Systems
Installation Hex Shaft
with 1/2" Square Drive**
- For installation and
removal of 600A reducing
tap plug bushings
- 3/8" Hex Shaft with
5/16" internal hex at end

LRTP-12



59Z

Ripley Flat Nose Pliers

- Ergonomic handles
- 5.7" Length

59L

Torque Wrench and Shaft

59P

Shaft Only

59R

Torque Wrench Only



Milwaukee M18 Fuel 7/16" Hex Utility High Torque Impact Wrench w/ One-Key

M43 Kit: Includes qty 2- 5Ah batteries, charger, bag and inverter- Model# 2865-22

M44 Bare Tool- Model# 2865-20



M64

M18 Fuel 1/4" Hex Impact Driver
(Tool Only) Model# 2953-20



MB1

M18 Fuel 1/2 Compact Impact Wrench w/ Pin Detent Bare
Tool Model# 2855P-20
- 4.9" length provides most access in tight spaces
- up to 250 ft-lbs of fastening and nut-busting torque



MB2

M18 Fuel 1/2" Mid-Torque Impact Wrench w/ Pin Detent
(Tool Only) Model# 2962P-20
- provides 650 ft-lbs of nut-busting torque



MB3

M18 Fuel 1/2" Hammer Drill/Driver
(Tool Only)
Model# 2904-20



M71

Milwaukee M18 Fuel Super Hawg Right Angle Drill with 7/16" Quick-Lok
(Tool Only) Model# 2811-20



MR2

M18 Fuel 1" SDS Plus Rotary Hammer
(Tool Only)
Model# 2912-20



MR4

M18 Fuel 1-3/4" SDS MAX Rotary Hammer
Kit: Model# 2718-22HD
Includes qty 2- HD12.0 Batteries, Rapid Charger and Case



M78

Milwaukee M18 1 1/2" Lineman Magnetic Drill Kit
Model# 2788-22HD
Includes qty 2- XC 8.0 Batteries, Charger, Lubrication Tank, Chuck Key, Carrying Case, Chuck Adapter and qty 2 1" Retractable Pilot Pins



Milwaukee M18 Force Logic 6T Linear Utility Crimper Kit

- Includes 2 M18 2.0 Batteries, Charger and Bag



Milwaukee M18 Force Logic 6T Utility Crimper

- Includes 2 M18 2.0 Batteries, Charger, Bucket Bag and Carabiner

- M38** Crimper Kit with D3 Grooves and Fixed BG Die Model# 2978-22BG
- M39** Crimper Kit with D3 Grooves and Fixed O Die Model# 2978-220
- M24** Bare Tool without head, batteries, charger or case Model# 2978-20

- M53** Crimper Kit with D3 Grooves and Fixed BG Die Model# 2678-22BG
- M54** Crimper Kit with D3 Grooves and Fixed O Die Model# 2678-220



M81

Milwaukee M18 Force Logic 6T Pistol Utility Crimper/Cutter without Jaws (Tool Only) #2977-20

- Use with existing Milwaukee 6T interchangeable jaws
- 340 degree rotating head
- One-Key Technology



M82

Milwaukee M18 6T Fixed BG Crimping Jaw

49-16-BGD3
- slot for "W" style dies and fixed BG die in front



M83

Milwaukee M18 6T Fixed O Crimping Jaw

49-16-10D3
- slot for "W" style dies and fixed O die in front



M68

Milwaukee M18 6T- 1/2" EHS Guy Wire Cutting Jaw

49-16-2777
Capacity: 1/2" EHS Guy Wire, 1/2" Non-EHS Guy Wire, 4/0 AWG ACSR, 3/8" Rebar, 3/8" Ground Rod



M73

Milwaukee M18 6T- 750 MCM Cable Cutting Jaw

49-16-2772
Capacity: 750 MCM Cu / 1000 MCM Al



M74

Milwaukee M18 6T- 477 ACSR Cutting Jaw

49-16-2773
Capacity: 477 Hen ACSR, 3/8" Non-EHS Guy Wire, 3/8" Rebar, 3/8" Ground Rod



M8

Milwaukee 1/2" EHS Guy Wire Replacement Blades



M9

Milwaukee 750 MCM Cu/Al Replacement Blades



M10

Milwaukee 477 ACSR Replacement Blades



Milwaukee M18 Force Logic 12 Ton Utility Crimper

- Engineered to reduce weight and improve balance; 350° rotating head; for use with "U" style dies; Features Milwaukee® ONE-KEY™ Technology

M50

Crimper Kit with charger, 2.0 battery, 5.0 battery, carabiner, bag and inverter Model# 2778-22



Milwaukee M18 Force Logic 15 Ton Crimper

- Crimper's in-line design and center-balanced grip allows you to use it with one hand; 350° rotating head; for use with "P" style dies or "U" style dies with use of adapter; Features Milwaukee® ONE-KEY™ Technology

M52

Crimper Kit with charger, 2.0 battery, 5.0 battery, P to U-Die Adapter, carabiner, bag and inverter Model# 2879-22



M77

Milwaukee M18 Force Logic 1590 ACSR Cutter Kit w/ ONE-KEY

Model# 2777-21

- Cuts up to 1590 Falcon ACSR and 1/2" EHS Guy Wire
- Includes qty 2- XC 5.0 Batteries, Charger, Inverter, Utility Bag and Carabiner



M66

Milwaukee M18 Force Logic 3" Underground Cable Cutter w/ Wireless Remote Model# 2776R-21

- Removes the physical connection to the tool allowing linemen to cut up to 1500MCM copper 15kV wirelessly
- The kit includes wireless remote, M18 XC 5.0 extended capacity battery, AC/DC wall and vehicle charger, utility bag and carabineer



M48

Milwaukee M18 Fuel 16" Chainsaw (Tool Only) Model# 2727-20

- Delivers the power to cut hardwoods; power and performance of a gas engine up to 40CC



Milwaukee 16" Saw Chain Replacement #49-16-2715

- The chain features a durable design and is weather resistant for increased life

M11



Milwaukee 16" Chainsaw Guide Bar #48-09-3001

- To be used with the Milwaukee M18 FUEL™ 16" Chainsaw and 16" Chainsaw Chain

M12



M3

Milwaukee M18 Fuel Metal Cutting Circular Saw (Tool Only)

Model# 2782-20

- 5-3/8" – 5-7/8" Metal Saw delivers the fastest cuts
- Comes equipped with a 30T 5-3/8" METAL TECH™ Carbide-Tipped Metal Saw Blade and Blade Wrench



M84

Milwaukee M18 Fuel Deep Cut Band Saw (Tool Only)

Model# 2729-20

- Versatility to cut up to 5 in. by 5 in. material in one pass and adjustable shoe allows for less tool rotation when cutting material above 5"



M57

Milwaukee M18 Fuel Sawzall Recip Saw (Tool Only)

Model# 2821-20

- Fastest cutting reciprocating saw in its class



M95

Milwaukee M18 Fuel Hackzall (Tool Only)

Model# 2719-20

- Fastest cutting and most powerful one-handed reciprocating saw



M93

Milwaukee M18 Cordless 10oz. Caulk and Adhesive Gun (Tool Only)

Model# 2641-20

- Deliver caulk or adhesives smoothly and steadily, even with the highest viscosity materials, with the incredible pushing force



M5

Milwaukee M18 Fuel 4-1/2" / 5" Grinder, Paddle Switch No-Lock (Tool Only)

Model# 2880-20

- Delivers power of corded grinder; wheel sold separately



MC1

Milwaukee M18 Compact Blower (Tool Only)

Model# 0884-20

- 3-Speed electronic switch and variable speed trigger allow for versatile clearing power



MB5

Milwaukee M18 Fuel Blower (Tool Only)

Model# 2724-20

- Gets to full throttle in under 1 second; Maximum Air Speed: 120 MPH



M14

Milwaukee M18 Force Logic 10,000 psi Hydraulic Pump Kit #2774-21HD

- The cordless hydraulic pump is designed to be fully compatible with all existing 10,000psi rated hydraulic hoses and heads
- 6ft Controller Cord with On-Board Storage for Easy Operation
- Includes HD12.0 Battery and Rapid Charger



MB6

Milwaukee Bucket Hanger for M18 Force Logic 10,000psi Hydraulic Pump #49-12-2776

Milwaukee M18 Top-Off 175W Power Supply #2846-20

- (1) AC 120V outlet, (1) USB-C PD port, and (1) USB-A port
- Quickly charge up to three devices at the same time
- Battery not included



MB7



M85

Milwaukee M18 Six Pack Sequential Charger Model# 48-59-1806

- Charges up to Six Batteries Sequentially



M86

Milwaukee M18 Dual Bay Simultaneous Rapid Charger Model# 48-59-1802

- Charges 2 batteries simultaneously, over 3X faster than standard sequential chargers



M87

Milwaukee M18 / M12 Vehicle Charger Model# 48-59-1810

- Allows users to charge battery packs on the go from the DC Outlet of any vehicle



M75

Milwaukee M18 Redlithium XC5.0 Extended Capacity Battery Model# 48-11-1850



M76

Milwaukee M18 Redlithium High Output XC6.0 Battery Model# 48-11-1865



M88

Milwaukee M18 Redlithium High Output XC8.0 Battery Model# 48-11-1880



M89

Milwaukee M18 Redlithium High Output HD12.0 Battery Pack Model# 48-11-1812



Greenlee Battery Crimping Tool EK425LX

- 18V Lithium-Ion Battery; Up to 325 crimps per charge
- 6-Ton Crimping Force
- Can be used with all industry "W" style crimping dies
- When crimp is completed, signals the operator by automatically opening the jaws
- LED work light illuminates dark work areas
- Equipped with Bluetooth Communication enabled via the Greenlee Gator Eye app. Features LED display screen communicating pressure and battery levels as well as tool diagnostics.
- Two batteries, battery charger, and convenient bucket pouch included

Available Models (Call For Current Pricing)

- 79MM** CJD30 Jaws- D₃ and O Die grooves w/ 120 volt Battery Charger EK425LXD011
- 79PP** CJD30 Jaws- D₃ and O Die grooves w/ 12 volt Battery Charger EK425LXD012
- 79QQ** CJD3BG Jaws- D₃ and BG Die grooves w/ 120 volt Battery Charger EK425LXDBG11
- 79RR** CJD3BG Jaws- D₃ and BG Die grooves w/ 12 volt Battery Charger EK425LXDBG12



Chargers for Battery Operated Tools

- 95UU** 120V AC Charger 3.0Ah, 4Ah and 5Ah 18V Lithium-Ion Batteries- Makita

- 99XX** 12V DC Charger for 3.0Ah, 4Ah and 5Ah 18V Lithium-Ion Batteries- Makita



- 99A5** 5.0Ah Makita 18V Lithium Ion Battery



Burndy PATCUT245L5 Battery Actuated Cutter

- 18V Lithium-Ion
- Latch style head for mid-span cuts
- For up to 2.45" O.D. AL/CU
- Comes with case, charger and 2 batteries
- Not for use on steel, ground rod, rebar, or guy wire



Burndy PATCUT129L5 Battery Actuated Cutter

- 18V Lithium-Ion
- Capable of cutting 1.29" AL/CU, 1113 ACSR, 5/8" Ground Rod, 1/2" Rebar, 5/8" diameter soft steel bolts, up to 1/2" standard guy strand and up to 3/8" EHS guy strand
- Comes with case, charger and 2 batteries



Burndy PATCUT2156L5 ACSR up to 2156 kcmil

- 18V Lithium-Ion
- Capable of cutting Copper/Aluminum up to 2"; ACSR up to 2156 kcmil; Ground Rod up to 3/4"; Standard and EHS Guy up to 9/16"; Soft Steel Bolts up to 3/4"
- Comes with case, charger and 2 batteries

BURNDY CRIMPERS



18V Lithium-Ion Lightweight Burndy Patriot In-Line 6 ton Battery Actuated Tool- Ergonomic Design

- can be operated with one hand allowing for advance, retract, and hold functions for easier operation
 - uses "W" style dies in the permanent D₃ groove
 - LED worklight
 - supplied with vinyl tool bag
- works with Makita 3.0Ah, 4.0Ah and 5.0Ah batteries

Without Charger and Batteries

1QL

PATMD6LWLCB with "BG" and D₃ Grooves- Call for Price

1RL

PATMD68LWLCB with "O" and D₃ Grooves- Call for Price

Makita batteries and chargers on page 52



Burndy PAT600L5

6-Ton Battery Actuated Crimping Tool

- 18V Lithium-Ion
 - Permanent "D₃" groove accepts all "W" dies
 - Completes a crimp in approximately 3 seconds
 - 180° Head Rotation
 - Comes equipped with carrying case, battery charger and two batteries
- Please Call For Pricing



Burndy PAT750L5

12-Ton Battery Actuated Crimping Tool

- 18V Lithium-Ion
 - Capable of using all "U" style dies
 - High speed hydraulic pump
 - 355° Head Rotation
 - Comes equipped with carrying case, battery charger and two batteries
- Please Call For Pricing



Burndy PAT46LWL5

15-Ton, Lightweight Latch Head

- 18V Lithium-Ion
 - Uses P or U Style Dies (PUADP-1 adapter needed if using U dies)
 - 2" Jaw opening
 - 355° Head Rotation
 - Comes equipped with carrying case, battery charger and two batteries
- Please Call For Pricing



Burndy PAT46LWSL5

15-Ton, Lightweight Scoop Style C-Head

- 18V Lithium-Ion
 - Uses P or U Style Dies (PUADP-1 adapter needed if using U dies)
 - 2" Jaw opening
 - 355° Head Rotation
 - Comes equipped with carrying case, battery charger and two batteries
- Please Call For Pricing



Burndy OH25 Dieless Full Cycle Ratchet

- Installs Service Entrance Splice Connectors #10-1/0
- Ratchet Mechanism does not allow handles to open until full cycle is complete



Burndy Hand Operated Crimping Tool

- Hickory Handles
- D₃ Groove accommodates "W-" die inserts
- Installs full range of connectors: #14 through 4/0

1A

MD6 with "BG" and D₃ Grooves

1B

MD6-8 with "O" and D₃ Grooves



Slingco Mechanical Crimping Tool

- Ergonomic handles for comfortable use and maximum leverage
 - D₃ Groove allows W Dies
- TCR7004: BG and D₃ Grooves
TCR7002: O and D₃ Grooves

SL4

SL5

Burndy W-Dies

Aluminum

W-BG	W-167
W-O	W-237
W-KK	W-239
W-C	W-241
W-K840	W-243
W-161	W-245
W-162	W-247
W-163	W-249
W-164	W-31ART
W-165	W-660
W-166	W-687
W-K737	W-702
W-K747	

Copper

W-4CRT	W-27RT
W-2CRT	W-28RT
W-1CRT1	W-29RT
W-25RT	W-31RT
W-26RT	W-34RT

Burndy U-Dies

Aluminum

U-1CART	U-28ART
U-2CART	U-29ART
U-25ART	U-30ART
U-26ART	U-31ART
U-27ART	U-34ART
U-39ART2	U-36ART

Copper

U-2CRT	U-28RT
U-1CRT	U-29RT
U-25RT	U-30RT
U-26RT	U-31RT
U-27RT	U-34RT
U-39RT	U-36RT

Other

U-654	U-655
U-660	U-D3
U-O	U-C
U-D	U-N
U-BG	U-997

Burndy P-Dies

P-39ART	P-44ART
P44RT	P-724



79T

Burndy W-28K Cutting Die

- #4-4/0 ACSR, AL, CU



99W

Burndy PUADP-1 "U" Die Adapter

- Allows use of "U" dies in tools equipped with "P" die slot



1K

Jenny Tools XPJ Compression Tool- 2, 4, 6

- This rugged and lightweight fiberglass handled XPJ compression tool has 3 fixed die nests machined into the tool jaws for crimping #2, #4 & #6 non-insulated connectors



M67

Milwaukee 15T P to U-Die Adapter

49-15-PUAD

- allows for use of U-Dies in 15T Crimper



79V

Burndy W-Die Tree

For Convenient Storage of W Style Dies



Klein Tools 7/16" High Torque Impact Wrench

- Designed for professional impact fastening and drilling applications
 - 7/16" Quick-Release Chuck
 - Up to 500 ft-lbs max torque; 0-1900 RPM
- Multi-speed trigger control for a variety of applications

79SB

Bare Tool

79S

Tool with Bag, 2- 20V 4Ah Dewalt Batteries and Dewalt Charger



Klein Tools Battery-Operated Cable Cutter

- One tool that cuts copper, aluminum, ACSR and EHS Cable
 - Replaceable insert blades
 - Two work lights
- Cuts 750 MCM Copper, 1500 MCM Aluminum, 1590 MCM ACSR and 1/2" EHS
- Includes tool, 2 20V 4 Ah batteries, charger and bag

10Y

Kit #BAT20GD14H



Burndy Plastic Die Case

W-Die Case(Plastic) - fits 12 dies

98E

U-Die Case(Plastic) - fits 15 dies

98N



18" TEFLON DEEP CUT

QUICK CHANGE

UTILITY POLE **IMPACT**

WRENCH AUGER BITS

28T 7/16 HEX SIZE

DIAMETER	18" Length
9/16"	08806
11/16"	08808
13/16"	08810
15/16"	08812
1 1/16"	08814



28Z Wood Owl 7.5" x 9/16"
Quick Change Bit

24" TEFLON DEEP CUT

QUICK CHANGE

UTILITY POLE **IMPACT**

WRENCH AUGER BITS

28W 7/16 HEX SIZE

DIAMETER	24" Length
9/16"	01006
11/16"	01008
13/16"	01010
15/16"	01012
1 1/16"	01014



Wood Owl 18" Nail Chipper TRI-CUT Auger Bit - 7/16 Quick Change Shank

- TRI-CUT design with 3 precision ground edges for fast, smooth cutting without resistance
- Reduces nails to chips without grabbing and leaves a clean hole with minimal "blowout."

28Y

DIAMETER	18" Length
9/16"	03806
11/16"	03808
13/16"	03810
15/16"	03812



M60

Milwaukee Shockwave Linemans Impact Auger Bit 7/16" Hex Quick Change Shank 18" Length

DIAMETER	18" Length
11/16"	48-13-6705
13/16"	48-13-6707
15/16"	48-13-6709

M70

Milwaukee Shockwave Linemans Impact Auger Bit 7/16" Hex Quick Change Shank 24" Length

DIAMETER	24" Length
11/16"	48-13-6805
13/16"	48-13-6807
15/16"	48-13-6809

M80

Milwaukee Shockwave Linemans Impact Auger Bit 7/16" Hex Quick Change Shank 30" Length

DIAMETER	30" Length
11/16"	48-13-6905
13/16"	48-13-6907
15/16"	48-13-6909



Milwaukee Shockwave Lineman's Fiberglass Drill Bits

- Engineered for fiberglass and composite poles and arms
- 7/16" hex for quick connect

FB1 9/16" x 12"

FB2 11/16" x 22"

FB3 13/16" x 22"

FB4 15/16" x 22"



M69

Milwaukee Lineman's 10 Piece 2-in-1 Socket Set

- Contains the following 12PT 2-in1 Sockets: 3/8" to 1/2", 7/16" to 5/8", 9/16" to 3/4", 11/16" to 7/8", 13/16" to 1", 1-1/8" to 15/16"; qty 2 7/16" to 1/2" adapters; qty 2 1/4" to 1/2" adapters



Milwaukee Shockwave Lineman's 2-in-1 Sockets

- 1/2" Drive
- Comes with 7/16" to 1/2" Adapter
- 12PT Design

M96

9/16" x 3/4"

M98

15/16" x 1-1/8"



78Z

66010

Klein 6 Piece 2-in-1 Impact Socket Set

- Twelve sizes combined into six sockets including: 1-1/8 x 15/16-Inch, 1 x 13/16-Inch, 7/8 x 11/16-Inch, 3/4 x 9/16-Inch, 5/8 x 7/16-Inch, and 1/2 x 3/8-Inch
- Sockets have a high-torque, 12-point design making it easier to position on fasteners
- Deep socket with a 1/2 Inch drive works great for pole hardware installation and removal



M16

Milwaukee 12pc Shockwave Impact Duty 1/2" Drive SAE Deep 6 Point Socket Set

- The following sizes are included: 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1, 1-1/16



K9

66031

Klein 3-in-1 Slotted Impact Socket, 12-Point, 3/4 and 9/16-Inch

- Impact socket features an alignment slot to tighten and loosen most hot-line clamps
- Deep socket with a 1/2" drive works great for pole hardware installation and removal



78Q

66001

Klein 2-in-1 Impact Socket 12-Point, 3/4" x 9/16"

- Hands free adjustment between socket sizes
- Deep socket with a 1/2" drive works great for pole hardware installation and removal



K14

66030

Klein 2-in-1 Coated Impact Socket, 12-Point, 3/4 and 9/16-Inch

- 20% lighter than Klein #66001
- Hands free adjustment between socket sizes
- Deep socket with a 1/2" drive works great for pole hardware installation and removal



RK3

Rauckman BugWrench 2-in-1 Socket, 3/4" and 9/16"

- 12 Point design fits both hex and square head hardware
- Impact grade, deep well with 1/2" drive



M46

Milwaukee Shockwave Lineman's Pole Step Socket

- Designed for removal of 5/8" pole steps and features quick insert slot
- 1/2" Drive (7/16" x 1/2" adapter included)



79Y

Inwesco Pole Step Driver

- Rapidly places or removes a standard 1/2" step in a wood pole
- Fits 1/2" Drive Wrenches



78XN



Madi Slot Socket PLUS SS-2

- Multi-use wing nut and eye bolt type clamp applications
- Fits 3/4" Square Nut on a 1/2" Bolt
- Improved fit on large J Hooks
- 1/2" Drive



MH6

Milwaukee Shockwave Lineman's J Hook Removal Socket

- Designed for use with 7/16" J hooks
- 1/2" Drive (7/16" x 1/2" adapter included)



55S

White Industrial Tool Inc. Drill Chuck - 1/2" Square

- Converts your 1/2" Square Drive Drill into 7/16" Quick Change Hex

Milwaukee Lineman's Hex Bit Socket

- 1/2" Square drive
- 1-3/4" hex fastening depth



MH7

5/16" Hex

MH8

3/8" Hex

MH9

1/2" Hex



1/2" Male Square x 7/16" Hex Shank

79L

Standard (low/mid-torque use)

79W

Heavy Duty (high-torque use)



1/2" Male Square x 7/16" Hex Shank with Detent Pin

79K

Standard (low/mid-torque use)

79X

Heavy Duty (high-torque use)



MC2

Milwaukee 1/2" Square to 7/16" Quick Change Chuck #48-66-0061



M63

Milwaukee Shockwave Lineman's 7/16" to 1/2" Impact Socket Adapter 48-32-5100



M65

Milwaukee 1/4" Hex to 1/2" Square Impact Adapter 48-32-5034



Milwaukee Shockwave Linemans 3-in-1 Utility Socket

- The socket features a 3 in 1 square design for single sided fastening, eliminating the drop hazard of removing the socket from the adapter to change sizes. The Push and Twist Barrel Lock allows for secure, one-handed size changes, even while wearing gloves.

- for use with 1/2", 5/8" and 3/4" Square Headed Machine Bolts
- Includes 7/16" Hex to 1/2" Square Adapter



Klein NRHD4 4-in-1 Square Impact Socket

- Single ended impact socket wrench with hands free adjustment between socket sizes
- Two coaxial spring loaded sockets in one tool, comprising of four square socket sizes: 3/4", 13/16", 1" and 1 1/8"
- 7/16" hex quick-change adapter included

78RA Adapter Only



Greenlee Nut Runner Socket Wrench

For use with Impact Wrench for installing and tightening pole hardware. Hollow so that bolts that extend up to 6" beyond nut can be accommodated.

COMES IN 2 MODELS

25X NR1- Fits 5/8", 3/4", 13/16", 1" Nut Sizes for 3/8", 1/2", 5/8" Bolt Diameters

25Y NR2- Fits 1 1/8", 1 5/16", 1 1/2" Nut Sizes for 3/4", 7/8", 1" Bolt Diameters

79C Replacement Adapter for NR1 79D Replacement Adapter for NR2



89F

Klein NRHD Distribution 3-in-1 Impact Socket

- 3 sizes in 1 (3/4", 1", and 1 1/8" square sizes)
- 13/16" diameter, 6" long hollow shaft allows use on long threaded bolts
- 7/16" hex quick-change adapter included

89FA Adapter Only



RK4

Rauckman BW-NR100 Impact Socket

- Drives 3 sizes of square nuts on distribution poleline hardware (1/2", 5/8" and 3/4" Bolts)
- Hollow-bore shaft accepts excess bolt length of 6 inches
- 7/16" hex quick-change adapter included

RK5 Adapter Only



89H

Lowell Transmission 3-in-1 Impact Socket

- Square socket Openings: 1-1/8" for 3/4" Hardware; 1-5/16" for 7/8" Hardware; 1-1/2" for 1" Hardware
- 7/16" hex quick-change adapter included

89HA Adapter Only



89SE

Lowell SETSIS Single End Triple Square Impact Socket

- For 1/2", 5/8" and 3/4" Hardware; Change sockets by sliding the locking head; 7/16" hex quick change adapter included; 9" Length

#89SA- Replacement Adapter



99U

Burndy Hydraulic Impact Wrench with 8' Hose and Couplers

- HIW716MAG hydraulic impact wrench
installed with swivels, 8' NCR hose and
flat face couplers



44F

Greenlee Utility Hydraulic Pole Tamper - Hose End Valve

- Makes quick work of setting poles
- Reversible on/off valve for Open- and
Closed-Center hydraulic systems
- Standard with kidney-shaped foot

Specifications:

Length- 60"

Flow Range- 4-6 gpm

Operating Pressure- 1,000-2,000 psi

Pressure Port Thread- 9/16- 18 SAE

Return Port Thread- 3/4- 16 SAE

Call For Pricing

H4802



80B

80C

Greenlee Utility Rubber Low Pressure Hose Set

- Certified nonconductive orange rubber
- Double rayon braid
- Working pressure 2,250 psi tested to 75 kV/ft. for 5 minutes

3/8" x 8' I.D. Hoses with 3/8" NPTF male fittings 135245

3/8" x 10' I.D. Hoses with 3/8" NPTF male fittings 135247


HTMA COUPLERS: 3,000 psi maximum operating pressure



80J

F020198K


HTMA Male Coupler
3/8" NPTF
internal thread



80K

F020197K

HTMA Male Coupler
1/2" NPTF
internal thread



80L

F020195K

HTMA Female Coupler
3/8" NPTF
internal thread



80M

F020196K

HTMA Female Coupler
1/2" NPTF
internal thread



80V

F016775

Adapter 3/8" NPSM x 9/16
- 18 Straight Thread



80P

54925

HTMA Female Coupler
3/4- 16 SAE
O-ring external thread



80Q

54924

HTMA Female Coupler
9/16- 18 SAE
O-ring external thread



80R

54923

HTMA Male Coupler
3/4- 16 SAE
O-ring external thread



80S

54922

HTMA Male Coupler
9/16- 18 SAE
O-ring external thread



80X

F016776

Adapter 3/8" NPSM x
3/4 - 16 Straight Thread

ELECTRICAL TEST EQUIPMENT

32V



2" Jaw Opening

Klein CL900 Clamp Meter

- 2000A AC/DC Current
- 1000 AC Voltage and 1000V DC Voltage
- 60MΩ Resistance
- 6000μF Capacitance
- Audible Continuity
- CAT IV 600V Rating
- Worklight and Backlit Display
- Includes test leads, batteries, and case

32EN



Klein CL700 Clamp Meter

- 600A AC Current
- 1000V AC Voltage and 1000V DC Voltage
- 60MΩ Resistance
- Audible Continuity
- Jaw Size 1 3/8"
- Non Contact Voltage
- CAT IV 600V Rating
- Includes test leads, batteries, and case

51X



IR10

Klein Dual-Laser Infrared Thermometer, 20:1

- Temperature measurements using IR Emission or K-Type Probe
- Range: 40° to 1200° F (-40° to 650° C)
- Custom Pouch, K-Type Probe and Battery

32W



HVNCVT-1

Klein Dual-Range High Voltage Non-contact Tester

- Use to check for the presence of voltage in overhead conductors or find faults in cables
- LOW range for 50V AC to 1.5kV AC
- HIGH range for 1.5kV AC to 132kV AC
- Audible and visual signals indicate the presence of voltage



51K

Knopp K-3

Phase Sequence Indicator

- Rotary type; 60-600 volts, 25-60 Hertz
- Case sold separately

K8



T1250

Klein Rechargeable Thermal Imager

- Has over 10,000 pixels to troubleshoot hot and cold spots; Adjustable emissivity from .10 to .99
- 2.4" TFT LCD Screen
- Store and share images with optional microSD® Card
- Includes micro-USB charging cable and carrying case

32X



HVNCVT-2

Klein Broad-Range High Voltage Non-Contact Tester

- Use to check for the presence of voltage in overhead conductors or to find faults in cables
- 7 sensitivity ranges up to 230kV AC (240V, 4.2kV, 15kV, 25kV, 35kV, 69kV, 115kV, 230kV)
- Audible and visual signals indicate the presence of voltage

51P



Case for Knopp K-3 Phase Sequence Indicator

- nylon rugged carrying case



DVI

HD Electric Digital Voltage Indicator DVI-500T/K02

- Designed to be used on both transmission and distribution systems in overhead and underground applications
- Indicates voltage from 0.1kV-500kV and is auto-ranging
- Includes two overhead probes; one 6" overhead hook probe for transmission and one 2" overhead hook probe for distribution
- Includes underground bushing probe



HVA

HD Electric High Voltage Ammeter HVA-2000

- Measures AC current from 1 to 2000 Amps on system voltages up to 500kV line-to-ground
- Dual measurement modes, peak hold and real time
- Versatile for overhead and underground applications
- Can connect to universal stick or shotgun



VWS

HD Electric Personal Voltage Detector - VWS-20

- The V-Watch Detector is worn around the front of the body and is ideal for line crews, storm restoration workers and first responders seeking an extra layer of protection against unknown voltage sources
- Alerts user to the proximity of high voltage with a load alarm and bright lights
- Typical warning distance: about 7 ft from a 4kV (2.4kV line-to ground) AC conductor; warning distance increases at higher voltages

32Z



Bierer Phasing Meter #83280

- 35kV analog phasing voltmeter/voltage detector, 8 ft. regular cable, 8 ft. extension cable, hook probe, straight probe, 3kV power supply, manual, case



STB Phasing Voltmeter/Sensor with Hot Sticks (full set-6)

- Voltage detection and phasing at capacitance test points or voltage detection and phasing on bare energized conductors (overhead & underground)
- 25' coiled cable included

32G 0-25kV

32P 0-35kV



STB Phasing Voltmeter/Sensor

- Voltage detection and phasing at capacitance test points or voltage detection and phasing on bare energized conductors (overhead & underground)
- 25' coiled cable included

32R 0-25kV

32S 0-35kV

EQUIPMENT BAGS

Klein Lineman Backpack

Unique option for transporting tools to the jobsite. Wide opening (easily accommodates belts and other equipment)
18"L x 23"H x 10"W
Black or Orange



30R



30M

29Y



Klein Premium Vinyl Equipment Bag
Hard Rubber Bottom, Padded Shoulder Strap & 2 Velcro Outside Pockets
24"L x 20"H x 10"W

29X



Klein Large Vinyl Equipment Bag
Hard Rubber Bottom, Padded Shoulder Strap & 1 Velcro Outside Pocket
24"L x 20"H x 10"W

90L



Buckingham Yellow Vinyl Equipment Bag with
Hard Rubber Bottom, Shoulder Strap and 2 Outside Pockets
24"L x 19"H x 11"W

90M



Buckingham Black Vinyl Equipment Bag with
Hard Rubber Bottom, Shoulder Strap and 2 Outside Pockets
24"L x 19"H x 11"W

30X



DragonWear Big Easy Tool Backpack
- Gives optimal organization and easy access to gear
- 22" Height; 16" Width

29C



Bashlin Tool Bag with Shoulder Strap
24"L x 19"H x 11"W

29Q



Bashlin Equipment Bag on Wheels
- Two Outside Pockets
- Connected to Wheels w/ an Extendable Handle
24"L x 19"H x 11"W

29W



Bashlin Backpack Duffle Equipment Bag
- Draw string closure with buckles to secure top cover
- Padded back with adjustable shoulder straps and rubberized handle
- 26" Height
- Front Pocket is 16" x 16" x 4"

29F



Bashlin Equipment Bag on 6" All-Terrain Wheels
- Two Outside Pockets
- Connected to Wheels w/ an Extendable Handle
24"L x 19"H x 11"W



30P

5144BHB140S

Klein Hard Body Bag
15"L x 7"W x 10"H
15 Inside Pockets; 14 Outside Pockets



30Q

5144BHB

Klein Hard Body Bag
15"L x 7"W x 10"H; 15 Inside Pockets



30S

5144BHB

Klein Hard Body Bag with Kickstand
15"L x 7"W x 10"H; 15 Inside Pockets
No Handles 5144BHB



29T

Klein Hard Body Bucket w/ Knife Sheath
- 14" Length x 10" Height x 7" Width
- Includes Leather skinning knife sheath and 14 other interior pockets



M32

Milwaukee Oval Bag
Inside and Outside Pockets - 24 Total
14.57"L X 8.27"W X 10.43"H



2B

Estex Tall Oversized Hard Body Bucket Bag
14 outside pockets, 15 inside pockets
Pocket Depth: 5" Inside/Outside
15"L X 9"W X 11"H



Klein Canvas Bag
29GB 5102-12 12"L x 6"W x 10"D
29GA 5102-18 18"L x 6"W x 14"D
29G 5102-24 24"L x 6"W x 15"D



30C

Estex Hard Body Bag w/ 14 outside pockets and 15 inside pockets
Pocket Depth: 4 3/4" Inside; 5 1/4" Outside
15 x 7 x 9 1815-14HB2G



30L

Klein 17 Pocket Tool Tote with Handles and Shoulder Strap
10 Exterior Pockets, 7 Inside Pockets
58890 15 1/2"L x 10"D x 8"W



M17

Milwaukee Parachute Organizer Bag

- Designed with 6 Interior compartments, 2 exterior pockets, and an exterior zipper pocket
- 11" x 11 3/4"



30G

1216-7

Buckingham "The Deep One"

- 6 pockets on the inside.
- 14" L x 19" H x 6 1/2" W
- Hooks are included



30H

1216-1

Buckingham Bucket Bag

10" H x 6 1/2" W

Hooks are included



MB9

Milwaukee Canvas Utility Bucket

75lb Rating



31R

Klein Tools 100lbs Load Rated Leather Bottom Bucket with Swivel Snap

- No. 1 Canvas
- Leather-reinforced bottom
- Inside Pocket measures 8" x 8"
- 12" Diameter x 17" Height

5104S



31W

Klein Tools 75lbs Load Rated Wide-Opening Straight-Wall Bucket With Swivel Snap

- No. 6 Canvas
- Black molded polypropylene bottom
- 12" Diameter x 15" Height

5109S




31Z

Klein Tools 100lbs Load Rated Vinyl Bucket with Swivel Snap

- Water-resistant vinyl helps keep tools dry
- Black molded polypropylene bottom
- 12" Diameter x 15" Height

5109SV



31Y

Klein Canvas Tapered Bottom Bag

- two pockets for small parts
- snap for hanging
- tapered so parts stay in center



31A

Estex Splicer Tool Bucket

12" Diam. x 15" H
Two outside Pockets.

2071-C



31C

Estex Powder Actuated Tool Bag

12" Diam.. x 15" H

2070-AMP-1



31H

Bashlin 8" diameter x 12" depth plastic bottom



31U

Klein Mini Bucket Bag with Leather Bottom

- 6" Height and 4.5" Diameter
- Great for pencils, pens and other accessories



31K

Mini Bucket bags are great for the car, office and at home. Store your keys, change, pencils or whatever you like! 5"x7"

30AA



55421BP-14

Klein Tradesman Pro Organizer Backpack

- 39 pockets for tons of tool storage
- Tough, durable molded bottom

30AB



55421BP14CAMO

Klein Tradesman Pro Organizer Camo Backpack

- 39 pockets for tons of tool storage
- Tough, durable molded bottom

30AC



55456BPL

Klein Tradesman Pro Organizer Tech Backpack

- 25 pockets for tool storage
- Separate compartment keeps laptop protected from other tools
- Tough, durable molded bottom

30AF



55431

Klein Tradesman Pro Organizer Lighted Tool Bag

- 31 pockets for maximum tool storage
- Twist on/twist off removable LED light can be positioned to illuminate inside the bag or the workspace
- 14" H; 15.25" L; 8" W

31T



2609

Estex Utility Bag

- Water Resistant Yellow Vinyl Coated Nylon
- Large enough for most safety related items
- 17.75" L X 9" W X 10" H

92P



2198

Estex Trash Bag

19"L x 6.5"W x 22"H

31X



5216V

Klein Lineman Duffel Bag

- Water-resistant vinyl protects against the elements
- Mesh strips keep bag aerated so clothes and equipment can dry
- 12" x 12" x 24"

BUCKET ACCESSORIES

39A



Buckingham Aerial Basket Tool Apron
23"L x 22"H

90X



Buckingham Vinyl Tool Apron with Magnet
23"L x 22"H



Klein Vinyl Tool Apron
- 24" Length and 23" height
- Sewn in magnet design (as pictured)

90D

90E

- Without magnet



M42

Milwaukee Aerial Tool Apron
- 25 pockets
- Magnet
- Auger holder
\$164.90



Klein Vinyl Tool Apron with Hot Stick Pocket and Magnet

- Large pouch for hot stick and attachments
- Sewn-in magnet design won't catch on gloves
- Includes 10 hand tool pockets, two pouches, hammer loop and a drill bit pocket

90A



MA1

Milwaukee Compact Aerial Tool Apron
- 18 Pockets; Auger Holder



39Q

Estex Deluxe Blue Aerial Tool Apron

- Hard body crimp tool pocket, battery impact holster, magnetic socket pocket, hard body catch all, hard lined drill bit slot, rigid hammer loop, 8 hand tool pockets, short shotgun stick sleeve, tape thong, swivel hook 24" x 28"

39D



Estex Small Canvas Tool Apron
18"L x 4"W x 10 1/2"H

1828

39X



Klein Small Vinyl Tool Apron
- Takes up less space
18" Height; 19.5" Length



MA2

Milwaukee Bucket Hook- for 2" Lip


48-22-8292 (sold individually)



31O

Estex Injection Molded- 2" Lip

1H-1840 (price per pair)



31PP

Estex Rated Aerial BucketHook

- WLL 65 lbs.
- Fits 2"-2.5" Lip Buckets

(Price per pair)



31M

11" Tall

Safety Hook

For hanging tools inside/outside of bucket

(PER PAIR)



49H

MADI 3" Safety Bucket Hook

- Integrated safety gate

8" Tall- Sold Individually



MA3

Milwaukee Bucket Hook- for 3" Lip

48-22-8293 (sold individually)



31N

Estex Injection Molded Fits 3" Lip Bucket

1H-1842 (price per pair)



31QQ

Estex Rated Aerial Bucket Hook

- WLL 65 lbs.
- Fits 3"-3.5" Lip Buckets

(Price per pair)



BK1

Buckingham Buckeye Bucket Hook with Tether Hole

- Fits up to a 2 1/2" bucket lip
- 40 lb. WLL (3:1 safety factor), two inside accessory hooks with a 15 lb. WLL

(3:1 safety factor)

(Sold Individually)



55JD

24-15D

Jameson Double Pocket Tool Holder

- Ideal for bolt cutters and crimping tools
- Adjustable clamp bracket

Back Pocket: 6.25" x 2.25" x 17"

Front Pocket: 5.25" x 2.5" x 15"



39C

24-17

Jameson Tool Tray

- Features removable dividers and fixed bucket mounts

23" x 14" x 8"



92G

Estex 4 Compartment Tool Holder for Bucket

Front Compartments 14" Deep

Rear Compartments 17" Deep

Overall: 24"H; 15"W; 6"L

1P-2651-4



39K

Bucket Knuckles

- Bucket Knuckles are a tool holding and organization bracket designed to suspend and separate tools and rigging inside an aerial device
- 19.75 inches long x 3 inches tall x 2.5 inches wide - Hangs from two standard bucket hooks
- Bucket Knuckles are designed to hold up to 50 lbs.. The individual rigging points on the device are capable of supporting a maximum of 10 lbs. continuously



40A

40B

Estex Bucket Covers

This heavy duty vinyl coated nylon cover comes equipped with a lanyard and snap to keep the cover with the truck. It has a heavy bungee cord in the hem.

2711- Fits all one man and man and a half buckets

2712- Fits all two man buckets



Coffing LSB-B Ratchet Lever Hoist

- These stamped steel ratchet lever hoists are lightweight and durable
- 360 degree rotating handle
- Easy free chaining

3/4 Ton (1,500 lb)

Capacity Model

33F- 5' Lift

33FA- 10' Lift

1 1/2 Ton (3,000lb)

Capacity Model

33Y- 5' Lift

33YA- 10' Lift

Hook options for Little Mule Strap Hoists



**Standard
Hook**

on Farwest

Part#'s

33D

33E

33ED

**Hot Stick
Hook**

on Farwest

Part#

33EE

**Hot Stick Hook
and Gate Latch**

on Farwest

Part #'s

33DE

33EC

33EG



Little Mule Strap Hoist

- Lightweight and Rugged
- 250 Series: Capacity 1000 lbs. Single Line; 2000 lbs Double Line
- 250 Series: Lift 9 ft Single Line; 4 1/4 ft Double Line
- 300 Series: Capacity 1500 lbs. Single Line; 3000 lbs Double Line
- 300 Series: Lift 9 ft Single Line; 4 1/4 ft Double Line

Models:

33D- 250A (Standard Hook)

33DE- 250DHA
(Hot Stick Hook and Gate Latch)

33E- 300A (Standard Hook)
33EC- 300DHA
(Hot Stick Hook and Gate Latch)



Little Mule Strap Hoist

- Polyester Web Strap
- Insulated Fiberglass Handle
- Capacity: 2000lbs (single line); 4000lbs (double line)
- Lift: 11ft (single line); 5.5ft (double line)

Models:

33ED- 344C (Standard Hook)
33EE- 344DC (Hot Stick Hook)
33EG- 344DHC
(Hot Stick Hook and Gate Latch)



Coffing ATG Ratchet Lever Hoist

- Malleable iron roller chain ratchet lever hoists are efficient and durable
- 2 Strands of Load Chain
- 57" Standard Lift
- 3,000 lb Capacity
- 17 lb weight


33R



Klein Web-strap Hoist

- Large, non-conductive dial allows web slack to be adjusted with ease
 - 360 degree handle rotation
 - Tight ratcheting mechanism allows precise tensioning
- Single Line: Load Rating 1500lbs; Pulling Distance- Max: 138" / Min: 20"
- Double Line: Load Rating 3000lbs; Pulling Distance- Max: 79" / Min: 26"
- Weight: 12.5lbs

33U- KN1500PEX
(Standard Hook)



Klein Havens Grip

- For messenger and guy strand
- 5000 lbs. maximum safe load
- Min: .125" Max: .50"

34AA 1604-20 (without latch)


34B 1604-20L (with latch)



Klein Parallel Jaw Grip

- Pulls an exceptionally wide range of cable types and sizes
- Designed with a round inside-jaw contour for maximum contact
- 4500 lbs. maximum safe load
- Latch helps prevent the grip from falling in case of jaw disengagement
- Min: .157" Max: .875"

34BB 1685-20



Klein Parallel Jaw Grip

- Pulls an exceptionally wide range of cable types and sizes
- Designed with a round inside-jaw contour for maximum contact
- 7500 lbs. maximum safe load
- Latch helps prevent the grip from falling in case of jaw disengagement
- Min: .625" Max: 1.25"

34BC 1685-31




16477

Klein Parallel Jaw Grip


- Pulls bare copper, aluminum and ACSR
- 5,000 lbs. maximum safe load
- Min: .16" Max: .883"

K60 #16477



Klein Chicago Grip - 1656 Series

- Round, smooth inside jaw contour on this series of grips is ideal for bare ACSR
- 34MM** 1656-20 Min: .20" Max: .40"
- 4500lbs maximum safe load
- 34PP** 1656-30 Min: .31" Max: .53"
- 4500lbs maximum safe load
- 34QQ** 1656-40 Min: .53" Max: .74"
- 8,000 lbs maximum safe load




1613-30

Klein Bare Wire Chicago Grip

- Designed for working with solid and stranded bare wire from .08" to .20"
- 1500 lbs. maximum safe load
- single "V" groove jaw

34N 1613-30



1613-35

Klein Chicago Grip for Small Copper

- 4500 lbs. maximum safe load
- Pulls #6 and #8 copper wire without damaging or deforming the cable

34G 1613-35



Klein Parallel Jaw Grips

- For wide range of cables; spring loaded
- 34CF** KT4500 Min: .18" Max: .60"
- 5000lbs maximum safe load
- 34CJ** KT4600 Min: .30" Max: .80" 10,000 lbs maximum safe load
- 34CK** KT4800 Min: .70" Max: 1.25"
- 12,000lbs maximum safe load




1716-70

Klein Parallel Jaw Grip, HDPE Tree Wire

- Spring-loaded for one-handed operation and easy placement
- Tough carbide grit technology
- 4,000 lbs. maximum safe load
- Min: .625" Max: 1.362"


34TS 1716-70



1613-40

Klein Chicago Grip

- For messenger and guy strand
- Double V grooves provide four-point contact
- 4500 lbs. maximum safe load
- Min: .12" Max: .37"
- 34NA** 1613-40




1684-5F

Klein Chicago Grip with File Insert

- For messenger and guy strand
- Single V with file insert
- 8000 lbs. maximum safe load
- Min: .16" Max: .550"

34NC 1684-5F



16845C

Klein Chicago Grip - Coated Guy Wire

- Sawtooth jaw profile provides extra gripping power to prevent slipping on guy strand
- 8000 lbs. maximum safe load
- Min: .16" Max: .55"
- 34ND** 16845C



KT45005C

Klein Parallel Jaw Grip for Guy Strand, EHS and Coated Cable

- Spring helps maintain cable position
- Sawtooth jaw profile ensures optimal grip strength
- 5000 lbs. maximum safe load
- Min: .18" Max: .60"
- K70** KT45005C

LITTLE MULE GRIPS / LINK STICKS / ETC.



Little Mule Bulldog-Type Jaw Grip

34E LMG1000 Min: .04"(18AWG); Max: .394 (1/0AWG); Capacity 1000lbs

34EA LMG2000 Min: .109"(8AWG); Max: .594 (4/0AWG); Capacity 2000lbs



Little Mule Parallel Jaw Grip

- Standard grip; Spring Loaded

34EB LMG4500 Min: .18" Max: .60"
5000lbs maximum safe load

34EC LMG4600 Min: .30" Max: .80"
10,000 lbs maximum safe load

34ED LMG4800 Min: .70" Max: 1.25"
12,000lbs maximum safe load



Little Mule Hot Line Parallel Jaw Grip

- Spring Loaded; Notched Handle

34F LMG4501 Min: .18" Max: .60"
5000lbs maximum safe load

34FA LMG4601 Min: .30" Max: .80"
10,000 lbs maximum safe load

34FB LMG4801 Min: .70" Max: 1.25"
12,000lbs maximum safe load



Little Mule Parallel Jaw Grip

with Aggressive Teeth

- Spring Loaded

34AG LMG4500A Min: .18" Max: .60"
5000lbs maximum safe load



Hastings Isolated Link

- Standard swivel eye on one end and safety hook

- Load Limit 4000lbs
- Overall Length 24";
Fiberglass Length 12"

34JG



Hastings Isolated Link

- Standard swivel eye on one end and hot stick operated safety latch

- Load Limit 4000lbs
- Overall Length 24";
Fiberglass Length 12"

34JH



Hastings Spiral Link Stick

- Standard swivel eye on one end spiral hook

- Load Limit 2000lbs
- Max wire size 795ACSR
- Overall Length 24";
Fiberglass Length 12"


34JK



33GR

Anchor Rod Pulling Eye

- Adjusts from 1/2" to 1"
- Working Load Limit of 6,000 lbs.



38R

Klein Howe Wire Tool

One Man operation. Holds load at any distance, great for

re-sagging large service drops. SWL 500lbs
1702-20N



38L

Klein Howe Wire Tool with Handle

- Durable plastic handle ideal for pulling
- Snap hook for easy attachment of small grip


SWL 500lbs
1702-20HH

Klein Slack Blocks

You know the story...the boss says you can handle it by yourself. These light weight blocks will get you out of many jams. They have aluminum alloy sheaves and bronze bushings with snubbing hooks, designed for a one man operation. Max pull 750 lbs.



Klein Slack Block Parts



Klein 470 Snap
M.S.L. 750 lb




Klein Snap Hook
M.S.L. 1500 lb



Eagle Line Tools
Snap
750 lb Safe Load



S.S. Swivel
Eye Snap



Carbine Snap
Hook
7/16" Opening



Carbine Snap
Hook
3/8" Opening



Kong Wire Bent Paddle
Carabiner- 22kN Strength
1.25" Opening; 4.5" Length



Twist Lock Aluminum Carabiner
Min Breaking Strength: 5171 lbs
Gate Strength: 3600 lbs
Opening: .748"



Triple-Action Aluminum Carabiner
Min Breaking Strength: 27kN (6,069 lbs)
Gate Strength: 16kN (3600 lbs)
Opening: .708"



Twist Lock Steel Carabiner
Min Breaking Strength: 10,116 lbs
Gate Strength: 3600 lbs
Opening: 1.06"



**Petzl ROLLCLIP Z
TRIACT-LOCK**
- Min. rope diameter: 7 mm
- Max. rope diameter: 13 mm
- Max. working load: 2 x 2 = 4 kN
- Major axis strength: 20 kN
- Minor axis strength: 8 kN
- Open gate strength: 7 kN
- Approximately 4 1/2"



Buckingham Big BuckSnap
- Allows the user to easily connect over 4" angle iron. Rounded inner edge designed to prevent damage to conductors when used in hot work applications
- 3600lb. rated gate




Rock Exotica SwivaEye Carabiner
Weight: 5.5oz
Breaking Strength: Major Axis: 30 kN;
Minor Axis: 7 kN Open Gate: 12 kN;
Gate Opening: .84"



**Fixed Eye Double Action Steel
Snaphook**
- Minimum Break Strength 10,116 lbs.
- Gate Strength 3600 lbs
- Gate Opens .86"



**Double Action Forged Steel Swivel
Snaphook**
- Minimum Break Strength 11,240 lbs.
- Gate Strength 3600 lbs
- Gate Opens .86"




Eye to Hook

MBS= 6,000 lb; WLL= 1,500 lb

Eye to Sheave

MBS= 10,000 lb; WLL= 2,500 lbs



The Buckingham OX BLOCK™ is a rope snatch block with an integrated friction bar used for hurt man rescue, lowering loads, snubbing loads, and raising loads. It allows the rigging professional to handle loads with greater control. When lowering loads, tension is transferred from the worker to the OX BLOCK™. The OX BLOCK™ replaces standard handline blocks, parted blocks, and various snatch blocks. The OX BLOCK™ also has greater Working Load Limits than blocks of similar size.



OX BLOCK



OX BLOCK
with Clevis Top



OX BLOCK
with Clevis Top
and Hook



OX BLOCK Clevis Top
with OX HORN




94LA

OX BLOCK
with an
attached
4' x 5/8" ad-
justable sling
and a steel
carabiner



94LB

OX BLOCK
Clevis Top
and Hook
with an
attached
4' x 5/8" adjustable
sling



94SL

Sling for OX BLOCK

- 4' x 5/8" adjustable sling
- WLL: Straight 3200lbs;

Choker 2560 lbs; Basket 6400 lbs



OX BLOCK Handline Assembly

- With an attached 4' x 5/8" adjustable sling, a steel carabiner and 1/2" handline assembly

*Handline hook MBS 500lbs. and handline snap MBS 750lbs. Not To Be Used For Human Support.

94LC 80' Handline Assembly

94LD 100' Handline Assembly



OX BLOCK Clevis Top Handline Assembly

- With an attached 4' x 5/8" adjustable sling and 1/2" handline assembly

*Handline hook MBS 500lbs. and handline snap MBS 750lbs. Not To Be Used For Human Support.

94LE 80' Handline Assembly

94LF 100' Handline Assembly



OX HOOK Handline Assembly
OX HOOK on one end, and a
model 1706 steel locking snap
hook spliced on the other for
added versatility

82Q 80'


82S 100'



37R

Buckingham Steel
Double Action
Rigging Carabiner

- MBS: 11,240 lbs
- WLL: 2,500 lbf.
- 3,600 lbs gate strength



Rock Exotica Material
Handling 2.6" Om-
ni-Block Pulley MHP55

- Brings heavy duty rigging with a working load limit of 4,500lbf.
- 3/8" - 1/2" rope capacity
- Push-button access to open the sideplate

#MHP



Buck Side Swivel

- Heavy Duty aluminum sheave pulley that has 5/8" diameter rope capacity and 2500 lb working load limit
- The "Side Swivel" plate allows rope to be installed/removed with disconnecting it from the anchor point

#BS1 Single Sheave

#BS2 Double Sheave



Rock Exotica Omni-Block 1.5

- Aluminum pulley with swivel
- Opens to allow installing/removing the rope while the pulley is still anchored
- 1798 lb working load limit

- 1/2" rope capacity

#RE1 Single Pulley

#RE2 Double Pulley

HANDLINE KITS / BLOCKS / ACCESSORIES



**Eagle Line Tools
Handline Kit**

- Comes with rope, snap, block, and hook

82L 80' Braided Rope

82M 100' Braided Rope



Klein 470 Snap
M.S.L. 750 lb



Chance Handline Hook
500 lb Maximum Load



**Bashlin Handline
Hook 35H**



Buckingham Ox hook
- WLL of 2,500lbf (gate closed),
1,000lbf (gate open)
- 3,600lb. rated locking gate can
be locked in the open position



82H
**Eagle Line Tools
Nylon Hand
Block**
1,000lb. Safe Load
With Hook



82R
**Tallman AHB-3
Handline Block**
- 3" sheave
accommodates rope
up to 5/8" diameter
- 1,000 lb. safe
working load



CH7



CH8

Chance Block
- Made of high dielectric, fiberfilled
natural nylon
- Maximum 1/2" rope
- Max Load 3,500 lbs
CH7 Double Block Model
CH8 Triple Block Model



RE3
**Reliable Nylon/
Fiberglass Di-Electric
Handline Block with
Meat Hook**
- Capacity of 5/8" rope
- 1,000 lbs Safe
Working Load



82T
**Tallman AHB-4
Tower Block**
- 4" Sheave
- 7/8" Rope
Capacity
- 2,500 lbs. Safe
Working Load
- 6.3 lbs.



SL6

**Slingco 3" Nylon
Fiberglass Block**
- 5/8" maximum
rope size
- 1,000 lb safe
working load limit



**Chance Snatch Block
with Meat Hook**
- 5/8" maximum rope
size
- 1,250 lb maximum
load capacity

CH10



MU Type- Multi Weave Cable Grip

- Triple weave construction is ideal for heavy loads; the cable grips are color coded for ease of identification; primarily for pulling aluminum conductor

Part#	Color	Size Range/Lattice Length	Approx. Break Strength(lbs)
ZCS1710	Dark Green	.25-.50" Range/ 31" Lattice	7,000
ZCS1711	Brown	.50-.75" Range/ 45" Lattice	10,500
ZCS1712	Light Blue	.75-1.00" Range/43" Lattice	14,000
ZCS1713	Gold	1.00-1.25" Range/65" Lattice	25,000
ZCS1714	Black	1.25-1.50" Range/59" Lattice	31,000
ZCS1715	Red	1.50-1.75" Range/82" Lattice	31,000



A Type- High Strength Cable Grip

- Can be used for aluminum conductor or for pulling rope; Slingco Feed Tube is recommended when inserting rope into A Type cable grips

Part#	Color	Size Range/Lattice Length	Approx. Break Strength(lbs)
ZCS1800	Dark Green	40-.63 Cond./ .5-.9 Rope/ 41" Lattice	14,000
ZCS1801	Red	.63-.88 Cond./ .75-1.10 Rope/ 58" Lattice	20,000



Slingco Feed Tube

FTU1891- for use with ZCS1800
#FTU1892- for use with ZCS1801



Line Pulling Swivel- Stainless Steel




- Designed to the highest specifications for underground and overhead pulling applications.

Part#	Safe Working Load (lb.)		Recommended* for Cable Grip Color Code
	Underground	Overhead	
ZSW2091	2,250	1,350	
ZSW2092	3,500	2,100	Dark Green
ZSW2093	5,000	3,000	Brown and Light Blue
ZSW2094	7,000	4,200	
ZSW2096	10,000	6,000	Gold, Black, Red


* Color code recommendation is a rough guide. Working load should be determined by the competent person(s) using the cable grip and/or Slingco swivel

- 3:1 factor of safety used, based on the ultimate load for underground use
- 5:1 factor of safety used, based on the ultimate load for overhead use

SLINGS



These rugged orange nylon slings are made for the utility industry and made to the current ANSI standards.



Auger Sling

- Strong, lightweight sling features reinforced eyes.
- 1" x 10' nylon web.

Endless Slings					
		Width	Vertical	Basket	Choker
35A-	950-100	1"	3200	6400	2560
35AA-	950-100D1"	DT	6200	12400	4960
35C-	950-175	1 3/4"	4000	8000	3200
35CC-	950-175D1 3/4"	DT	8800	17600	7040
Double Eye Standard					
		Width	Vertical	Basket	Choker
35D-	951-100	1"	3200	6400	2560
35DD-	951-175	1 3/4"	5400	10800	4320
35DA-	951-200	2"	6400	12800	5120
35DB-	951-300-4	3"	7800	15600	6240
Double Eye Single Ply					
		Width	Vertical	Basket	Choker
35E-	952-100	1"	1600	3200	1280
35EE-	952-175	1 3/4"	2800	5600	2240
35EA-	952-200	2"	3200	6400	2560
35EB-	952-300-4	3"	4200	8400	3360
Return Eye					
		Width	Vertical	Basket	Choker
35F-	953-200	2"	5600	11200	4480
35FF-	953-350	3 1/2"	7600	15200	6080
Pole Slings					
		Width	Vertical	Basket	Choker
35H-	2011-36	1 3/4"	1000	2000	1000
35HH-	2011-48	1 3/4"	1000	2000	1000
35G-	2012-36	1 3/4"	3300	6600	2640
35GG-	2012-48	1 3/4"	3300	6600	2640




Bashlin 1/2" Adjustable Rope Sling

- Works well on transformers or as an anchor for a handline
 - Adjusts from 28" - 48"
- Safe Working Load: Vertical: 1,500lbs;
Choker: 1,200lbs; Basket: 2,990lbs



Buckingham BuckLink SLING - 3903S-6

- This product is the ultimate daisy chain style anchor sling and has endless uses
- MBS. Ratings when new:
Straight: 5,000 lbf.
Choked: 5,000 lbf.
Basket: 10,000 lbf.



Eagle Cable Reel Handler

- Provides the ability to flip, lift and payout reels of wire

2,000 LB Capacity


38X

4,000 LB Capacity

38Z



This lightweight, aluminum grounding saddle is made for grounding conductors up to and including 336 MCM. It has graphite bushings, a spring loaded tension arm, and offset sheaves for solid contact.



This is a heavy duty traveling ground for conductors sized up to and including 1590 MCM. The spring loaded center sheave maintains tension. The solid 1/2" aluminum rod is provided for attachment to the ground clamp.

Husky - 12 Strand Adjustable Transformer Slings

- Slings have a ballistic nylon outer jacket at the three critical wear points for extended life. Premium Husky Coating is applied to provide excellent resistance to chemicals, sunlight and abrasion. Color coded for easy differentiation.

3/8" Diameter- Basket Rating 2,112 lbs	35U	24"- 50"	35W	24"-72"
1/2" Diameter- Basket Rating 3,200 lbs	35X	24"- 50"	35XA	24"-72"
5/8" Diameter- Basket Rating 6,120 lbs	35Y	24"- 50"	35YA	24"-72"
3/4" Diameter- Basket Rating 8,000 lbs	35Z	24"- 50"	35ZA	24"-72"

3-Strand Twisted Composite - Poly Dacron

- High strength polyester on the outside of each strand and lightweight white polypropylene on the inside of each strand on. Red Tracer. Easy to the hand and splices well. Holds a good knot.

	36D	36DA
3/8" Diameter- Avg. Break Strength 2,700 lbs	150'	600'
1/2" Diameter- Avg. Break Strength 4,500 lbs	150'	600'
5/8" Diameter- Avg. Break Strength 6,500 lbs	150'	600'

"Handline Pro" 12-Strand Braided Polyester over Polyolefin

- Polyolefin keeps the center dry for minimal electrical conductivity. Light weight and very durable. Easy to the hand, soft cover. Easy to splice.

	36HP	36HA
3/8" Diameter- Avg. Break Strength 5,400 lbs	150'	600'
1/2" Diameter- Avg. Break Strength 9,300 lbs	150'	600'
5/8" Diameter- Avg. Break Strength 14,000 lbs	150'	600'

Safetylite 16-Strand Braided Polyester Arborist Climbing Line- 1/2"

- Neon Colors for visibility
- Firm polyester braid provides great resistance to abrasion and keeps round shape
- 7,500 lbs average tensile strength

36X 1/2" x 150'

36XA 1/2" x 600'

36Y

"Target Line" 100% Slick Throw Line
- braided firmly to avoid snagging and abrasion; avg. break 250lbs
1/8" x 1000'

"Husky Bull Rope" Double Braided Composite Bull Rope

- Provides the best in abrasion resistance, break strength and energy absorption. Has a polyester jacket and a nylon core. Premium Husky coating is applied to provide excellent resistance to abrasion.

	36Z	36ZA
1/2" Diameter- Avg. Break Strength 9,500 lbs	150'	600'
9/16" Diameter- Avg. Break Strength 14,000 lbs	150'	600'
5/8" Diameter- Avg. Break Strength 18,000 lbs	150'	600'



CH15



CH21



C26



C32



C28

Chance
C4032213
Pruning Saw
with Universal
Fitting
- 16.1" overall
length



CH19

Chance C4033284
Fuse Grappler Tool
with Universal Fitting



CH12

Pricing/Description for Chance Sticks

#CH13 Chance Grip-All, 4' Shotgun (4'9" Overall Length)	C4030291
#CH14 Chance Grip-All, 6' Shotgun (6'8" Overall Length)	C4030292
#CH15 Chance Grip-All, 8' Shotgun (8'7" Overall Length)	C4030293
#CH21 Chance Grip-All, Telescoping; 5' 6 3/4", 6' 9 1/2", 8'; Retracted Length 5' 2 3/4"	C4031035
#C27 Chance 6' Universal Hotstick Pole	H17601
#C26 Chance 8' Universal Hotstick Pole	H1760
#C32 Chance 6' 5" Wire-Holding Stick	C4033068

Chance Wire Puller Hook- WPH3

- For use in cutting deadends and pulling slack on automatic deadends
- Holds the insulator and deadend assembly directly in line with the conductor
- Can be applied by hand or with hot stick
- Maximum rated load of 3500 lbs



CH33

Chance M44559
Disconnect



CH20

Chance M1867
Grip-All to Universal
Adapter




41A

Chance C4031416
Tie Wire Claw with
Universal Fitting




41B

Chance C4031417
Utility Head with Uni-
versal Fitting



Chance 48" Strap Type Temporary Conductor Support - T4001939

- With two conductor supports
- Working load: 150 lb. per wireholder
- 2" wide strap is 44" in length to fit most structures
- Wireholder accepts up to 1" diameter conductor



Hastings Compact Cluster Bar - 6767

- 36" of chain
- 5/8" bar accepts both "C" and duckbill type ground clamps



Reliable Pole Mounted Support Bar

- 72" of chain
- Accepts "C" type and duckbill grounding sets
- Copper support bar is 11" wide by 4 1/4" deep
- Tested to ASTM F855 Grade 5H



Rauckman 5' Plastic Insulating Cover-Up

- Hotstick handle for grip-all (shotgun) stick
- Class 4; 36.6kV max use rating covered phase to covered phase
- Maximum conductor size 666 kcmil ACSR
- Meets ASTM F 712 requirements



Chance Electric Drive Capstan Hoist - C3081370

- 3,000 lb Load Rating
- Includes foot control switch



Chance LoadLooker Ammeter - Up to 69kV

- Model #MEAMP11RW
 - Up to 69kV max voltage
 - Up to 2,000 amps max current
 - True RMS reading
 - 3.86" jaw size
 - 60 Hertz unit
- Typical Applications Include:
- Identifying load imbalances
 - Verifying accuracy of current transformers
 - Determining load to select properly sized jumpers
 - Measuring load before opening switches



Chance All-Purpose Bracket for 3,000-lb Capstan - C3081443

- Wheel handles on chain binders make tightening easy

SLINGCO DRIVE WRENCHES

Slingco 10K Drive Wrench Assembly For Efficient Installation of Screw Anchors



Drive Wrenches

- Designed to allow anchor rods to telescope inside them
- Rated to 10,000 ft-lb of torque
- Weight: 57 lbs

#SAE09639 (Orange) 2.25" Hub Size;
1.375" Shaft Size

#SAE08666 (Yellow) 2.5" Hub Size;
1.5" Shaft Size



Drive Wrench Lock Assembly

- The three position rings allow for easy capture of the drive wrench and the anchor rod, holding them securely while under torque and releasing each when needed

#SAE10425



Hex Kelly Bar Adapters

- Used to connect the drive wrench lock assembly to the Kelly Bar of the bucket truck. Two versions available which fit the most common drive bar dimensions

#SAE10486 2.5"

#SAE10427 2.625"



Dica Outrigger Pads

"The Lightweight Heavy Duty Outrigger Pad"

- Incredible recovery memory

#92J - 18" x 18" x 1" Weight 10lbs.

#92K - 24" x 24" x 1" Weight 18lbs.



Pulling Hooks For Deadends & Strandwise (Guy Deadends)

- Pulling hooks aid in the installation of all automatic compression deadends. The high tensile, heat treated steel alloy pulling hook is used in place of a rope sling to hold the deadend in line with the conductor, simplifying the installation and saving valuable time.

REL9055 10" Length WLL: 6,500lbs

REL9062 15" Length WLL: 5,000 lbs



SL7

Slingco Pole Stand

- Lightweight and compact
- Quick swing-and-lock legs
- Positions poles for safe and comfortable framing
- 6,000 lb capacity
- Weighs 32 lbs



CH9

Chance Double and Triple Blocks with 150' Rope- T4001258

- Blocks are made of high dielectric, fiberfilled natural nylon
- Comes with 150' of 1/2" composite fiber braided rope



33L

Dixie Certified Lifting Tongs

#40228

- 1" Material Diameter
- 25" Maximum Opening
- WLL at Degree of Opening:
- 1,500 lb limit at 180 degrees
- 2,000 lb limit at 135 degrees
- 2,500 lb limit at 75 degrees



TSG

DDIN Temporary Ground Rod

- A temporary 6' copper clad ground rod with T-Handle

HOT TOOL ACCESSORIES



2C

Litfinger

The First Hot Stick Finger Light

- Built in LED Light
- Fits all major hot sticks with universal slotted connector



53G

Deviner - Universal Vine/Vegetation Removal Solution

- A quick affordable way to safely remove vegetation away from power lines
- Made of Glass Filled Nylon for 100% non-conductive material



41D

P10431

Hastings Universal Disconnect Hook

- For opening and closing switches
- \$13.90



98S

Hastings Fuse-Cup

- Makes changing out fuses easier than ever
- Allows one fuse holder for 100 AMP and 200 AMP fuse barrels from any manufacturer



Salisbury PG Tool Sockets

78K

9/16"

78L

3/4"

78M

15/16"



41A

Chance C4031416 Tie Wire Claw with Universal Fitting



41B

Chance C4031417 Utility Head with Universal Fitting



41T

10-180

Hastings 2 Brush Cleaner



92M

10-178

Hastings Conductor Cleaning Brush

- Guard to protect hands and gloves
- Molded in eye for use with shotgun sticks

#92MM- 10 Pack Repl. Brushes



41R

Hastings Hot Stick Hanger

- Hook and stainless steel clamp
- Attaches to 1 1/4" and 1 1/2" diameter sticks



41Q

Convertible Adapter

- Change from quick change to universal
- Thread size: 5/8"-11



41P

A10021

Hastings Universal Rotary Blade Tie Stick Head

- Blade has self aligning swivel action for removal of ties without looped ends



41S

10-096

Hastings Armor Rod Applicator

- Facilitates application and removal of factory formed conductor ties and armor rods



41W

5455-46

Hastings Universal Socket Wrench

- 1/2" Square drive; used with standard wrench sockets



41Z

DDIN Shotgun Adapter



41Y

A10042


Hastings Universal Pigtail Disconnect



41N

P10046

Hastings Universal S Hook



41V

P10459


Hastings Extra Long 4.75" Universal Disconnect Hook



41X

Hastings Wing Bolt With Washer

HOT TOOLS / MEASURING STICKS / ACCESSORIES



Pricing/Description for Hastings Sticks

#92R	35 ft Standard Tel-O-Pole Hot Stick #S235; Extended Length 17'-21.5'-26'-30'-35'; Retracted Length 63 3/8";
#92U	40 ft Standard Tel-O-Pole Hot Stick #S240; Extended Length 22'-26'-30'-35'-40'; Retracted Length 65 3/8"
#92XA	16 ft Tel-O-Pole II Hot Stick #HV216 Triangle Shape w/ Auto Lock; "No Twist"; Extended Length 16' 9"; Retracted Length 60"
#92X	35 ft Tel-O-Pole II Hot Stick #HV235 Triangle Shape w/ Auto Lock; "No Twist"; Extended Length 35'; Retracted Length 68"
#92Y	40 ft Tel-O-Pole II Hot Stick #HV240 Triangle Shape w/ Auto Lock; "No Twist"; Extended Length 39' 6"; Retracted Length 69"
#92Z	35 ft Measuring Stick Feet and Inches #E35 Extended Length 35'; Retracted Length 65 3/4"
#92ZZ	35ft Telescopic Hot Stick/ Measuring Stick #EV35 Extended Length 35'; Retracted Length 68"
#93A	40 ft Measuring Stick Feet and Inches #E40 Extended Length 40'; Retracted Length 65 3/4"
#93AA	39' 6" Telescopic Hot Stick/ Measuring Stick #EV40 Extended Length 39' 6"; Retracted Length 69"
#93V	50 ft Measuring Stick Feet and Inches #E50 Extended Length 50'; Retracted Length 69 3/16"
#93C	8'6" Fixed Length Shotgun w/ External Rod ⁸¹⁰⁸
#93F	6'6" Fixed Length Shotgun w/ External Rod ⁸¹⁰⁶
#93L	Telescopic Shotgun Stick; Retracted Length 5'1"; Operating Lengths 5'1", 6'6", 8' ⁸¹⁵⁸
#55A	8' Universal-One End Only Hot Stick w/ Hanger Hook ⁵⁶⁷⁻⁸
#55G	6' Universal-One End Only Hot Stick w/ Hanger Hook ⁵⁶⁷⁻⁶
#55C	26 1/2" Retracted and 8' Extended Tel-O-Pole Retractable Bucket Stick ^{HV-208}
#55CC	37" Retracted and 12' Extended Tel-O-Pole Retractable Bucket Stick ^{HV-312}
#55F	Bucket Canister for Hastings HV-208 Bucket Stick ⁰⁶⁻¹⁸⁵
#55FF	Bucket Canister for Hastings HV-312 Bucket Stick ⁰⁶⁻¹⁸⁶
#93G	Vinyl Case for Hastings HV-208 Bucket Stick ^{C-208}



Estex 7.5" Wide Vinyl Hot Stick Bag
#93H - 7.5" x 72" #93J - 7.5"x 84"
#93K - 7.5" x 96" #93M - 7.5"x 108"

98Q



Hastings Hot Stick Wipes 50 Pack

- Excellent for daily wiping
- Removes contaminants and leaves silicone moisture barrier



Hastings 18" x 18" Silicone Treated Wiping Cloth

- Deposits water repellent film while removing dust and dirt particles

98R

Place your order at
WWW.FWLSP.COM or call (800) 466-7153

GLOVES



Youngstown Arc Rated Ground Glove

- High quality goat grain leather; Double Layering at palm, saddle, knuckles and fingertips; Arc Rated 23 cal/cm2
- sz. M-2XL



- ## Youngstown FR Ground Glove Lined w/ Kevlar
- High quality goat grain leather; Double Layering at palm, saddle, knuckles and fingertips; Arc Rated 37 cal/cm2
- sz. M-2XL



- ## Youngstown Arc Rated FR Mechanics Hybrid- 12 Cal
- Form-fit design for superior comfort, dexterity and grip. Palm features a liner made of Kevlar® fiber for cut resistance. Top of hand is made with Nomex Fiber®.
- sz. M-2XL



- ## Youngstown Arc Rated Leather Utility Plus Wide-Cuff
- High quality goat grain leather; Double Layering at palm, saddle, knuckles and fingertips; Arc Rated 25 cal/cm2
- sz. M-2XL



- ## Youngstown Arc Rated Leather Utility Plus
- High quality goat grain leather
 - 4" Safety Cuff; Arc Rated 20 cal/cm2
- sz. M-2XL



- ## Youngstown Arc Rated Leather Utility Lined with Kevlar- Wide Cuff
- High quality goatskin leather and lined entirely throughout by Kevlar®
 - 4" Safety Cuff; Arc Rated 27 cal/cm2
- sz. M-2XL



- ## Kunz 2" Cuff Gloves
- Kunz #552



- ## Seattle Elkskin Driver Glove
- Super Soft Elkskin Leather
 - Unlined
- sz. S-XL



- ## Majestic Lineman Gloves Double Leather Palm
- 1516E

MG2



Milwaukee High-Visibility Cut Level 4 Polyurethane Dipped Gloves

- These hi-vis cut resistant gloves have a reinforced nitrile coating between the thumb and index finger for enhanced durability in high wear points
- SMARTSWIPE Touchscreen Compatible Fingertips
- ANSI Cut Level 4
- Available in sizes M, L or XL

SQ9



Squids Grabber

- Dielectric / Non-conductive material
- Breakaway feature

SQ10



Squids Grabber with Belt Clip

- Dielectric / Non-conductive material
- Breakaway feature

RUBBER GLOVE PROTECTORS

45S



Youngstown Arc Rated 10" Leather Protector

- Ergonomically designed to fit perfectly over Class 0 and Class 00 rubber gloves
- Features FR Strap System
- Arc Rated: 25 cal/cm2

45X



Youngstown Arc Rated 10" Leather Protector Lined with Kevlar

- Kevlar® throughout entire glove and cuff to provide enhanced cut resistance, puncture resistance and flame resistance
- Arc Rated: 36 cal/cm2

45T



Youngstown Arc Rated 14" Leather Protector

- Features FR Strap System
- Arc Rated: 32 cal/cm2

45M



Edwards 10" Low Voltage Glove Protector

45R



Chance 14" Leather Protectors

Kunz Rubber Glove Protectors

45K- 12"

1050-3

45KM- 14"

1050-5

45KK- 16"

1050-7



GLOVE & SLEEVE ACCESSORIES



2449-TU-C

94B

Estex Extra Large Glove and Sleeve Bag

Sleeve Portion:

4" W x 29" H

Glove Portion:

8" L x 4" W x 17" H



2449CEV

29L

Extra Long Sleeve Bag

12" L at top/ 8" L at bottom x

4" W x 29 1/2" H



Estex Glove and Sleeve Bags

290- 2420 14" H

29N- 2423 16" H

29M- 2426 18" H



Bashlin Glove Bag

10L- 24M- 10.5" Glove Bag

10M- 24-14" Glove Bag

10Q- 24L- 16" Glove Bag

10R- 24XL- 18" Glove Bag



45Q

Sleeve Straps without Buttons (Pair)



45J

2-Piece Sleeve Buttons (Pack of 4)

- Threaded 2 piece buttons for rubber sleeve straps



45Y

Quickeze FR-Rated Sleeve Straps (Pair)

- FR Rated; Easily Adjustable; Unique oval buttons designed for quick and easy attachment to sleeves
- Single Piece; no extra buttons needed



10H

Bashlin Glove and Sleeve Bag

Back Portion: 32" Height

Glove Portion: 17" Height



The F.A.I.T

- Field Air Inspection Tool for daily visual air inspection of rubber gloves



46W



44C

GluvEze Talc

- Squeeze or spray liberally on hands or inside your gloves. Helps absorb perspiration.

#44C- 5 oz. Squeeze bottle

#44D- 5 lb Container

46G



MFRWB-1

Madi Mini FlatRound Wire Brush- Ideal for Distribution
- Up to 1000 MCM

46F



FRWB-1

Madi FlatRound Wire Brush
- Up to 1590 MCM




Standard "U" Brush

46C

8 Sol. 500MCM

46H

8 Sol. 954 ACSR



1520010GAH

46D

Brush with Handle and Cover



RK1

Grease Pot with Two Brushes



Rauckman Hold Tag Tagging Device with Clips for Hold Card

RK2



46B

Salisbury Salcor Connector End Line Hose
OR125-6C Class 2 1.25" x 6'



46Y

Rauckman Clamp Pin

- Ends are shaped to engage the end ferrule of a grip-all clampstick
- Integrated button for securing or attaching an insulated blanket

46YH

Rauckman Clamp Pin with Hotstick Eye

- Ends are shaped to engage the end ferrule of a grip-all clampstick
- Integrated button for securing or attaching an insulated blanket



Salisbury Rubber Blankets

46O



900E

Class 4 Eyelet Style Rubber Blanket- 36" x 36"

CH1



Chance Lubricant

- For line hose
- 10oz.



SL1

Slingco Blanket Pin

- Handles of the pin are shaped for clampstick (shotgun stick)



SL2

Slingco Blanket Pin with Hot Stick Clip

- Handles of the pin are shaped for clampstick (shotgun stick)

46N



1300

Slotted Style Rubber Blanket
36" x 36" Class 4 w/ 28 Eyelets

46R



300E

Class 2 Eyelet Style Rubber Blanket - 36" x 36"

45Z



Blanket Canister with Handle
10" Diameter x 37" Height

DIGGING TOOLS / POLE HANDLING TOOLS



Cant Hook



Peavey

83A	Straight Shovel	10ft (TE-019-120-0813)	83AA- 12ft (TE-019-144-0814)
83R	Western Spoon	10ft (TE-019-120-W803)	83RR- 12ft (TE-019-144-W804)
83C	Shoe Tamping Bar	10ft (TE-015-120-0823)	83CC- 12ft (TE-015-144-0824)
83KK	Hole Digger (SPLIT HANDLE)	10ft (TE-015-120-0CED)	
83P	Cant Hook (9" Hook)	4 1/2ft (T-029-054-0175)	83PP- Replacement Handle (W-029-054-0328)
83TR	Cant Hook (12" Hook)	66" (T-029-066-L177)	
83Q	Peavey	4 1/2ft (T-029-054-0123)	83QQ- Replacement Handle (W-029-054-0298)

*** Please call for shipping costs for digging tools 10ft and over.
Freight shipping charges apply



48S- Orange 16oz. throwing bag
48V- Throw line storage bag only
(see 48R)
48T- Green plastic dipped 16oz.
throwing bag
48Z- Buckshot Premium 16 oz.
throwbag



Buckingham 1379

TREE SADDLE: ORDER BY WAIST SIZE	
S	30-34
M	34-40
L	42-48
XL	46-54



Big 8 Stainless Steel Descender
Rated @
11,250lbs
2 7/8" Diameter opening



Buckingham 50" Chainsaw Lanyard with Bronze Snap Attachment
- tear away safety pack that activates when 200 lbs. of force is applied



U.S. Rigging Wire Core Flip Line
- Swivel eye snap hook; Permanent rope grab; Meets ANZI Z133-2012

54X 10' 54Y 16'



Big 8 Aluminum Descender
Rated @
9,000lbs
2 3/4" Diameter opening



6015C



15"
6515C



6222C

21"

47T

TREE CLIMBERS

Order Top straps and Pads separately on pages 26-28



Buckingham Steel Tree Climbers
SB95089

50C



Bashlin Steel Tree Climbers
BD16BTIN

50E



Corona 21" Razor Tooth Saw

47A



47C

Corona 13" Razor Tooth Saw

SAFETY PRODUCTS / ARBORIST



Wire Raiser
- Designed for placing cable on rollers, construction blocks and hardware



Universal Tool Adapter
- Adapts any manufacturer's universal head tools to pole



Universal Saw Blade Adapter
- Adapts (51G) saw blade to any universal hot stick or (51M) adapter



Pole Saw Casting
- Adapter for Saw Blade so it can be used with pole



16" Tri-Cut Saw Blade
- Attaches to stick using universal saw blade adapter (51R) and universal tool adapter (51M) or (51R) only if you already have universal stick



16" Teflon-coated Saw Blade
- Attaches to stick using casting adapter (51H) or by using universal saw blade adapter (51R) and universal tool adapter (51M)



TWISTARP™

- Helps reduce injuries
- Keeps the work site clean
- Transport fill without a hassle
- Ergonomically correct tool that solves difficult situations
- 1/2 yard of dirt or gravel for poles and urd work

Sizes to Choose From:

88P 8' x 8' (5,000# lift capacity)

88Q 10' x 10' (5,000# lift capacity)



Jameson 1.75" Cut Big Mouth Pruner
- Double pulley
- Rope and Adapter Included

51A



Base Pole

- Hollow fiberglass stick with female ferrule on top and rubber end cap on bottom
- 51A- 6 foot
- 51AA- 8 foot

51B



Extension Pole

- Hollow fiberglass stick with female ferrule on top and male ferrule on bottom
- 51B- 6 foot
- 51BB- 8 foot



88Z

Estex Rated Material Handling Bag

- 26" L x 26" W x 24" H
- Designed to hold 3300 lbs
- Stevedore strap handles for center pick-up
- 10" discharge bottom chute with protection flap





Slingco Dirt Tarps

- Used at pole change-outs, transformer terminations, pedestals as well as underground gas, telephone and other underground utility applications
- Gives user the ability to move crushed rock, sand, dirt, wet cement, dig spoils and other contaminated soil
- 5,000 lb Maximum Capacity

#ZLD10016 8' x 8' Dirt Tarp

#ZLD10015 10' x 10' Dirt Tarp



Grounds Flag

- 16" square blaze orange nylon reinforced vinyl flag with 1 1/2" wide lime reflective stripes. "GROUNDS" is printed in 3 1/2" black letters. Wire loop stiffener at the top and a weighted bottom.

#3GF



Worker on Line Marker

- Hi-Visibility orange marker with two reflective strips for easy visibility when working at night. Has a clear vinyl pocket for crew or company information

#3LM



Brief Relief Bag

- Individually packaged bag for liquid waste. Includes antimicrobial wipe.

#PB Case of 100

#PB10 Pack of 10



88G

Indian 5-Gallon Galvanized Fire Pump

- Kidney shaped design with contoured back support
- 4" tank opening for easy filling



85H

Weldas SWEATSopad Hardhat Sweatband 2- Pack

- Flame retardant treated fleecy cotton outer layer, air cushioned foam inner layer, hook and loop for universal fit
- Hardhat and suspension not included



85C

Snap-On Hard Hat Sweatband

- Machine Washable
- 100% Cotton
- Available in Beige or Navy



64Q

Petzl Vertex Helmet

- Unventilated outer shell protects against electrical hazards
- Six-point textile suspension adapts to shape of head
- Meets ANSI Z89.1 Type 1 Class E
- Available in White or Hi-Vis Yellow



64P

ERB Omega Wide brimmed hard hat with 6 point ratchet suspension

Available in White, Yellow, Blue and Red
Meets or Exceeds ANSI Z89.1 - 2003 Type 1, Class E, G, & C

64S- Replacement Suspension



64X

Chill-Its 6700FR Evaporative FR Cooling Bandana - Tie

- FR Evaporative Cooling Bandana: Activated polymers bring cooling relief along with FR protection
- ATPV rating of 7.1 cal/cm2



85E Benchmark Flame Resistant Hard Hat Liner

- Wicks Moisture
 - Protects your neck from the sun and covers ears
 - Flame resistant for life
- HRC 2; ATPV 9 cal/cm2

Benchmark FR Sol Shade

- 5.2 oz soft breathable blend
 - One Size Fits All (most style hard hats)
 - Protects neck and ears from the sun
- HRC 1; EBT 6.4 cal/cm2



FR Wide Brimmed Hard Hat Sun Shield (FM2804)

- Hi-Vis Mesh
 - Protects your neck from the sun
 - Fits around the brim of large brim hard hats
- ATPV 4.6 cal/cm2



Paulson Sun Shields for Wide Brimmed Hard Hats

- Great for protecting against overexposure to sun

For Bullard® Model 303/C33
For MSA V-Gard®



NSA 12 Cal PureView Arc Flash Head Protection Kit

- This 12 cal kit includes: the PureView™ faceshield with hard hat, UltraSoft® balaclava, safety glasses and storage bag

- #14U**- Complete Kit (as pictured)
- #14V** Faceshield Unit with Hard Hat Only
- #14SB** Face Shield Bag



12 Cal Arc Flash Kit; Hazard Risk Category 2

- 14K** Kit with Jacket, Bib Overalls, Face Shield w/ Hardhat, Nomex Hood, Safety Glasses, Ear Plugs and Storage Bag

- 14L** Kit with Coveralls, Face Shield w/ Hardhat, Nomex Hood, Safety Glasses, Ear Plugs and Storage Bag



ARC FLASH KITS



Arc Flash Gear Storage Bag

- 30" Length; 12" Diameter



43 Cal Arc Flash Kit; Hazard Risk Category 4

- 14M** Kit with Jacket, Bib Overalls, Hood, Safety Glasses, Ear Plugs and Storage Bag

- 14Q** Kit with Coveralls, Hood, Safety Glasses, Ear Plugs and Storage Bag



56Q

Smith & Wesson Elite Safety Glasses

- Lightweight "retro-style" design
- ANSI Z87.1
- Available in Amber, Smoke, or Clear Lens



64G

Nemesis Safety Glasses

- Meets ANSI Z87.1 and CE Certified
- Now available in 3 Styles:
 - Smoke
 - Amber
 - Clear



56B

EDGE KAZBEK Safety Glasses

- Meets ANSI Z87.1+2015
- Multi-Fit Adjustable Nosepiece
- Available in 2 Lenses:
 - Smoke Vapor Shield
 - Clear Vapor Shield



56S

EDGE Mazeno Slim Fit Safety Glasses

- Meets ANSI Z87.1+2015
- Available in 2 Lenses:
 - Smoke
 - Clear



MG4

Milwaukee Performance Safety Glasses- Fog-Free Lenses

- Meets ANSI Z87.1+
- Arc Tested following ASTM F2621
- Available in 2 Lenses:
 - Smoke
 - Clear



56G

EDGE ZORGE G2 Safety Glasses

- Meets ANSI Z87.1+2015
- Available in 3 Lenses:
 - Smoke
 - Amber
 - Clear



56A

EDGE BRAZEAU Safety Glasses

- Meets ANSI Z87.1+2015
- Available in 3 Lenses:
 - Smoke
 - Copper "Driving"
 - Polarized Smoke



56P

EDGE Reclus Safety Glasses

- Meets ANSI Z87.1+2015
- Available in 2 Lenses:
 - Smoke
 - Polarized Smoke



96C

Camo Nemesis Sunglasses with Amber Lens

- Meets ANSI Z87.1



56R

Nemesis RX™ Safety Glasses

- ANSI Z87.1 Compliant
- 'Cheaters' style with diopters for vision assistance

SMOKE LENS or CLEAR LENS

- Available in +1.5, +2.0, or +2.5



56F

Wildcat Safety Goggles

- Meets ANSI Z87.1+ Standards
- Side vents to increase airflow
- Smoke anti-fog lens



Milwaukee M18 LED Search Light (Bare Tool)

- Four Output Modes: Spot, Flood, Spot/Flood, and Strobe
- 1,250 Lumens of TRUEVIEW™ High Definition Output
 - Superior Beam Distance of 730 yards
- IP54 rating for superior water and dust resistance in all weather
- 198° Light Head Rotation



Milwaukee M18 ROCKET Tower Light/Charger

- Delivering 6,000 lumens, it fills up large areas with TRUEVIEW™ High Definition light
- Powered by M18™ REDLITHIUM Battery or Extension Cord
- 3 Independently Pivoting Light Heads
 - Max height of 7' and collapses to less than 4' for easy transportation and storage
- Batteries not included



Milwaukee REDLITHIUM USB Hard Hat Headlamp

- Spot/Flood Mode: 475 Lumens- 2 Hrs.
- Flood High Mode: 300 Lumens- 4.5 Hrs
- Internally Charges REDLITHIUM® USB Batteries through Micro-USB Port



Milwaukee USB Rechargeable Hot Stick Light

- The light has two separate LED lights providing users with 350 lumens of halo lighting. Adjustable output levels. Up to 8 hours of use off one full battery charge. Waterproof and dustproof protection.



Klein LED Headlamp

- Anti-slip silicone strap keeps lamp securely fastened to hard hat
- Two modes: spot and floodlight
 - 3 AAA Batteries Included
- Spotlight: 150 Lumens; Floodlight 50 Lumens



Klein Rechargeable LED Auto-Off Headlamp

- Rechargeable 400 lumen Auto-Off LED Headlamp has 3 modes: Boost at 400 lumens for 4 hours, Spotlight at 200 lumens for 12 hours, and Floodlight at 100 lumens for 22 hours
- Rechargeable via micro-USB port (cable included)



Klein Cordless Utility Light (Tool Only)

- Lights both the inside of the bucket and the outside working area
- Flood, spot and both Flood-Spot setting provide a variety of lighting options up to 2,500 lumens
- Powered by DeWalt 20V lithium batteries; fits up to 8 Ah batteries
- Clamp function locks to either the straight wall or corner of utility buckets for optimal positioning
 - Batteries not included



Milwaukee M18 Utility Bucket Light (Tool Only)

- 2,500 lumens with 500 yard beam distance
- Dual light head design with 180 degrees of vertical and horizontal head rotation
- 3 output modes: Spot, Flood and Spot/Flood
 - Spring loaded bucket clamp
 - uses M18 battery system
 - Batteries not included



Pole Bug LED Strobe Light & 2-Flag Holder with Flags

- Comes with Red Strobe and 2 Red Flags
 - Four flash patterns
- Powered by three "C" batteries(included)
 - Heavy Duty Strap
- 7015R: With 1 Light
- 7026R: With 2 Lights



M21

Milwaukee M18 Utility Remote Control Search Light w/ Portable Base

- Spot and flood modes
- Can be used with a permanent or portable M18™ Magnetic Base
- Wireless remote control to rotate, adjust, and power from afar
- 4,250 Lumens of TRUEVIEW™ High Definition Output
- 1,250 Yards of Beam Distance
- Batteries not included



M22

Milwaukee M18 ROVER Mounting Flood Light

- 1500 Lumens of TRUEVIEW™ High Definition Output
- Folding and Rotating Light Head
- Spring Loaded Clamp with 2" Capacity for Versatile Mounting Capabilities
- Powerful Magnetic Base
- Batteries not included



65Y

Golight with Clear Top Housing

- Portable model with suction cup and magnetic shoe
- Wireless hand-held remote included
- Peak Beam Intensity: 225,000 Candela
 - Cr5 Pentabeam Technology
- 5.5 Amps with 12v Power Source

Model: 7901GT+10203



64L

LED Golight with Clear Top Housing

- 10 High Flux LED's
- 410,000 Candela, Max Beam Distance 4,200ft
- 15' Cord with Cigarette Plug for 12V DC
- Magnetic model with wireless hand-held remote

Model: 79014GT+10203

Golight Accessories



65V

Nylon Carrying Case

- For Golight or Stryker



65W

Wireless Dash Mount Remote

- Compatible with wireless Golight and Stryker



65X

Wireless Hand Held Remote

- Replacement remote for Golight or Stryker



Golight LED Retrofit Insert

- Converts your Halogen Golight/Radiator into an LED
- Easy Install

64M

Model: 15444



Nasco Sentinel Raingear - 10oz.

ARC 2; ATPV 14 cal/cm2

- FR Polyurethane Barrier; 100% FR Cotton Knit Lining
- Fall protection access
- 3 piece hood-in-collar
- Nomex mesh ventilation system in Jacket
- Bib style trousers have quick release suspenders system
- Jacket: ANSI 107 Class 3, Level 2
- Bib Style Trouser: ANSI 107 Class E, Level 2

66E JACKET: M-3XL

66F BIB TROUSER: M-3XL

MADE IN U.S.A.

ECLIPSE™



Tingley

10.5 oz. Eclipse FR Raingear

Flame Resistant PVC on Nomex

- Yellow-Green
- ARC Rating 8.7 Cal/cm2
- D-ring access for harness
- High visibility ANSI/ISEA 107 Class 3
- FR Corduroy Collar with hood in collar construction

IMPORTED

66G Jacket S-4XL

Overall S-4XL

66H

14Z



MADE IN U.S.A.

**ML Kishigo Premium FR Hi-Vis
Long-Sleeve T-Shirt (F406)**

- 6.25 oz; Lightweight modacrylic Flame Resistant interlock knit material
- ARC 2; ATPV 9.8 cal/cm2
- ANSI Class 3
- Left Chest pocket
- M-3XL

14W



MADE IN U.S.A.

**ML Kishigo Premium FR Hi-Vis
Henley T-Shirt (F594)**

- 6.25 oz; Lightweight modacrylic Flame Resistant interlock knit material
- ARC 2; ATPV 9.8 cal/cm2
- ANSI Class 3
- Left Chest pocket
- M-3XL

14G



**Benchmark Hi Visibility Flame
Resistant T-Shirt (7033FR)**

- ANSI/ISEA 107 Type R, Class 3
- 6.2 oz 100% FR Cotton & 7 oz Modacrylic, Twaron, Llyocell
- Moisture wicking
- ATPV: 8 cal/cm2
- CAT/HRC 2
- M-3XL

MADE IN U.S.A.

14F



**Ergodyne GloWear FR
Modacrylic Vest**

- Arc Rating 4.6 cal/cm2
- 5.6 oz Modacrylic Mesh
- D-ring access slot
- Pockets: One inside, one dual pen pocket
- ANSI Class 2
- Available in S/M; L/XL or 2X/3X

94V



MADE IN U.S.A.

DragonWear Elements Nova Hoodie

- 4 way stretch inherent 12.3 oz tri-blend fabric
- Water repellant/Wind resistant
- ARC 3; 25 cal/cm2;
- M-3XL

14E



MADE IN U.S.A.

ML Kishigo FR Pullover Hoodie (F587)

- 10.5 oz Modacrylic blend Flame Resistant sweatshirt material with extremely soft fleece-like inner texture
- ARC 2; 19.7 cal/cm2
- ANSI Class 3
- M-3XL

FLAME RESISTANT CLOTHING



68Q

Ariat FR Work Crew

- CAT 2; ATPV 8.9 cal/cm2
- 6.75 oz FR Knit; 100% Cotton
- Available Silver Fox or Navy
- M-3XL Reg

50Z



100237

Carhartt 6.75oz FR Knit Long-Sleeve Henley

ARC Category 2; ATPV 8.9
100% FR Jersey Knit

AVAILABLE IN LIGHT GREY OR DARK NAVY
M-3XL



68Y

Benchmark FR T-Shirt With Chest Pocket- Light Gray

- CAT 2; ATPV 8 cal/cm2
- 6.2 oz 100% FR Cotton
- Available in sizes M-3XL

68Z



Benchmark Raglan FR T-Shirt with Chest Pocket

- CAT 2; ATPV 8 cal/cm2
- 6.2 oz 100% FR Cotton
- Available in sizes M-3XL



86A

SLU8GY

Bulwark 6oz. FR Button Front Shirt

ARC Category 2; ATPV 8.7
FR 88% Cotton/12% Nylon
AVAILABLE IN KHAKI OR GREY
M-3XL

85S



FRS160

7oz FR Twill Shirt with Pocket Flaps - Khaki

ARC Category 2; ATPV 8.6
Blend of 88% cotton and 12% high-tenacity nylon
M-3XL



5.5 oz. Drifire Arc-rated Base Layer Tee

- Dries 4x faster than a regular cotton t-shirt
- Moisture wicking, fast drying and inherent flame resistance
- Layer underneath other FR garments for maximum protection
- ASTM 1506; NFPA 70E; CAT 1; Arc Rating 4.4 cal/cm2 (ATPV)

Available in Navy or Desert Sand

13W Shortsleeve M-3XL

13X Longsleeve M-3XL



Drifire Prime FR Base Layer

- Lightweight 6.5 oz. fabric with super soft feel and 4-way stretch that allows superior mobility
- Uses drirelease®, the same patented moisture wicking technology used by the world's best athletic brands to keep you cool and dry
- CAT 1; ATPV 4.9 cal/cm2

68J Shortsleeve M-3XL

68K Longsleeve M-3XL



68L

Drifire Prime FR Base Layer Long John Pant

- Lightweight 6.5 oz. fabric with super soft feel and 4-way stretch that allows superior mobility
- Uses drirelease®, the same patented moisture wicking technology used by the world's best athletic brands to keep you cool and dry
- CAT 1; ATPV 4.9 cal/cm2 M-3XL



86H

10016173

Ariat FR M4 Low Rise Boot Cut - Clay

- CAT 2; ATPV 20 cal/cm2
- 13 oz denim; 100% cotton
- Boot cut leg opening; Medium wash; Look of light sanding and tacking



86R

10017262

Ariat FR M4 Workhorse - Flint

- CAT 2; ATPV 20 cal/cm2
- 13 oz denim; 100% cotton
- Boot cut leg opening; Medium wash; Phone Pocket; Multi tool pocket



86S

10017226

Ariat FR M4 Workhorse - Charcoal

- CAT 2; ATPV 12.7 cal/cm2
- 11 oz canvas; 88% cotton; 12% nylon
- Boot cut leg opening; Phone Pocket; Multi tool pocket; reinforced hem guard

FLAME RESISTANT CLOTHING



86M



FRB159

Carhartt Dark Navy FR Midweight Canvas Pant- Loose-Fit

CAT 2; APTV 12

- 8.5-oz, FR Canvas

- 88% Cotton/12% high tenacity nylon

- Cell phone pocket on left leg and utility pocket on right leg

86E



FRB13

Carhartt FR 11.75 oz. Denim Dungaree

CAT 2; APTV 16

Flame-resistant
midweight denim
100% Cotton



83Z

104633

Carhartt Flame Resistant Force Rugged Flex Relaxed Fit Utility Jean

CAT 2; EBT 12 CAL

- 11 oz; 69% Cotton, 29% Modacrylic, 1% Elastane,
1% Aramid FR denim

- Multiple tool and utility pockets

- Built to move with Rugged Flex stretch technology

86G



FRB100

Carhartt FR 11.75 oz. Jean Relaxed Fit - Straight Leg

CAT 2; APTV 16

100% Cotton
flame-resistant denim



Carhartt FR Duck Active Jac
 CAT 4; ATPV 54
 - 13-ounce, 100% FR duck
 - 11.5-ounce FR quilted twill lining/FR
 modacrylic batting insulation for warmth
 M-3XL



**Carhartt FR Duck Vest -
 Sherpa Lined**
 CAT 3; ATPV 32
 - 13-ounce, 100% FR duck
 - FR sherpa lining
 - Two large front pockets lined with FR
 Sherpa for warmth and comfort
 M-3XL



**Ariat FR
 DuraLight Stretch Canvas Jacket**
 ATPV 44 cal/cm2; CAT 4
 - 9 oz FR polar fleece lining
 M-3XL



**DragonWear 11oz
 Elements Flak Jacket**
 FR Fabric - CAT 3; 28 cal/cm2
 - Full zip hoodie with 3 panel hood designed for comfort
 under hardhats; Built-in fleece Balaclava for optional
 coverage
 M-XL
 2XL-3XL

FLAME RESISTANT CLOTHING

94Z



Benchmark FR 12 oz Hooded Sweatshirt (Navy)
 - ARC 2; ATPV 20
 - 50% Modacrylic, 50% Cotton blend
 sz. M-3XL

MADE IN U.S.A.

88X



Ariat FR Rev Pullover Hoodie
 - CAT 2; ATPV 22 cal/cm2
 - 10 oz FR Fleece; 100% Cotton
 M-3X Reg

67L



Carhartt FR Force Original Fit Midweight Hooded Sweatshirt - Granite Heather
 - CAT 3; ATPV 25 cal/cm2
 - 10.5 oz, 40% Cotton/35% modacrylic/15% viscose/8% aramid/2% antistat FR fleece
 M-3X Reg

104983

67N



Carhartt FR Force Original Fit Midweight Hooded Sweatshirt - Navy
 - CAT 3; ATPV 25 cal/cm2
 - 10.5 oz, 40% Cotton/35% modacrylic/15% viscose/8% aramid/2% antistat FR fleece
 M-3X Reg

104983

69K



DragonWear Elements Cyclone Hoodie
 - 4 way stretch inherent 12.3 oz tri-blend fabric; Grey with contrast stitching
 - CAT 3; 28 cal/cm2
 M-XL
 2XL-3XL

MADE IN U.S.A.

94C



Benchmark FR 12 oz Hooded Zip-up Sweatshirt (Navy)
 - ARC 2; ATPV 20
 - 50% Modacrylic, 50% Cotton blend
 sz. M-3XL

MADE IN U.S.A.



85W

Benchmark FR Knit Beanie

EBT 36 cal/cm2; HRC 3

- Double layered knit hat has a folding brim for additional warmth around the ears



85V

DragonWear Livewire Beanie

CAT 3; 32 cal/cm2

- Lightweight warmth and designed to be worn comfortably under a hardhat



67J

Carhartt FR Knit Watch Hat

CAT 2; 19 cal/cm2

- Dark Navy; Stretchable rib-knit



85T

N-Ferno Modacrylic Blend FR Fleece Balaclava

ATPV of 10.6 cal/cm2

- Stretchable modacrylic fleece keeps head and neck comfortable



84X

N-Ferno FR Balaclava Face Mask - Black

ATPV of 20 cal/cm2

- Hinged design for versatile wear from neck gaiter to ski mask
- Breathable warmth and moisture-wicking



85M

DragonWear Cold Warrior Balaclava

CAT 3; 28 cal/cm2

- Full head and facial protection extending below the neckline for extra coverage



69F

Nomex Blend Hood

- Nomex/Lenzing Blend
- Double Layer
- HRC 2; ATPV 10.1

KN-51-NFPA



3049FRB

Benchmark FR Face Muffler Gaiter - Beige


HRC 1, Arc Rating 6.4 cal/cm2
- 5.2 oz



85R

DragonWear Yukon Fleece Neck Gaitor

- CAT 4, Arc Rating 40 cal/cm2
- Eliminates cold drafts at the neck and can be pulled up to keep your lower face warm



Electric Linemen DVD From the History Channel Series "Tougher In Alaska"

- History presents this captivating look into the harsh and dangerous job of Alaska's Electric Linemen
- Join host Geo Beach as he ventures into the Alaskan wilderness to discover what it takes to keep the power on in a state where more than half of its people live off the grid and plunging temps snap even the strongest power lines.
- 50 minutes


91U



Light Up the World Children's Book

- Ignite your child's imagination and give them a glimpse into life as a lineman
- Hardbound
- Written by Sarah Reijonen


91W



73B

Lineman- The Unsung Hero Children's Book

Linemen work very hard to keep our power on. This book is a token of appreciation to all linemen. Enjoy the detailed illustrations and fun text. Share it with the children in your life—share it with everyone!



The American Lineman

- by Alan Drew

- Honoring the evolution and importance of one of the nation's toughest, most admired professions
- 519 Pages; Hardback


73J



High Tension

- By William Wister Haines
- Also includes 5 short stories of American line work
- 271 Pages; Hardback

73H



Slim

- By William Wister Haines
- Slim movie was based off this novel
- Great reading for linemen and anyone interested in linework

73E



9Y

Lineman Decal

- Only white portion above
- Perfect for tinted windows
- 3 1/2" Wide x 5" High



Lineman Decal

- 2 Sizes Available

9W

2 3/8" Wide and 4" Tall

9X

3 1/2" Wide and 6" Tall



74F

Klein 17" BBQ Set

74M



The Lineman Key chain

74G



Klein Beverage Opener

31K



Buckingham Mini Bucket Bag

Great for your car, office or home.
5" diam x 7" Tall

31U



Klein Mini Bucket Bag with Leather Bottom

- 6" Height and 4.5" Diameter
- Great for pencils, pens and other accessories

36F



Rapid Rope Canister and Cartridge

- A convenient and compact way to store and access rope when you need it.
- Cut-Ready Dispenser (Built in blade)
- 120' of Rope; 1100 lb Tensile Strength
- 6" Height and 2 3/4" Diameter
- Weighs only 1 lb.

Refill Cartridge Only

36G



Lineman Cap Holder
9" x 21" Plasma Cut



Lineman Key Holder
7" x 21" Plasma Cut



48-22-1520

- Milwaukee FASTBACK Folding Knife**
- 7.5" Overall Length
 - Belt Clip
 - Press and flip mechanism providing easy, one-handed opening



48-22-1530

- Milwaukee FASTBACK Spring Assisted Folding Knife**
- 7.48" Overall Length
 - Belt Clip
 - Spring assisted mechanism and flipper for one-handed opening



48-22-1540

- Milwaukee FASTBACK 5-in-1 Folding Knife**
- 7.87" Overall Length
 - Belt Clip
 - Press and flip mechanism providing easy, one-handed opening
 - Has bottle opener and fold-out 1/4" bit holder with reversible phillips and slotted bit



44142

- Klein Tools Compact Pocket Knife**
- 3 1/2" Blade
 - 7" Overall Length
 - Pocket Clip
 - Dual Thumb Studs for one hand open



44220

- Klein Pocket Knife Black Drop-Point Blade**
- 3 1/2" Blade
 - 8 1/4" Overall Length
 - Pocket Clip
 - Dual Thumb Studs for one hand open



44222

- Klein Pocket Knife Realtree Xtra Camo**
- 3 1/2" tanto-style blade
 - 8 1/8" Overall Length
 - Pocket Clip
 - Dual Thumb Studs for one hand open



**Klein Polished Stainless Steel Knife
With Rosewood Inlay Handles**

- # 74P 1 5/8" Blade
- # 74O 2" Blade
- # 74N 2 5/8" Blade



44213

- Klein Bearing-Assisted Open Pocket Knife**
- Bearing-assisted opening mechanism enables a smooth, easy deployment of the blade
 - 3.4" Blade
 - 8" Overall Length
 - Pocket Clip
 - Ambidextrous flip lever for easy one finger opening



New Era Stretch Mesh Lineman Logo Cap

- Chocolate/Khaki
- Stretch Fit

Sizes:
S/M (6 7/8- 7 1/4)
M/L (7 1/8- 7 1/2)
L/XL (7 3/8- 7 3/4)



New Era Stretch Mesh Lineman Logo Cap

- Black/Black
- Stretch Fit

Sizes:
S/M (6 7/8- 7 1/4)
M/L (7 1/8- 7 1/2)
L/XL (7 3/8- 7 3/4)

***87J and 87K hats run on the large side; if you are borderline it is recommended you round down**



Lineman Logo Cap- Black/White

- Cotton twill front panels and visor with mesh back panels
- Adjustable plastic snap backstrap



Lineman Logo Cap- Black/Charcoal

- Cotton twill front panels and visor with mesh back panels
- Adjustable plastic snap backstrap



Farwest Line Specialties Cap- Black/White

- Cotton twill front panels and visor with mesh back panels
- Adjustable plastic snap backstrap



75P

Lineman US Flag Bottle Opener with Wood Backing

10" x 16"



75Q

Journeyman Lineman Bottle Opener with Wood Backing

10" x 16"

K16



AESEB1

Klein Bluetooth Jobsite Earbuds

- Earbuds provide high-quality stereo audio while protecting your hearing with an NRR (Noise Reduction Rating) of 28
- Trusted Bluetooth® 5.0 technology offers ultra-stable connection, faster one-step pairing and universal compatibility
- Built-in microphones allow for crystal-clear calls in busy environments and voice assistant

74W



AEPJS1

Klein Wireless Jobsite Speaker

- Connects wirelessly via Bluetooth or a wired auxiliary input
- 32.8 ft connectivity range (in open space) 10-Hour battery life
- Includes 1/8" (3.5 mm) stereo auxiliary cable and micro USB-to-standard USB charging cable
- 3 7/8" x 3 1/2"

73F




The Lineman's Pocket Reference (56 pgs.)

Compact reference packed exactly with the information linemen need most

- Essential safety data; NESC clearances; safe working loads; weights of wood poles and other popular construction materials; conversion tables; math laws and formulas

77A




Distribution Transformer Handbook (80 pgs.)

Transformer facts including:

- Connection diagrams
- Transformer formulas
- Safety Tips
- Grounding Information
- Installation procedures


77F



The Lineman's and Cableman's Handbook

- Over 1000 pages
- The industry "bible" since 1928


77C



The Lineworker's Rigging Handbook (277 pgs.)

- Knots linemen should know
- Splicing techniques
- Using slings to lift transformers
- Estimating tension (lines, guys)
- Instructive Illustrations

73G



Underground Distribution (312 pgs.)

Explains the job skills lineworkers need to safely instal and maintain underground distribution systems

- How to pull cable
- Cable Splicing procedures
- Troubleshooting
- Safe switching procedures
- Entering confined Spaces

77R



Transformers for Linemen (184 pgs.)

Everything a lineman needs to know about distribution transformers

- AC circuit concepts, transformer formulas, delta and wye connections, phasing and paralleling banks, how to energize transformer safely and more

AC Minimum Approach Distances

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.0	3.0	3.0
Exposed live parts	3.0	3.0	3.0
Grounded parts	1.0	1.0	1.0

Minimum Approach Distances for 10-500 kV systems			
Minimum Approach Distances	10 kV	15 kV	20 kV
Unexposed live parts	3.		

OSHA AC Live-Line Work Minimum Approach Distances

Available in 77L-8" x 6" Decal

or 77LL-18 x 24" Poster

77H



Pocket Lineman

- Connection diagrams, formulas, and much more!

77J



Pocket Rigger

- Sling tensions, pole weights, rope capacities, friction, haul line tension, and more

77K



Pocket Transformer

- Connection diagrams, 3ph output voltages, and more




Folds and fits in your Wallet!



Buckingham 105RSK1 - Suspension Trauma Rescue System with FR Pouch

Designed to alleviate the effects of suspension trauma. Allows a victim to immediately deploy a body support system that allows for improved blood circulation until rescue. Attaches to a full body harness and is fully adjustable.



Buckingham 3813D1Q6 - Hurt Man Bucket Truck Rescue System

- The bag allows you to deploy the system components from the bottom of the bag rather than reaching all the way to the top of the bag, saving you valuable time in a rescue situation.
- Designed to keep water out of the system allowing it to be permanently mounted to the boom.
- Pulley system gives you a 4:1 mechanical advantage, allowing for an easier rescue.
- 7/16" diameter rope allows for up to a 20' lift and reduces twisting of the pulleys.



Bashlin 700FP Boom Mount Rescue Pack

- Designed to mount to the boom for lifting an injured worker from an aerial basket
- Pouch includes 75' of 3/8" rope, a pair of blocks, carabiner and storage pouch



The Buckingham Rescue Buck with harness is ideal for pole top rescue training, retrieval training, and fall protection testing. 694

55lb Box Buck Fill for Rescue Buck
Qty 3 Recommended to fill Rescue Buck
14X 694F1



Buckingham 301SRK-50 Self Rescue System

- Lightweight, compact design
- Comes with 50' rope
- Weight limit 310 lbs.
- Bag material withstands 40cal/cm2 electric arc exposure



Buckingham Retrieval Harness

- A full body harness that features a reflective nylon dorsal attachment and easy access reflective loops at the shoulders, hips, pigtail and neck area
- Meets ASTM F887
- Available in M, L or XL



Buckingham 301SRKQ2-65 Self Rescue System for 2-Man Bucket

- With 2 descenders
- Comes with 65' rope
- Rated up to 440 lbs.
- Bag material withstands 40cal/cm2 electric arc exposure



- 488PR - SuperSqueeze Rescue Trainer**
- This unique system allows hi-vis orange cut rope to be stowed in a bag that is attached to the rescue mannequin. After the rescuer cuts the rope and lowers the mannequin, simply pull additional rope from bag, run it through the BuckGrab™ and tie a stopper knot in the end of the rope. Includes 25' of hi-vis cut rope.

78J Extra Rope Only: 25ft. 488AR-25

FARWEST LINE SPECIALTIES

830 E. Parkridge Ave.
Corona, CA 92879



CHECK OUT OUR ORDER ON-LINE WEBSITE

WWW.FWLSP.COM

PHONE ORDERS & CUSTOMER SERVICE

800-466-7153 OR 805-466-7163